St. Louis County (SW) West Lake SLF

JOHN ASHCROFT

Governor

RON KUCERA



STATE OF MISSOURI DEPARTMENT OF NATURAL RESOURCES

DIVISION OF ENVIRONMENTAL QUALITY
ST. LOUIS REGIONAL OFFICE
10805 Sunset Office Drive, Suite 100
St. Louis, MO 63127-1017
314-822-0101
Fax No. 314-822-0943

Division of Energy
Division of Environmental Quality
Division of Geology and Land Survey
Division of Management Services
Division of Parks, Recreation,
and Historic Preservation

December 30, 1992

Mr. Glenn A. O'Bryan Laidlaw Waste Systems, Inc. 13570 St. Charles Rock Road Bridgeton, MO 63044

Dear Mr. O'Bryan:

Enclosed is a report of an inspection conducted by Mr. Joe Trunko of my staff. The report contains recommendations which the inspector has determined are warranted based on his findings at the facility.

Please review the report and implement the recommendations presented. Should you have any questions or comments, please contact the St. Louis Regional Office at (314) 822-0101.

Sincerely,

ST. LOUIS REGIONAL OFFICE

Robert 5. P. Eck Regional Director

RSPE/JOF/lv

Enclosures

c: SWMP Brad Bomanz, St. Louis County Health Dept., Solid Waste Miles Stotts, Laidlaw Waste Systems, Inc. Dennis Wike, Laidlaw Waste Systems, Inc.

SANITARY LANDFILL INSPECTION REPORT

FACILITY

West Lake (Bridgeton) Sanitary Landfill Laidlaw Waste Systems, Inc. St. Louis County MDNR Permit #118912

INTRODUCTION

On December 29, 1992, the above referenced facility was inspected for compliance with regulations pursuant to the Missouri Solid Waste Management Law. Messrs. Joe Trunko and Terry Hoevelkamp represented the Missouri Department of Natural Resources (MDNR), St. Louis Regional Office. Also present was Mr. Frank Dolan of the MDNR, Solid Waste Management Program. Ms. Sue Taylor and Mr. Brad Bomanz represented the St. Louis County Health Department. Mr. Glenn A. O'Bryan represented the facility.

FINDINGS

- 1. A large amount of exposed waste was observed at the facility.
- 2. Erosion gullies were observed in the wet-weather area.
- 3. An underground fire was occurring in the wet-weather area.
- 4. The new flare has not been constructed.
- Regulated quantities of hazardous waste have been disposed of at this facility.

DISCUSSION

A large amount of exposed waste was observed in the wet-weather area, along the quarry walls and in the north area of the active pit. Exposed waste may contribute to the generation of odors at this facility. Efforts must be made to ensure that at least six inches of compacted cover is applied daily and that inactive areas are recovered and regraded as needed.

As per the approved engineering report, intermediate cover (one foot of compacted soil) is not required at this facility until the landfill reaches an elevation where surface water can be drained to the natural ground surface. The lack of intermediate cover on the inactive sections of the landfill may also be contributing to odor generation. Consideration should be made by Laidlaw to apply intermediate cover, especially if odor problems persist after completion and start up of the new gas extraction system. The intermediate cover could be stripped off when landfilling resumed in an inactive area. A permit modification request must be submitted to the SWMP if this is pursued.

St. Louis County Westlake SLF Inspection Report Page 2

Numerous erosion gullies were observed on the south slope of the wet-weather area. The occurrence of erosion in this area is common due to the steep slope and the large amount of surface water that drains into this area. Actions to minimize the erosion, such as the establishment of vegetation and/or terracing, should be taken.

An underground fire was burning in the wet-weather area near the quarry wall.

Additional cover had been placed along the quarry wall in order to minimize the
flow of oxygen into the fill. Mr. O'Bryan stated that additional actions would
be taken (such as grouting the walls) should the fire continue.

Installation of the new flare has been delayed due to zoning restrictions by the City of Bridgeton. As a result of this delay, Laidlaw has decided to relocate the flare to an area that will not require zoning approval (area of existing flare station). Due to the continued odor problem at this facility, existing flare station), but to the flare be completed as soon as it is imperative that construction of the flare be completed as soon as possible.

On August 5, 1992, approximately 10 cubic yards of filter waste from the P.D. George Company was dumped at this facility. A hazardous waste determination performed by P.D. George has shown that the filters contained cresols above the regulatory limit as specified in 40 CFR 261. Laidlaw has developed a plan for removal of the waste. Selection of a consultant for coordinating the project is near completion. As per a letter dated December 14, 1992, from Glenn is near completion. As per a letter dated December 14, 1992, from Glenn O'Bryan to the Department, a timeline for removal of the waste will be obsolided to the Department by January 31, 1993. The project is scheduled to be completed by March 31, 1993.

RECOMMENDATIONS

- Additional cover must be applied to all areas of exposed waste. Efforts
 must be made to ensure that at least six inches of compacted cover is
 applied to the active face on a daily basis. The regrading and recovering
 of fill areas must be performed on a regular basis so that erosion of cover
 material is minimized and solid waste is not exposed.
- Consideration should be made by Laidlaw to apply intermediate cover to inactive areas at the facility should odor problems persist.
- The south slope of the wet weather area should be terraced and/or vegetation established so that erosion on the area is minimized.
- 4. Continue with efforts to eliminate the fire in the wet-weather area.
- 5. By February 1, 1993, construction of the new flare must be completed and the gas collection system must be operable. Failure to complete construction of the flare by this date may result in the initiation of enforcement action by the Department.



MISSOURI DEPARTMENT OF NATURAL RESOURCES DIVISION OF ENVIRONMENTAL QUALITY SOLID WASTE AND RECOVERED MATERIALS DATA SHEET

West Lake (Bridgeton) Sanitary Land Fill REGIONAL OFFICE			FICE	INSPECTOR JOSEPH L. Trunk		
12-29-92 St. Louis				1 sept 1-1 water		
IG FEES		garine a region (1994) (1997) - St. Agendar (1997) (1997) - T. L.		I WHITE GOODS		
00.82 ORA	compacted	PICKUP LOAD		N/4		
\$ 30.00	Sound waste	CARLOAD		TIRES N/A		
N 10.50	in man			r <u>Markania (h. 1986). A sara da markania da markania da markania da markania da markania da markania da marka</u>		
	TYPE OF	ere (Kultin Kultin	AMOUNT	AMOUNT RECYCLED/MONTH		
LICABLE *	MATERIAL		RECOVERED/MONTH	CUBIC YARDS OR TONS		
regeratore Leonologica	RECOVERED	<u> </u>	CUBIC YARDS OR TONS	1		
	ALUMINUM					
MA _	Cans	: : 	and the second s			
	Scrap		The state of the s	The second secon		
		13		· · · · · · ·		
{:·		, l	Mo			
	OTHER METAL		ar of the second			
- 	Ferrous					
	Non-Ferrous			te te		
	PAPER					
ing kayatan d	Newspaper		er er gereger fra 1900 gant er bereit 190 0, er e			
	Corrugated		<u> </u>			
A A CONTRACTOR	Computer/White					
	Mixed			The state of the s		
				- 1		
	GLASS	.				
	Clear	ŀ	Acceptance of the second secon			
7	Mixed	ŀ				
		<u>.</u>				
				· •		
	PLASTIC	-	The second of the second second second			
	Milk Jugs					
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Soda Bottles					
<u> </u>	Mixed					
l.						
	CAR BATTERIES		The state of the s			
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		4			
.]		/	-	to the second se		
	TIRES					
		*	1.4	,		
				gradient state of the state of		
	WHITE GOODS			•		
[į.	·	•		
1	COMPOST FROM	,				
-	YARD WASTE	'				
50 XVA 1	YAHU WASIE		and the second of the second	1 · · · · · · · · ·		
	COMPOST FROM	,				
V	SOLID WASTE		And the second s	The second secon		
arrive a service and	Jorio Milasta		and the San	Committee of the state of the s		



MISSOURI DEPARTMENT OF NATURAL RESOURCES DIVISION OF ENVIRONMENTAL QUALITY

	and the second second		and the second second	
SANITARY		****		
CARITADV	IABITELL	INCOEPTI	AN ALIE	OVIDE
JAKULADI	LANGUITIE			

TYPE OF INSPECTION Decenterly

L CENEDAL MECOL	IATION		(HVI)L	14:			····
I GENERAL INFORM	MATION	DAYSWEEK ODEN	No. Anno 1980 -	Trais of Applicati	A CONTROL OF THE CONT		
(3-39-9	à	DAYSWEEK OPEN -4100	in-F)	TIME OF ARRIVAL	9130 am		
WEATHER		1	S.+ /		TEMPERATURE		
Overcast	· luet			. N	50°	i .	
FACILITY NAME	<u>,</u>			COUNTY	PERMITIN		
Westlake Co	Sridgeton) S	schiltery Lands	RI	St. Louis	Š	18315	<u> </u>
owner Laidlaw Was	te Systems	Luc			(314) V139-	19 19	
ADDRESS			CITY	The state of the s	STATE Z	P CODE	
13570 St. CI	urles Rock	Road	Brid	lgeton)		<u>6304</u>	1
	as owner				TELEPHONE NUMBER		
ADDRESS		Consequence of the design of t	CITY	<u> </u>	STATE Z	IP CODE	<u> </u>
TO SECTION AND THE SECTION OF SECTION AND THE SECTION OF SECTION AND THE SECTI	We stand to			The state of the s		1	e da la
II REMAINING LIFE	OF LANDFILL	<u> </u>	ARE	A SERVED	Weisels de Migdele (Mangele et al.) Spiral in the properties of the control of		<u>disperansi bilik bili.</u> Yangan bilik bilik bilik
A. Estimated quantity		ed # 36,000		Cities:	The state of the s	* *	
yards or tons/week		YV		We have the control of the control o	Virginia (S. 1868)	At Lea	c
B. Estimated life of re				24. Penizi	Various monteil	bert Cie	ب
3.200	Region was a second	en e	В. С	Counties:		'','''	
C. Fixed operating ter	m date, 11-	18-95,			s, St. Charle	S	
NOTE Chack all eith	sections SAT-Satis	lactory or UNIS-Hesstlete	iclory If non	oscant doorshoul Me	iolations under "Remarks."	PAT	likio
10 CSR 80-2.020 PERMIT I					iolations under Hemarks.	<u> </u> SAT	UNS
		ED PER APPROVED TERMS		The second section of the second section is the second section of the second section section is a second section of the second section	<u>ali terre erat, eta gi etangunan diddugi sa sa s</u> Anna gipapa pagi territor pasa general pagi a sada	7	1.12 × 1.
10 CSR 80-2,060 CERTIFIE				113	entre dell'acceptante della companya della companya della companya della companya della companya della company Alla companya della c Alla companya della	J	l
	LID-WASTE TECHNIC				(Joe Durako)	T ./	T
10 CSR 80-3.010 SANITAR		er e e		The second secon	SQUE SVINIS	<u> </u>	
(2) SOLID WASTE ACCEPT	0.76, 50.76 0. 2.06 1 1		ON SOLID G	ROUND:			F. 19
The state of the s	ANIMALS COVERED I		,,			1 /	1
(3) SOLID WASTE EXCLU	· · · · · · · · · · · · · · · · · · ·	10000 0000					
	Anna Maria Maria Maria Maria Maria	10-15-16-16 - F - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	IT IN ACCORI	DANCE WITH APPROVED PL	ANS.	T ./	i i
		WASTE NOT APPROVED IN				1./	
	ECIAL WASTE DISPO	and the second of the second of the second	A CONTRACTOR OF THE CONTRACTOR				
<u> </u>		NG EXCLUDED WASTES.				Y	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	OR SCREENING AND	REMOVAL OF EXCLUDED	WASTES.				3.44.17
		PIT AND COVERED WITH F	25 26 26 25 26 2	F COMPACTED SOIL.			774
	***************************************	SECTION (3)(A) OF THIS R			O		1
(4) SITE SELECTION (4)(1 /	
	and the second s	ALTERNATE SANITARY LAI	atem and attended to				
NAME:		n in ere min kamesa, gelen elektre i dari. Tarih di	· visk i symysii ·	e i provincia de la compania de la c La compania de la co	Na ang Marana ang ang ang ang ang ang ang ang ang		
(5) DESIGN (5)(C)1. CO	NSTRUCTION AND O	PERATION OF THE SITE IN	ACCORDANG	CE WITH PLANS AND SPECI	FICATIONS.		
and the second s	OOT BUFFER ZONE I	MAINTAINED.	- 	and the first of the second of	and a second	/	F
	ANUAL AVAILABLE.	Table Comments	1			1	I
(6) SURVEY CONTROL	en er er er er e	en e			······································		
(6)(C)1. BOUNDARY MA	RKERS, BENCHMARKS	HORIZONTAL CONTROL ST	ATIONS, à CO	NSTRUCTION STAKES CLEAR	RLY MARKED & IDENTIFIED.		
(6)(C)2. MISSING OR D	ISPLACED BENCHMA	ARKS OR HORIZONTAL COL	NTROL STAT	IONS REESTABLISHED.	in the state of th	/	
(6)(C)3 MISSING OR D	ISPLACED CONSTAL	CTION STAKES REESTABL	ISHED,				
(6)(C)4. MONUMENTS	AND BOUNDARY MAI	RKERS PLACED PRIOR TO I	RÉCEIVING A	UTHORIZATION TO OPERA	TE.		
	ON STAKES MARKING	THE ACTIVE AREA PLACE	D PAIOR TO	DEPOSITION OF WASTE.		/	<u></u>
(7) WATER QUALITY		errado do grandares como como en el como de la como en el como en Carlo de la como en el	· marka kata ini ji		is not considered and a considered by	<u> </u>	
				NG TO PROMOTE RUNOFF WITH	OUT EXCESSIVE EROSION. (4)	: 100, 2, 7, 77 + 100, 200, 100, 100, 100, 100, 100, 100,	/
(7)(C)2. CONTACT BET	WEEN WATER AND S	OLID WASTE MINIMIZED.		and the second s	rdeng padadag separatis mangganitang separatis		.(
		DLLED ON-SITE AND NOT ALLO	WED TO DISCH	IARGE OFF SITE OR DISCHARGE	EINTO WATERS OF THE STATE	1 /	<u> </u>
(8) GROUND-WATER MON	ITORING			a digitar da sa			
	ER-MONITORING WE	LLS OPERATIONAL PRIOR	TO ACCEPT.	ANCE OF WASTE.	Andrew Committee	/	
(9) AIR QUALITY		and the second s	1 1111 1111				
	OLID WASTE PROHI	BITED UNLESS A BURNING	PERMIT IS C	BTAINED.		/	
10 780-0354 (3-90)			· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·		7.78	* * . *

		SAT	UNS					
(10) GAS CC	INTROL (10)(C)1. DECOMPOSITION GAS CONTROL SYSTEMS IMPLEMENTED AS NECESSARY.							
(10)(C)2.A.	METHANE NOT ALLOWED TO CONCENTRATE IN BUILDINGS ON SITE ABOVE 25 PERCENT LEL FOR METHANE.							
(10)(C)2.B.	METHANE NOT ALLOWED TO CONCENTRATE IN THE SOIL AT THE PROPERTY BOUNDARY ABOVE 5 PERCENT LEL FOR METHANS.							
(10)(C)3.	DECOMPOSITION GAS MONITORING RESULTS SUBMITTED TO THE DEPARTMENT AS REQUIRED BY PERMIT.	./						
(11) VECTO								
(12) AESTHE								
(12)(C)1.	LITTER CONTROL DEVICES UTILIZED AS NEEDED, LITTER COLLECTED & INCORPORATED INTO THE ACTIVE CELL AT THE END OF	_ /						
(islohu								
(dayto)a:	EACH DAY OR PLACED IN CONTAINERS.							
(12)(C)2.	WASTES EASILY MOVED BY WIND COVERED AS NECESSARY.							
(12)(C)3.	ON-SITE VEGETATION CLEARED ONLY AS NECESSARY.							
(12)(C)4.	SALVAGED MATERIALS REMOVED DAILY OR STORED IN AESTHETICALLY ACCEPTABLE CONTAINERS.							
(13) COVER	(13)(C)1. DAILY COVER APPLIED.		in the state of th					
(13)(C)2.	INTERMEDIATE COVER APPLIED.							
(13)(C)3.	FINAL COVER APPLIED.	/						
(13)(C)4.	FINAL SIDE SLOPES NOT TO EXCEED 33.3 PERCENT.	V						
(13)(C)5.	VEGETATION ESTABLISHED WITHIN 180 DAYS OF APPLICATION OR REGRADING OF COVER.	1						
(13)(C)6.	REGRADING AND RECOVERING AS NECESSARY. (3)							
(14) COMPAC	TION (14)(C)1. SOLID-WASTE HANDLING EQUIPMENT ON SITE AND OPERATED AS NECESSARY.							
	SOLID WASTE TO BE COMPACTED, SPREAD IN LAYERS NO MORE THAN 2 FEET THICK, & CONFINED TO SMALLEST PRACTICAL AREA.							
(14)(C)1.B.	WASTE COMPACTED TO SMALLEST PRACTICAL VOLUME.							
(14)(C)1.C.	COVER COMPACTED AS MUCH AS PRACTICAL.							
(14)(C)2	PREVENTIVE MAINTENANCE PERFORMED ON EQUIPMENT.							
			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1					
(14)(C)3.	SOLID WASTE NOT DISPOSED OF IN WATER							
	(16)(C)1. FIRE EXTINGUISHERS PROVIDED.							
(15)(C)2.	ALL FIRES IN WASTES BEING DELIVERED AT THE WORKING FACE OR WITHIN EQUIPMENT EXTINGUISHED.							
(15)(C)3.	COMMUNICATIONS EQUIPMENT AVAILABLE.	/						
(15)(C)4.	SCAVENGING PROHIBITED:	1	<u> </u>					
(15)(C)5:	CONTROLLED ACCESS TO SITE BY ESTABLISHED ROADWAYS & LIMITED TO HOURS WHEN OPERATING PERSONNEL ARE ON DUTY.	/						
(15)(C)6.	TRAFFIC CONTROLLED AND DIRECTED TO DISTINGUISH DISPOSING POINTS.							
(15)(C)7.	SITE DUST CONTROLLED.							
(16) RECORE	OS (16)(C)1.A. RECORDS OF MAJOR PROBLEMS AND COMPLAINTS.		47					
15 man 19 20 0 1 1 2 1 1 1 1 1 1								
	A. LEACHATE SAMPLING AND ANALYSES,	10 1 V 1 V 1						
	B. GAS SAMPLING AND ANALYSES.		1.					
i I	C: GROUND- AND SURFACE-WATER ANALYSES.							
30.5	RECORDS OF VECTOR CONTROL EFFORTS.		· · · · · · · · · · · · · · · · · · ·					
* * * * * * * * * * * * * * * * * * * *		-						
1 127 1 1 1 1 1 1	RECORDS OF DUST- AND LITTER-CONTROL EFFORTS.		· · ·					
	RECORDS OF QUANTITY OF WASTE HANDLED.	/						
(16)(C)1,F ₋	RÉCORDS OF DESCRIPTION, SOURCES, AND VOLUME OF SPECIAL WASTES LISTED IN SUBSECTION (3)(A).	/						
	GN SPECIFICATIONS							
(7)(C)3.	LEACHATE COLLECTION SYSTEM PROPERLY INSTALLED AND OPERATED.							
(7)(C)4.	LINER CONSTRUCTED BY APPROVED DESIGN SPECIFICATION.	/	<u> </u>					
(8)(C)1.A.	GROUNDWATER MONITORING WELLS INSTALLED.							
(13)(C)7.	BORROW AREAS RECLAIMED.	1						
REMARKS (1) 10 yel	s of crescl waste. From PD George has been disposed of at the facility. Item of the flate has been changed to avoid zoung deloys. Countration must be completed used which observed along quarry units. The wetweather area and in north section of actuation south side of not weather area. I should be terriced and/or seeded.	C. ah	102					
(A) LOW	the the three has been congent to those section delois, each me that he complete.	we with	1.75					
المنا ريي	1029 most observed and directly opens. In the mediate week me in mount of sections	in the						
(4) scorio	must south side of wet wellor area — should be terraced and/or seeded.	: <u></u>						
The second secon	NER/OPERATOR:	erengere e						
This inspection of your facility has been conducted under the authority of Sec. 260.225.1 (9) RSMo. The COMPLIANCE EVALUATION								
department representative has marked those items found in violation of the applicable environmental laws and regulations adopted thereunder pertaining to your facility. Your signature below or that of your agent.								
acknowledges that you have been notified of the deficiencies and have received recommendations and								
specific time frames for corrective action(s). If future inspections determine these violations persist, the Department may proceed with more formal enforcement procedures as authorized under Scotlons 260.230 Motice of Violation Issued; / / /								
and 260.240 RSMo, including but not limited to the assessment of penalties up to \$1900 per day for each								
day, or part thereof, the violation occurred. If any questions occur following your receipt of this inspection Return to Compliance By: 1/31/12 record, please of near the inspector named below.								
	The state of the s	<u></u>	1					
SIGNATURE OF	bough de Tumbro) St-Louis By Mail	<u> </u>						
OFFICE ADDRES	USE OFFICE DO. St. Louis, Ma 63127 (314) 522-0101	- 11 - W. T.						
14805 SV	10805 Sunset Office On, St. Louis, Ma 63127 (314) 822-0101							

ST. LOUIS COUNTY HEALTH DEPARTMENT WASTE MANAGEMENT SECTION

SANITARY LANDFILL SURVEILANCE RECORD

Date: 12/29/92 Days/Week Open: 6 Estimated amount of solid waste coming through get	6,
Dete: 12/29/32 Days/week Open. Name of Facility: Laidlay Waste Systems (Sanitary). Compacted Loads 42,250 yds./wk.	tons/wk.
6/22/03 vds./vk.	tons/wk.
Permit No.: U419 Expires: U722199 Noncompleted Loads	
Owner: Laidlaw Waste Systems Inc.	
Owner: 13570 St. Charles Rock Rd. Estimated volume of remaining landfill covered by ep	Dioase augmeening.
Bridgeton, MO 63044 plansacro(s) 11.5 years	errite di i

Ordinance 13,320 Chapter 607 Compliance Status

Check all sections: SAT-Satisfactory: UNS-Unsatisfactory; . Area(s) requiring additional attention.

Section Yumber	Satisfactory Compliance Operating Procedure	SAT	•	UNS	Section Number	Satisfactory Compilance Operating Procedure	SAT	•	UNS
FACILITY	PLAN				WATER C		19.7.1.1		1
720.0	Operations comply with facility plan.	χ			730.11	Surface weter courses diverted.			X
	ASTE HANDLING					Grading promotes surface water runoif without excessive arcsion.			Х
730.5	Bulky waste crushed and pushed to bottom	λ7/0 99 (β ν	98731 1			Grading does not exceed 33 1/3%.	Χ_		
	of cell.	X	34.34.7 47.74%	189 T		Surface water courses and ranoff control	,		
730.6	Demolition and construction waste, tree stumps, sto. pushed to bottom of cell.	X		(2.44)		20 year rainfall.	Х		╀
730.7	Quad animals under 40 lbs, covered immediately.	X			730,12	Minimum 15 feet between waste and meximum water table.	X	3 (A)	
730.8	Dead animals over 40 lbs. placed in pit and	Х			730,13	Water quality protection secure (ic. liner, bedrock).	X		
730.9	covered with 4 ft. of compected soil. Water treatment plant sludges incorporated	2 T T T	era seja Pirana	-	730.14	Leachato and treatment systems used where necessary.	X		
, 4:2:2	into active face and covered immediately.	Х	72.5°		760.15	Ground/surface water not contacting wasto.	Asset S		X
	Quantity of sludges does not interfere with normal active face operation.	X			730.36	All drinking water sources within 1/4 mile sampled annually.	Х		T
730.10 Incinerator and air pollution control residues					COVER	MATERIAL			
Archard.	incorporated into working face and preyented from becoming airborns.		X			Minimum of 6 inches approved cover	T	Ī	T
SOUD W	IASTE EXCLUDED	74 (* 46) 24 - 24 - 2	9.5V(\$).4	eysteryes The	730,3	applied deity.	X	<u> </u>	252
730.4	Responsible supervisor present.	X				Minimum 15 day stockpile of daily cover.	X.		
760.0	Entrance sign posted listing westes not eccepted.	X			730,32	Intermediate cover (min. 1 ft. after compaction) applied to all areas idla more than 60 days.	v		
SAFETY		1.4 1 1 1.4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		······································	730.33	Final cover (min. 2 ft. sfter compaction)	X	i Speliel St	7.00 see gi.
730.25	Fire extinguishers provided on all aquipment	. <u>X</u>		1		applied to completed areas.			
730.26	Provisions made for extinguishing fires.	X			COMPAC	CTION			
730.27	Communications equipment met standard.	χ	. 7		730.1	Solid waste spread in layers not to exceed			
730,28	Scavenging prohibited.	X		d Garage		2 (t. and reduced to smallest volume.	X	7.0	-
730.29	Controlled access limited to operating hours	. Х			730.2	Waste confined to smallest practical area on working face.	X		
730.30	Traffic directed to designated disposal points.	Х			730.24	Adequate equipment mainteined and	X		
730.31	Dust control adequate.	X				operated.			

Section Number	Satisfactory Compliance Operating Procedure	SAT	•	UNS	Section Number	Satisfactory Compliance Operating Procedure	SAT	•	UNS
AIR QUA	ury.				VECTOR:				
730,16	No open burning without parmission.	χ			730.19	Vector control programs implemented.	Υ	T	T
GAS COI	VTROL	i de la de Section			RECORDS	S		1	
730,17	Decomposition gas control implemented.	6000.7. 1435614	***** *****	X	730.35	Records maintained to cover:	T	T	T
730.18	Gases vented to prohibit explosive or toxio eccumulations.	Mari Sariti		v		a. Major problems and complaints.	X	1000	
AESTHET		1666. 21466] A		b. Monitoring of leachate, gas, ground, and surface water sampling and analyses.		#	
730.20	Litter control devices used properly,	V	1.1.			a. Vector control efforts.	X		100
<u> </u>	Litter collected and secured daily.	X				d. Dust and litter control efforts.	v		
730.21	Blowable waste covered promptly.	X				e. Quantity of waste handled.	Х	200	
730.22	Vegetation and natural windbreaks used			5/2/20	BONDING		11.4		
	Whole necessary.			X	690.1	Operating bond adequate.	Y		\$100 E
730.23	Salvaged meterials stored or removed daily,	X	Trail (1) Forward	Å Z	CLOSURE		<u> </u>		
730.34	Finel vegetation planted and graded as required.	χ	* 15 ° \$ 71 * 1	7 - 2/- 1 - 2/-	790,1	Final cover and vegetation provided.	l v		

Weather Conditions: rainy, cloudy, 50° and breezy	- 100 100 <u>160 - 11</u>
Observed With: Glen O'Bryan, Laidlaw Waste Systems; Joe Trunko, Frank Dolan & Terry Hoevelkam; Sue Taylor and Brad Bomanz, St. Louis County Consulted With: SAME	<u>, M</u> D
Additional Remarks/Comments: 1. Exposed waste was noted along the quarry walls in pit #3. A new	i ja : Ografi
technique of running the compactor parallel to the quarry walls and providing additional co	ver
will, hopefully, remedy the problems of poorly compacted waste and insufficient cover mater	
in these areas. It is to be noted that inadequate soil cover along quarry walls will	
contribute to passive gas venting and thus contribute to the enormous odor problem currentl	<u>у</u>
existing at this site. The new gas flaring system's 60 horsepower motor should increase	
subterranean negative air pressure. Areas with exposed waste and inadequate cover could ha	ÿe_
detrimental effects on the effectiveness of the gas extraction system by drafting in ambien	<u>L</u>
air (02).	
	*
2. The subterronean fire in pit #2 which was first noted Sent, 25, 1992 appears to have	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1

Signature of Inspector

Signature of Section Chief

OVER

subsided.

Laidlaw Waste Systems (Sanitary) Page 2

- A request to provide the office with leachate sampling/recording procedures is pending.
- 4. Surface water courses are not diverted from pit #3. This problem has been noted by Mr. O'Bryan and plans to recontour the site and provide drainage away from the landfill are in the planning stage.
- 5. Grading contours are promoting erosion and creating areas of exposed waste on the northern slope of pit #3. Plans by Laidlaw to address this issue such as terracing, strategic placement of straw bales and the application of additional soil cover were proposed by Mr. O'Bryan as possible solutions.

This office is requesting Laidlaw to submit in writing within two (2) weeks from receipt of this inspection an implementation schedule to correct violations [Section 607.730.11 (surface water courses diverted and proper grading as indicated) and 607.760.15 (surface water not contacting waste)]. If corrections have not been completed within the specified schedule, legal notification may ensue.

cc: Glen O'Bryan, Laidlaw, Oper, Mgr.
John Boonstra, Laidlaw, Reg. Div. Mgr.
Joe Trunko, MDNR-SLRO
Richard Houchin, Bridgeton City Hall
Glen Hampton, St. Louis Co. Waste Mgmt.

ignature of Inspector

Signature of Section Chief

fot. Louis Regional Office Date Received

JM2893

foure:	
	APCU
3841	SWWU
W. W.	WP-PRAT
	Rahill
and the second second	



January 7, 1993

JAN 1 2 '92

APCU

Mr. Brad Bomanz, C.P.S. Environmental Control Inspector St. Louis County Department of Health 111 South Meramec Avenue Clayton, Missouri 63105

Dear Mr. Bomanz,

Re: Laidlaw Waste Systems (Bridgeton), Inc

Pursuant to your request, this letter outlines the recent chronology of the underground fire located in the wet weather I was first made aware of the fire on November 30, At that time, small wisps of smoke were emanating from the quarry wall in a few locations around the wet weather area. The magnitude of the problem was not significant at that time. We began a daily inspection of the area, beginning the next day. On December 7, 1992, the fire was dramatically more intense, with visible flames at the north quarry wall in the wet weather area. personnel removed burning debris from the sidewall, and began placing a soil berm along the entire north wall. Further. landfill gas collection system in this area was turned off. berm along the north was completed on December 8. The landfill gas collection system was then turned back on December 9. then, site personnel have conducted daily visual inspections of the area. Persistent wisps of smoke and/or steam continue to be present in a few locations along the eastern quarry wall. I have determined that the smoke is finding a pathway through weathered rock and presenting itself approximately 15' above the elevation of the refuse in that location.

As conditions warrant, we are placing additional soil along the walls and over the area as a whole. We are also developing some data in the area by taking temperature readings in the landfill gas system. Additionally, we have purchased a Drager tube sampling pump and CO tubes. We are training site personnel in the use of this equipment and sampling will begin in the very near future.



I will keep you apprised of further developments in this area and the data generated from the described monitoring. Should any questions arise or clarification be necessary, please call me at (314) 739-1919.

Sincerely,

Glenn A. O'Bryan, P.E.

General Manager

cc. Joseph L. Trunko, MDNR Dennis Wike, Laidlaw St. Louis Regional Office Data Received

JAN 12'92

Route:	- mair (i
MANN	APCU
1 10 19 1	SWMU
V. 10.00 F.	WP TRAT
and the state of t	- 18177
n tradition of the second	



January 25, 1993

Mr. Robert S.P. Eck, Regional Director Missouri Department of Natural Resources Division of Environmental Quality St. Louis Regional Office 10805 Sunset Office Drive, Suite 100 St. Louis, Missouri 63127-1017

Re: Laidlaw Waste Systems (Bridgeton), Inc. Bridgeton Sanitary Landfill MDNR Permit #118912

Dear Mr. Eck,

Pursuant to your December 30, 1992 letter, this correspondence outlines the steps that we are undertaking to address the issues raised by the inspection performed by members of your staff on December 29, 1992. Specifically referencing items from the inspection report area <u>FINDINGS</u>:

- A large amount of exposed waste was observed at the facility.
- 2. Erosion guilles were observed in the wet-weather area.

Wet Weather Area (WWA) - We started cover improvements in the WWA during the week of January 4, 1993. This activity is ongoing and has been done in tandem with the construction of a new 12" landfill gas (LFG) pipe which traverses the WWA. Further actions, as weather allows, will include adding an estimated 7800 bey of soil to the WWA, constructing a soil wedge along approximately 600° of the quarry wall in the WWA, constructing erosion control berms and installing downdrains. In conjunction with the underground fire (see next item) we may install a synthetic cover over the WWA for oxygen deprivation, or we may vegetate the area. A final decision will be made after additional study of the underground fire character and extent.

Northern Area of the Active Pit - The northern area of the active pit has been regraded and repaired,

LAIDLAW

3. An underground fire was occuring in the wet-weather area.

A number of actions have already been taken on this issue. Our first effort has been directed toward shutting off oxygen pathways to the fire. Toward that end, we installed a soil wedge along the north wall of the WWA on December 8, 1992. As described above, we are adding to the soil wedge along the eastern and southwestern edges of the WWA along the quarry walls. This effort, combined with the additional cover soils in the WWA should dramatically reduce the oxygen potential. Further, we have purchased a Drager sampling pump and carbon monoxide (CO) tubes and a thermometer, to monitor LFG flows from the area, as well as the wisps of smoke/steam which emanate from the quarry wall in a few locations. We will monitor this situation daily and keep the Department apprised of the results.

4. The new flare has not been constructed.

Site clearing was started on the new flare location on December 28, 1992. Construction began on January 4, 1993. The concrete foundation and pad are now complete. The blowers, piping, and electrical will be installed during the week of January 18. The flare stack will be installed during the week of January 25, and we expect the flare to be operational during this same week.

5. Regulated quantities of hazardous waste have been disposed of at this facility.

We submitted a plan to the MDNR on December 14, 1992 for the remediation of this issue, with a completion date of March 31, 1993.

We trust that this correspondence satisfactorily addresses the concerns from the referenced inspection. Should any questions arise or clarification be necessary, please call me at (314) 739-1919.

Glenn A. O'Bryan, P.E.

General Manager

Sincerely

cc: Joe Trunko, MDNR
Brad Bomanz, St. Louis County Health Department
Miles Stotts, Laidlaw
Dennis Wike, Laidlaw



March 20, 1993

MR 24'93

Ms. Sue Taylor, Supervisor Waste Management Section St. Louis County Department of Health 111 South Meramec Avenue Clayton, Missouri 63105

Re: Laidlaw Waste Systems (Bridgeton), Inc. Bridgeton Sanitary Landfill St. Louis County Permit No. 0419 Inspection of 12/29/92

APCU
SWMU
WEFERNIT
W.MII

Dear Ms. Taylor:

I was reviewing my inspection files this morning and determined that I had not written a specific response to your inspection of 12/29/92. Your office was, however, copied on the response to the MDNR inspection of that same date which noted my responses to the same issues identified in your inspection. I did not, however, specify dates for the anticipated actions, which was requested within your inspection documents.

Regarding 607.730.11 (surface water courses diverted and proper grading as indicated) and 607.760.15 (surface water contacting waste), please find attached a sketch describing the corrective construction features. The corrective construction features include an all-weather access road, west downdrain, east erosion control berms, additional cover soils and downdrain, The road has been under construction during the past vegetation. month, and should be completed by April 15. The road will provide a solid path for our heavy equipment to move between the sanitary site and the demolition site. We may also use this road for refuse vehicle ingress and egress, particularly when maintenance is required for the main quarry road. Completion of the road will allow access for performing the additional work. plan to complete the construction of the cover soils, berms and other drainage features by May 15.

I trust that this correspondence adequately addresses your request. Should any questions arise or clarification be necessary, please call me at (314) 739-1919.

DE BEE

Glenn A. O'Bryan, P.E.

General Manager

Sincerely,

cc: Joe Trunko, MDNR-SLRO
Dick Houchins, P.E., City Engineer/Director of Public Works
Miles Stotts, Laidlaw
Dennis Wike, Laidlaw

BANDBAN - FLARE STATION WET WEATHER ATTER WEST DOWNDRAIN DOMNOSHIN -Bezus BRIDGETON LANDFILL PTEPARED 3/20/93 GUENN A. O'BEYAN ATTACHMENT TO LETTER OF 3/20/93 COLLECTION ATLEA ACTIVE ATLEA

ST. LOUIS COUNTY HEALTH DEPARTMENT WASTE MANAGEMENT SECTION

AR 2 3 1994

SANITARY LANDFILL SURVEILLANCE RECORD

	Estimated amount of solid waste coming through gate.
Days/Week Open: 0	Compacted Loads 37,500 yds./wk. tons/wk.
Date: 3-4-94 Days/Week Open: Systems (Sanitary) Name of Facility: Laidlaw Waste Systems (Sanitary) 6-22-94	Compacted Loads yds./wk. tons/wk.
Name of Facility: 10 - 6-22-94	Noncompacted Loadsyds./wk,tons/wk.
Permit No.: 0419 Expires: 022 34	
Taidlay Waste Systems, Inc.	Estimated volume of remaining landfill covered by approved engineering
Owner: 13570 St. Charles Rock Road	
Address: Bridgeton, MO 63044	plans,acre(s) years
Pringerou, 1.0	
하고 하고 있는 이 생각 이 생기가 생각이 있습니다. 그는 사람들은 그는 것이 있는 것이 없는 것이 없는 것이 없다.	그 그는 사람들이 가지 않는 것이 없는 것이다.

Ordinance 13,320 Chapter 607 Compliance Status

Check all sections: SAT-Satisfactory; UNS-Unsatisfactory; * - Area(s) requiring additional attention.

ection	Check all sections: SAT-Sations: SAT-Sations: Satisfactory Compliance Operating Procedure	SAT		Section S Number		SAT	+ 1	UNS
umber		जन्म मुद्रेश, स		WATER	QUALITY	 -	نیند	一
ACILITY		i . T	1)	730.11	Surface water courses diverted.	Х	<u> </u>	20 mg
20.0	Operations comply with facility plan.				Grading promotes surface water runoff		332 / v	l x
OLID WA	STE HANDLING	100 (100) 100 (100)		-	without excessive erosion.	Х	75 51	
30.5	Bulky waste crushed and pushed to bottom of cell:	X			Grading does not exceed 33 1/3%. Surface water courses and runoff control	χ		
30.6	Demolition and construction waste, tree stumps, etc. pushed to bottom of cell.	N/A		730.12	20 year rainfall. Minimum 15 feet between waste and	χ		
130.7	Dead animals under 40 lbs. covered immediately.	X		730.13	maximum water table. Water quality protection secure (ie. liner.	Х		1
730.8	Dead animals over 40 lbs. placed in pit and covered with 4 ft; of compacted soil.		6. A - <u>25 -</u> W - 5 C	730.14	bedrock). Leachate and treatment systems used	X		
730.9	Water treatment plant sludges incorporated into active face and covered immediately.	X		730.15	Where necessary. Ground/surface water not contacting waste	X		
	Quantity of sludges does not interfere with normal active face operation.	X		730.36	All drinking water sources within 1/4 mile sampled annually.	<u> x</u> _		<u> </u>
730.10	see so legiperator and air pollution control residues		COVER	MATERIAL				
	Incorporated into working face and prevented from becoming airborne.	<u> </u>		730.3	Minimum of 6 inches approved cover applied daily:	x		
SOLID W	IASTE EXCLUDED	<u> </u>			Minimum 15 day stockpile of daily cover.	X	<u> </u>	
730.4	Responsible supervisor present.	X			Total cover (min. 1 ft. after	T		
760.0	Entrance sign posted listing wastes not accepted.	X		730.32	compaction) applied to all areas like there than 60 days.	<u> </u>		
SAFETY		The second second	of as other	730.33	Final cover (min. 2 ft. after compaction)	X		
	Fire extinguishers provided on all equipme	it. X			applied to completed areas.	The State		
730.25	Provisions made for extinguishing fires.	X	3 3 3	СОМР	ACTION		-	- 1
730.26	Communications equipment met standard.	Х		730.1	Solid waste spread in layers not to exceed	X	1	
730.27	Scavenging prohibited.	Х	(2 ft. and reduced to smallest volume.	 	1	
730.28	Controlled access limited to operating hou	rs. X		730.2	Waste confined to smallest practical area on working face.	X		
730.29 730.30	Traffic directed to designated disposal points.	X		730.24	Das henisteles-	Х		
730.31	Dust control adequate:	X						-

Section Number	Satisfactory Compliance Operating Procedure	SAT		UNS	Section Number	Satisfactory Compliance Operating Procedure	SAT		UNS
AIR QUA	<i>UTY</i>			, ****** 	VECTOR	5	73		
730.16	No open byrning Without permission.	Х	10 TO	200	730.19	Vector control programs implemented.	X		T
GAS CO	NTROL		er elegis († 4. Vecales († 5.	e ivi Helitarika	RECORD	s		1	 _
730.17	Decomposition gas control implemented.			X	730.35	Records maintained to cover:	Ī.	Ī	T
730.18	Gases vented to prohibit explosive or toxic		10000			a. Major problems and complaints.	X	es i	2,,
نده ونسيسون	accumulations.	X	<u> </u>	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		 b. Monitoring of leachate, gas, ground, and surface water sampling and analyses. 	X		
AESTHE	IICS	Marks.	<u> </u>	9. A. V		c. Vector control efforts.	1 2 2 2	<u>4.745.8</u> 3.4507	2005 c
730.20	Litter control devices used properly.	χ	1			d. Dust and litter control efforts.	X		
	Litter collected and secured daily.	X	1			20 July 20 Jul	X	100 July 100	11
730.21	Blowable waste covered promptly.	X			lata di dela	e. Quantity of waste handled.	X	17, 4, 4	
730,22	Vegetation and natural windbreaks used	981 144 1861			BONDING				
	Where necessary.	Х			690.1	Operating bond adequate,	х	******	
730,23	Salvaged materials stored or removed daily.	χ	517 T		CLOSURE				H
730.34	Final vegetation planted and graded as required.	χ			790.1	Final cover and vegetation provided.	Х		

Weather Conditions: Clear, Sur	ny, 65° and breezy with low humidity.	
Observed With: Susan Taylor,	DÔH	
		_
Consulted With: Larry Giroux,	Laidlaw Waste Systems, Inc. & Susan Taylor, DOH	
		_
Additional Remarks/Comments:	UNSATISFACTORY CONDITIONS NOTED:	
		.:

- la. In areas idle for more than 60 days (Pits 2 and 3), settlement has occured pulling waste and cover material away from the quarry walls. Without proper cover and a good seal along the quarry walls, the odor problems will be accentuated and potentially decrease the efficiency of the gas collection system. (Section 607,720,0)
- 2a. Ponded surface water was noted throughout the site (Pits 1,2 and 3) due to settlement and poor contouring. Some erosion was also noted, however, trash was not exposed. (Section 607.730:11)
- 3a. Flames and smoke from an ongoing subterranean fire were noted along the eastern wall in Pit #2 (previously the wet weather area).
- 4a. Pit #2 has an apparently abandoned leachate well that has emerged due to settlement.

 Landfill gases are passively venting from this location.
- In pit #1, adjacent to the radioactive area, settlement of waste has created a large blow hole (approximately 5 feet in diameter) and fissures which are venting significant amounts of landfill gas. (Section 607.730.17)

continued on page 2

no:

Signature of Inspector

Signature of Section Chief

Laidlaw Waste Systems (Sanitary) March 4, 1994 Page 2

RECOMMENDATIONS


- 1b. Cover all waste up to the quarry walls and compact to eliminate all gas migration (an O2 intrusion). Particular attention to obtain a good seal should be made at the quarry wall. This violation was noted and has remained since the previous inspection on December 20, 1993. Soil coverage at the quarry wall should be monitored (preferably weekly) to assess the maintenance of a good soil/rock seal.
- 2b. Add additional cover material to establish proper contour levels as soon as possible. It is to be noted that this is the same violation that was noted in December, however, numerous areas have already been corrected since that time. Mr. Giroux is implementing the gradual regrading of Pit #3 to address this situation.
- 3b. Extinguish the subterranean fire. Aerial infrared photography has pinpointed the extent and location of the fire. Previous efforts to control the fire by placing additional soil cover along the quarry wall were noted. Efforts have been scheduled to remediate the situation and are to commence on March 9, 1994
- 4b. Properly reactivate and seal the base of the leachate well or properly close and cap the well. This violation was noted in the December inspection.

Add sufficient additional compacted soil cover material to seal off any escaping gases from the fissures. This area had additional cover placed on it in the recent past. It is recommended that this area be regularly inspected for fissures and blow holes and address such conditions immediately.

SATISFACTORY CONDITIONS NOTED:

Overall - Soil cover over most of the site was good.

cc: Larry Giroux, Laidlaw - Operations Manager John Boonstra, Laidlaw - Regional Division Manager Joe Trunko, MDNR - SLRO Richard Houchin, Bridgeton City Hall



ST. LOUIS COUNTY HEALTH DEPARTMENT WASTE MANAGEMENT SECTION

SANITARY LANDFILL SURVEILLANCE RECORD

Date: 4-27-94 Days/Week Open:	Estimated amount of solid waste coming through gate. Compacted Loads 37,500 yds./wk. tons/wk. Noncompacted Loads yds./wk. tons/wk.
Permit No.: U. L. Suctions Inc.	Estimated volume of remaining landfill covered by approved engineering
Owner: Laidlaw Waste Systems, Inc. 13570 St. Charles Rock Road Address: Bridgeton, MO 63044	plansacre(s) 10 years

Ordinance 13,320 Chapter 607 Compliance Status

Check all sections: SAT-Satisfactory; UNS-Unsatisfactory; * - Areals) requiring additional attention.

ection	Satisfactory Compliance	AT *	UNS	Section Number	Area(s) requiring additional attention. Satisfactory Compliance Operating Procedure.	SAT		UNS
umber	Operating Procedure S		terae raina. Spirit teraen	WATER O	UALITY			
ACILITY	PLAN	v		730.11	Surface water courses diverted.	X		1.62.2.5 1.76
20.0	Operations comply with facility plan	<u> </u>			Grading promotes surface water runoff	x		
OUD W	ASTE HANDLING				without excessive erosion:	X		T
30.5	Bulky waste crushed and pushed to bottom	x			Grading does not exceed 33 1/3%.		7	
30.5	of cell.		36.3 6.30 6.30		Surface water courses and runoff control 20 year rainfall.	X		
30.6	Demolition and construction waste, tree stumps, etc, pushed to battom of cell:	\/\ 	<u> </u>	730.12	Minimum 15 feet between waste and	x	\ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
30.7	Dead animals under 40 lbs: covered immediately.	χ		730.13	maximum water table. Water quality protection secure (ie, liner,	Х	ASC 18	
730.8	Dead animals over 40 lbs, placed in pit and covered with 4 ft. of compacted soil.	X		730.14	bedrock). Leachate and treatment systems used	X		
730.9	Water treatment plant sludges incorporated into active face and covered immediately.	X		730.15	where necessary. Ground/surface water not contacting waste	X		1
av ,	Quantity of sludges does not interfere with normal active face operation.	Х		730.36	All drinking water sources within 1/4 mile sampled annually.	<u> </u>		
730.10	leaterestor and air pollution control residues			COVER	OVER MATERIAL			
730.10	incorporated into working face and prevented from becoming airborne.	X _		730.3	Minimum of 6 Inches approved cover	X	4 3.7%	1 200
SOLID V	NASTE EXCLUDED				applied daily. Minimum 15 day stockpile of daily cover.	X	1_	_
730.4	Responsible supervisor present	X		730,32	an a train 1 ft. after		1	ľ
780.0	Entrance sign posted listing wastes not accepted.	Х		/30,32	compaction) applied to all areas los mans than 60 days.	X	1	
SAFET		₹7, \$7, 7 2, \$8, 92 1 , \$8	1 (1985) 1 (1985) 1 (1985)	730.33	Final cover (min. 2 ft. after compaction) applied to completed areas.	X	<u> </u>	
730.25	Fire extinguishers provided on all equipment	X_			The second secon			
730.26	Provisions made for extinguishing fires.	A			ACTION Solid waste spread in layers not to exceed	.	$\prod_{i=1}^{n}$	
730.27		X		730.1	2 ft, and reduced to smallest volumes.			
730.28	Scavenging prohibited. Controlled access limited to operating hour	X		730.2	Waste confined to smallest practical area	ļ "	.	}

Section Number	Satisfactory Compliance Operating Procedure	SAT	1 * A 401	UNS	Section Number	Satisfactory Compliance Operating Procedure	SAT	*	UNS
AIR QUA	шү	0.000 1 3 6 1 2 8 5 1 1 2	14 W. 124.	./***/* V.S.	VECTOR:			~* 44.7 44.	:
730.16	No open burning without permission.	X			730.19	Vector control programs implemented.	X	,	
GAS CO	VTROL	erinin ili. Azaroni	in a second	alan da sa	RECORD				
730.17	Decomposition gas control implemented.		*	783.4 783.4	730.35	Records maintained to cover: a. Major problems and complaints.	x		1
730.18	Gases vented to prohibit explosive or toxic accumulations.	X	¥.			b. Monitoring of leachate, gas, ground, and surface water sampling and enalyses.	1	1911. 1911.9	
AESTHET	(CS	···		: ** :		c. Vector control efforts.	X	-	
730.20	Litter control devices used properly:	χ				d. Dust and litter control efforts.	X		+ 122.74 10 T
	Litter collected and secured daily.	X			1, 2,2,2	e. Quantity of waste handled:	X	X	
730.21	Blowable waste covered promptly:	X_		2	BONDING		-		
730.22	Vegetation and natural windbreaks used where necessary.	X			690.1	Operating bond adequate.	Х		
730,23	Salvaged materials stored or removed daily.	X			CLOSURE			1.	
730.34	Final vegetation planted and graded as required.	X			790.1	Final cover and vegetation provided.	Х		

Weather Conditions: Clear, sunny 65° and breezy with low humidity.	
Miles Dolon, Yaidlaw Wanta Systams, Tag	••
Mars Dala Yardin Using Contains The	: '
	_
Additional Remarks/Comments: UNSATISFACTORY ITEMS	
There were no unsatisfactory items to be noted at the time of inspection.	Stranger
COMMENTS	
The landfill looked very good. Dirt cover was very good and all areas were being cont properly. A good dirt/rock seal is being maintained at the quarry walls and no waste	and the second of the second
to be protruding.	150 150 150 150 150 150 150 150 150 150
Roadways throughout the landfill were being maintained in very good condition and dust	
being controlled through the use of a newly acquired water truck and a newly implement	ted wet
down schedule. The roadways accessing the active face in Pit #3 have been reinforced	with
additional material and compaction. The access roadway to the dirt borrow area has a	lso been
reworked to allow better access to the area during wet weather. This action which has	s allowed
faster access time for the dirt trucks and this, an increased availability of soil con Better compaction operations have enhanced the appearance of the landfill, improved co	ver materia ontouring,
and have decreased passive gas migration through the soil cover.	

Signature of Section Chief

cct

Laidlaw Waste Systems, Inc. April 27, 1994 Page 2

A new fence has recently been installed around Pit #3 for better safety and security.

The present gas system is being reevaluated to assure that the entire surface of the landfill is within the influence of the existing gas extraction system. The gas burner was operational and operating at near maximum capacity. One burner head was having maintenance performed at the time of the inspection. The next set of laterals is being scheduled for installation with some possible as built changes relating to lateral sloping to eliminate line blockage and substituting stronger piping to reduce line collapse.

The fire in Pit #2 has been controlled and is believed to have been extinguished. Recent temperature checks along the quarry wall (where the fire was noted previously) indicated the temperature had dropped over 200 degrees. Another slurry injection in a series of 5 injections is scheduled for next week. These final injections are to confirm total remediation of the fire.

In pit #2, along the quarry wall next to the haul road, additional cover material had been applied to the insufficient cover that was previously noted. Areas of insufficient cover have received additional material and the entire surface area of Pit #2 is scheduled to be redressed after all equipment is removed from the fire remediation.

Paper was being hand picked from the entire landfill surface area at the time of the inspection.

Leachate levels are being kept within permitted limits. This is due to the interim pumping schedule recently initiated. A new computer program to track pump hours - pump breakdowns - maintenance cost - down time - repair time, etc. is being introduced to provide for greater pump efficiency through a preventative maintenance program.

Ponding surface water has been eliminated through better contours being maintained and dryer weather conditions.

ST/BB/kmw

ce: Larry Giroux, Laidlaw - Operations Mgr.

John Boonstra, Laidlaw - Regional Division Mgr.

Joe Trunko, MDNR - SLRO

Richard Houchin, Bridgeton City Hall

lignature of Inspector

Signature of Section Chief

1 9 1884

STATE OF MISSOURI

Mel Camahan, Governor . David A. Short, Director

DEPARTMENT OF NATURAL RESOURCES

DIVISION OF ENVIRONMENTAL QUALITY

Sr. Louis Regional Office

10805 Sunset Office Drive, Suite 100 St. Louis, MO 63127-1017

(314)822-0101

FAX(314)822-0943

June 22, 1994

Mr. Larry Giroux Laidlaw Waste Systems, Inc. 13570 St. Charles Rock Road Bridgeton, MO 63044

Dear Mr. Giroux:

Enclosed is a report of an inspection conducted by Mr. Joe Trunko of my staff. The report contains recommendations which the inspector has determined are warranted based on his findings at the facility.

Please review the report and implement the recommendations presented. Should you have any questions or comments, please contact Mr. Joe Trunko at (314) 822-0101.

Sincerely,

ST. LOUIS REGIONAL OFFICE

Robert S. P. Eck Regional Director

RSPE/JLT/mc

Enclosures

c; SWP Mr. Brad Bomanz, St. Louis County Health Dept., Solid Waste Mr. Dave Berger, Executive Director, Region L

SPEck

Weather Conditions:

Clear, sunny, 80 degrees and breezy with moderate humidity.

Observed With:

Mike Dolan, Laidlaw Waste Systems, Inc.

Consulted With:

Mike Dolan, Laidlaw Waste Systems, Inc.

Additional Remarks/Comments:

UNSATISFACTORY ITEMS

1A - Leachate levels reported for the month of May are high due to equipment breakdown and lack of parts for a timely repair. (Section 730.14)

COMMENTS

1A - Institute maintenance program and/or acquire additional pumps as backup.

The landfill looked very good. Dirt cover was very good and all areas were being contoured properly. A good dirt/rock seal is being maintained at the quarry walls and no waste was noted to be protruding.

Roadways throughout the landfill were being maintained in very good condition and dusting was being controlled through the use of a newly acquired water truck. The roadways accessing the active face in Pit #3 have been reinforced with additional material and compaction. The access roadway to the dirt borrow area has also been reworked to allow better access to the area during wet weather. Improved compactor operation has enhanced the appearance, provided for better contours and increased exclusion of gas migration through daily cover.

The present gas system is being reevaluated to ensure that the entire surface of the landfill is within the influence of the existing gas extraction system. The main gas burner was operational and operating at near maximum capacity. Both secondary burners were down. One was not operational due to an unscheduled shift of the active face — the other due to reduced volumes of methane. The next set of gas collection laterals is being scheduled for installation with the incorporation some possibly as built changes relating to lateral sloping to eliminate line blockage and the substitution of stronger piping to reduce line collapse.

The fire in Pit #2 has been controlled and, based upon thermal readings, believed to have been extinguished. The area is on a routine monitoring schedule to ensure reoccurrence of the fire will not take place.

Ponding surface water has been eliminated through the maintenance of better contours maintained and drier weather conditions.

cc: Larry Giroux, Laidlaw - Operations Mgr.
John Boonstra, Laidlaw - Regional Division Mgr.
Joe Trunko, MDNR - SLRO
Richard Houchin, Bridgeton City Hall

West Lake (Bridgeton) Sanitary Landfill Laidlaw Waste Systems, Inc. St. Louis County MDNR Permit #118912

INTRODUCTION

On June 8, 1994, the above referenced facility was inspected for compliance with regulations pursuant to the Missouri Solid Waste Management Law. Mr. Joe Trunko represented the Missouri Department of Natural Resources (MDNR), St. Louis Regional Office: Messrs. Larry Giroux and Mike Dolan represented Laidlaw Waste Systems, Inc.

Prior to the inspection, a meeting was conducted between representatives of Laidlaw Waste Systems, Inc., the Solid Waste Program (SWP), the Division of Geology and Land Survey and the St. Louis County Department of Health. The meeting concerned the hydrogeologic investigation that has been proposed for this facility, as required by the Subtitle D regulations. Following the meeting, a tour of the landfill was made, at which time the inspection was conducted.

UNSATISFACTORY FEATURE

None.

COMMENTS

Overall operations at the landfill were satisfactory. The active face was being maintained to a small area. An observation of the previous days active face indicated that adequate daily cover had been applied.

Laidlaw has begun using a synthetic daily cover (Connier 1440 woven polyethylene liner). Use of this material was approved by the SWP on 1/5/93. Condition no.2 of the approval requires that two copies of the final bid specifications for the material used and two copies of a detailed operations manual that specifies the guidelines for use of the cover be submitted to the SWP.

Laidlaw submitted a request to the SWP for approval to use soil contaminated with gasoline as daily cover. The SWP terminated its review of the request due to the failure of Laidlaw to obtain St. Louis County approval. In the meeting referenced above, use of this soil as daily cover for a trial period was discussed. Should Laidlaw wish to pursue the use of this material as daily cover for a trial period, a written request should be submitted to the SWP. Approval by the St. Louis County Department of Health must be obtained before the request will be reviewed by the SWP.

West Lake SLF (SW) June 22, 1994 Page 2

Condition 6.D of permit #118912 requires that the leachate in the collection sumps be maintained at a level less than 30 feet above the base of the sumps. The leachate sump reports submitted to this office for the months of February, March and April have shown compliance with this limit except for one reading taken at LCS 1 in April (46 feet). Mr. Dolan stated that the 58 h.p. pump utilized in this sump had malfunctioned. A backup pump was installed in the sump. However, operational problems were encountered with that pump as well. A pump was not operating in LCS1 at the time of the inspection. Mr. Dolan stated that a replacement pump as well as several backups were on order.

On September 29, 1993, Laidlaw requested a modification to construct and operate the storm water retention plan that was submitted to the Department on September 14, 1993. This plan was approved by the SWP on 5/4/94. Construction of settling basin #1 is scheduled to begin by the end of June.

A drainage ditch located near the asphalt plant was cleared of debris. As a result, much of the runoff from the closed landfills is now being diverted into the pond located next to the asphalt plant. The asphalt plant utilizes this water in their operation. Mr. Giroux stated that due to the decrease in stormwater flow from this area, the size of settling basin #2 may be decreased. Revised plans will be submitted to the SWP if a modification to the design of the basin is finalized.

A request for a waiver of the Subtitle D liner requirement for the quarry sidewalls and the ramp leading into the quarry was submitted to the SWP on 3/8/94. The liner waiver was approved by the SWP on 5/4/94.

The underground fire that was located in the former wet weather area appears to have been brought under control. A bentonite slurry has been used to seal the area between the quarry wall and waste, thus minimizing the entry of oxygen to the area of the fire. Laidlaw continues to monitor this area and additional slurry is applied as needed. Mr. Dolan stated that the gas collection trenches in this area would not be activated until Laidlaw was sure that the fire was extinguished.

The gas flare located in the quarry pit was not operating at the time of the inspection. The flare was disconnected as a result of preparations to install the next level of gas collection laterals. Evaluation and monitoring of the current gas collection system by Laidlaw has indicated that additional modifications to the gas system will be required in order for it to adequately handle the gas being generated by the landfill.

As required by 10 CSR 80-3.010(11)(C)3., owners/operators of all sanitary landfills must implement a routine methane monitoring program to ensure that methane is not allowed to exceed 5% LEL for methane at the property boundary or 25% LEL in buildings on the landfill. Laidlaw is currently monitoring all the buildings at the landfill with continual gas monitors. Gas migration at the landfill boundaries is being monitored through the use of a punch probe. Laidlaw is working on the development of a regular gas monitoring program, which will include gas monitoring wells at the landfill perimeter. Laidlaw must ensure that monitoring is provided for all layers of rock at the quarry walls that could provide a pathway for gas migration.

June 22, 1994
Page 3

During the inspection, the inactive area north of the flare was observed (former permit area #118906). Subsidence of the fill in this area has created several depressed sections. Cracks in the soil cover in these areas creates the potential for gas to vent to the atmosphere, thus causing additional odors. Laidlaw has made some attempts to fill and seal these areas.

RECOMMENDATIONS

- 1. Two copies of the following information must be submitted to the Solid Waste Program: the final bid specifications for the Cormier woven polyethylene liner; a detailed operations manual specifying the guidelines for use of the liner.
- 2. Continue with efforts to improve the operation of the leachate collection system. Actions must be taken to ensure that the pumps located in the leachate collection sumps remain operational and that adequate backup pumps and/or service contracts for the existing pumps are provided. Please submit a brief report to this office that describes the actions Laidlaw has pursued to insure that the leachate levels in the collection sumps remain in compliance with condition 6.D of permit 118912.
- Ensure that methane monitoring is conducted on the north and east sides of the permitted landfill.
 A report summarizing the results of any methane monitoring conducted at the landfill must be submitted to the St. Louis Regional Office at least on a quarterly basis.
- 4. Continue with efforts to recover and regrade the subsided areas in the inactive section of the landfill.

Questions concerning this report should be addressed to the undersigned.

PREPARED BY:

Joseph L. Trunko

Environmental Specialist II

Л.Т/тс

4.35	1		
15	\mathbb{G}_{i}	٥	,
/~S	Я.	W	١
///模	30	ŝΙ	1
190		w	۷.

MISSOURI DEPARTMENT OF NATURAL RESOURCES

DIVISION OF ENVIRONMEN	ITAL QUALITY	
	NADEOTION OU	OVI ICT
SANITARY LANDFILL	NSECTION CU	CULID

TYPE OF INSPECTION Delass De

	INFORMATION	DAYS/WEEK OPEN	e se di Saga Jawa Mi	TIME OF ARRIVAL	K.		
TE OF INSPECT	^{10N} 황-4나	्र इंडर्ड्डिड्डिड्डिड्डिड्डिड्डिड्डिड्डिड्डिड	eregere <u>galariana</u>	\(\oldsymbol{\O}\);\(\oldsymbol{O}\)	A-m.	eraz <u>rego e en</u>	<u></u>
CATUCO	Superior Control of the Control of t			The second secon	TEMPERATURE 80	F	
Sec. 1200.4 (A) 140.00	-Hy Cloudy; dr	y		COUNTY	PERMIT NU		
CILITY NAME	ake (Bridgeton)	Sourtary Law	real.	St. Louis	the state of the s	7915	<u> </u>
	THE RESERVE OF THE PROPERTY OF THE PARTY OF	The Mark Co., 1981			TELEPHONE NUMBER	1919	
Laidle	w Waste Syste	ms (The.	<u> , , , , , , , , , , , , , , , , , , ,</u>		ETATE ZII	CODE	ar Aren der Aren der
	and the second of the second o		CITY	digitari	10 No	63044	
1357	O st. Charles Roc	K Koao	1000	difference	TELEPHONE NUMBER		
PERATOR	some as counter		All Sales		The second secon		<u> </u>
DDDCCC.	SULUS NO CONTINE		CITY	4	STATE IL	P CODE	
DDRESS	· f						
I REMAIN	ING LIFE OF LANDFIL		75 6 75 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	EA SERVED			
V Ectimate	d quantity of waste acc	epted, 35,00	A. (Cities:	1.01.1	W. C.	175
vards or	tons(week)	and the contract of the second	<u> </u>	Vario	is Monicipalit	18.2	
3. Estimate	d life of remaining land	HTIII	-				
2	years.	<i>₩</i> .0€	B. 1	Counties:	Charles, Stal	avis Cit	f^{\perp}
C. Fixed op	erating term date,	~18 ~13.					
HOTE N. C	west all subcontions SAT-	Ratisfactory or UNS-Un	satisfactory. If ne	ecessary, describe "UNS" viol	ations under "Remarks."	SAT	UNS
NOTE P C	DO PERMIT ISSUANCE, SP	ECIAL OPERATING P	ERMITS, AND PE	RMIT EXEMPTIONS	24.	$T \sim T$	<u> </u>
(5)(E)	SITE CONSTRUCTED AND OP	ERATED PER APPROVED	TERMS AND CON	DITIONS OF PERMIT			1 19 19 19
10 CSB 80-3 (060 CERTIFIED SOLID WAS	STE TECHNICIANS		en e		1 71	11.77
(2)(A)	CERTIFIED SOLID-WASTE TEC	CHNICIAN.				1 0 1	7.1.
40.000.00.21	NO CANITARY LANDELLS	DESIGN AND OPERA	T)ON		<u> </u>	1 71	
in control	ASTE ACCEPTED (2)(C)1.	BULKY SOLID WASTE CR	USHED ON SOLID	GROUND.		 ' /	
(2) (C)2.	SMALL DEAD ANIMALS COVE	RED IMMEDIATELY.	Samuel Market Comment		AND THE RESERVE OF THE PARTY OF	<u> </u>	-
· · · · · · · · · · · · · · · · · · ·	THE PARTY OF THE PARTY OF THE	CIAL WASTE ADDROVA	S		na di kacamatan di Kabupatèn Balangan Kabupatèn Balangan Kabupatèn Balangan Kabupatèn Balangan Kabupatèn Balang Kabupatèn Balangan B	1 /1	<u> </u>
/3)(C)\$	THE DISPOSAL OF SPECIAL V	WASTE APPROVED IN TH	E PERMIT IN AGGO	RDANCE WITH APPROVED PLA	NS;		
(3)(C)2.A.	WRITTEN APPROVAL FOR SP	ECIAL WASTE NOT APPR	OVED IN PERMIT.				:
(3)(C)2.B.	APPROVED SPECIAL WASTE	DISPOSED OF PROPERLY	V		<u>al Campio al Propinsi Por este del Campio de la Campio del Campio de la Campio del Campio de la Campio de la</u>	$+$ \nearrow $ $	3.757
(3)(C)3.	SIGN POSTED AT ENTRANCE	LISTING EXCLUDED WA	STES.	rain Lagrandia de la Carlo de Carlo de Lagrandia de Carlo de Lagrandia de Carlo d	the state of the s	1/	
(3)(C)4.	PROCEDURE FOR SCREENIN	IG AND REMOVAL OF EX	CLUDED WASTES.			- /	
(3)(C)5.	LARGE DEAD ANIMALS PLAC	ED IN PIT AND COVERE	O WITH FOUR FEET	OF COMPACTED SOIL	at a sa area da Canda a casa a sa area. Na a sa area gandan paraga a Marana	ープ	
	the second of th	NO MONTH AND AND AND AND AND A SERVICE AND A SERVICE AND	MITHIE DUB E MOT	ACCEPTED FUNDIOLOGAL	TO WORKING PACE	1 7	
(A) SITE SEL	ECTION MICH. SITE AC	CESSIBLE IN ALL WEATH	ER CONDITIONS.	EMPORART ROADS FILO TIDES	TO WOHAING FACE.		7 300
(4)(C)2.	LIC A DOCKER BOADS ARE ELOS	ODED ALTERNATE SANI	LARA CAMPLIER WA	/AILABLE			29 . X
1,000	Pr. 20344.60 : 2021 A. H.	the last Contracted	+::11a	and the second of the control of the	MATIONS	1 /	
(5) DESIGN	(5)(C)1. CONSTRUCTION	AND OPERATION OF THE	SITE IN ACCORDA	ANGE WITH PLANS AND SPECIF	OATIONO.	17,	
(5)(C)2.	MINIMUM 50 FOOT BUFFER	ZONE MAINTAINED:	Maria de la Companya			17	
(5)(C)3.	OPERATING MANUAL AVAIL	ABLE.	and the second second		ana m _{ag} mangm <u>aga sa sa</u>		7.7.4.1
(6) SURVEY	CONTROL		1	ACUSTOMETAVES CLEAR	Y MARKED & IDENTIFIED.		
(6)(C)1.	I WE SHILL BENCH	IMARKS, HORIZONTAL CO	NTROL STATIONS, &	CONSTRUCTION STAKES CLEAR		//	<u> </u>
(6)(C)2.	MISSING OR DISPLACED BE	NCHMARKS OR HORIZO	NTAL CONTROLS	TATIONS REESTABLISHED.		1/,	
(6)(C)3.	MISSING OR DISPLACED CO	INSTRUCTION STAKES F	HEESTABLISHED	IO ALITHORIZATION TO OPERA	TÉ.		
(6)(C)4.	MONUMENTS AND BOUNDA	ARY MARKERS PLACED P	HIGH TO HECETAIN	IG AUTHORIZATION TO OPERA			Service .
(6)(C)5.		ARKING THE ACTIVE AR	EA PLACED PHIUH	TO DEPOSITION OF WASTE.			energy)
	QUALITY	. Land Carrier Commence Commen	Aguaration of a A	PADING TO PROMOTE RUNOFF WITE	HOUT EXCESSIVE EROSION:		1
(7)(C)1.	SURFACE WATERCOURSES & RU	INOFF PROPERLY DIVERTED	CONSTRUCTION & G	RADING TO PROMOTE RUNOFF WITH		//	<u> </u>
	CONTACT BETWEEN WATE	A AND SOLID WASTE MII	NIMIZEU.	DISCHARGE OFF SITE OR DISCHARG	INTO WATERS OF THE STATE		<u> </u>
(7)(C)2.	LICTORATE CENEDATED ON SIT	E CONTROLLED ON-SITE AN	NVIOL VITOMED 10 F	Mediume at a site of		erine in de la companya de la compa Companya de la companya de la compa	
(7)(C)2. (7)(C)5.	LEACHATE GENERATED ON OUT			and the second s	974-957		
(7)(C)2. (7)(C)5.	IN WATER MONITORING		. 1994 - Tolland <u>1994 - 1994 -</u>	The second secon	Hereite La confidencia de la caración de la confidencia de la confidencia de la confidencia de la confidencia de la co La confidencia de la		<u> </u>
(7)(C)2. (7)(C)5. (8) GROUN (8)(C)1.B.	ID-WATER MONITORING GROUND-WATER-MONITORING		. 1994 - Tolland <u>1994 - 1994 -</u>	The second secon			

		SAT	10 LONG
(10) GAS C	INTROL (10)(C)1. DECOMPOSITION GAS CONTROL SYSTEMS IMPLEMENTED AS NECESSARY.	JAI	UNS
(10)(C)2.A.	METHANE NOT ALLOWED TO CONCENTRATE IN BUILDINGS ON-SITE ABOVE 25 PERCENT LEU FOR METHANE.		1 2 2 2 2 3 3 1 2 2 2 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3
(10)(C)2.B.	METHANE NOT ALLOWED TO CONCENTRATE IN THE SOIL AT THE PROPERTY BOUNDARY ABOVE 5 PERCENT LEL FOR METHANE.	رسر	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
(10)(C)3:	DECOMPOSITION OF A CONTROLLE STATE OF THE ST		r
(11) VECTO		-/	<u> </u>
(12) AESTH			<u>:</u>
(12)(C)1.	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		<u> </u>
(,,,,,,,,	LITTER CONTROL DEVICES UTILIZED AS NEEDED, LITTER COLLECTED & INCORPORATED INTO THE ACTIVE CELL AT THE END OF	1	
(IN) (O) A	EACH DAY OR PLACED IN CONTAINERS.	V .	z i szegyetety
(12)(C)2.	WASTES EASILY MOVED BY WIND COVERED AS NECESSARY.	//	1,717 av 6
(12)(C)3.	ON-SITE VEGETATION CLEARED ONLY AS NECESSARY,	/	7557 F
(12)(C)4.	SALVAGED MATERIALS REMOVED DAILY OR STORED IN AESTHETICALLY ACCEPTABLE CONTAINERS.	7,	
(13) COVER	(13)(C)1. DAILY COVER APPLIED.	1	
(13)(C)2.	INTERMEDIATE COVER APPLIED.		
(13)(C)3.	FINAL COVER APPLIED:		-
(13)(C)4.	FINAL SIDE SLOPES NOT TO EXCÉED 33.3 PERCENT.		
(13)(C)5.	VEGETATION ESTABLISHED WITHIN 180 DAYS OF APPLICATION OF REGRADING OF COVER.		7400
(13)(C)6.	REGRADING AND RECOVERING AS NECESSARY:		1
(14) COMPAC	TION (14)(C)1. SOLID-WASTE HANDLING EQUIPMENT ON-SITE AND OPERATED AS NECESSARY.		
(14)(C)1.A.	SOLID WASTE TO BE COMPACTED, SPREAD IN LAYERS NO MORE THAN 2 FEET THICK, & CONFINED TO SMALLEST PRACTICAL AREA.		A CONTRACTOR
(14)(C)1.B.	WASTE COMPAGTED TO SMALLEST PRACTICAL VOLUME.	_ 1/_	
	COVER COMPACTED AS MUCH AS PRACTICAL.		· · · · ·
/ T T T T T T T T T T T T T T T T T T T	the commence of the commence o		
	PREVENTIVE MAINTENANCE PERFORMED ON EQUIPMENT.	/,	
(14)(C)3.	SOLID WASTE NOT DISPOSED OF IN WATER.	//	
	(15)(0)1. FIRE EXTINGUISHERS PROVIDED.		Arriya yar.
	ALL FIRES IN WASTES BEING DELIVERED AT THE WORKING FACE OR WITHIN EQUIPMENT EXTINGUISHED.		N. J.
(15)(C)3.	COMMUNICATIONS EQUIPMENT AVAILABLE		# 1.25v
	SCAVENGING PROHIBITED.		1 1 1 1 1 1
(15)(C)5.	CONTROLLED ACCESS TO SITE BY ESTABLISHED ROADWAYS & LIMITED TO HOURS WHEN OPERATING PERSONNEL ARE ON DUTY.		a land
(15)(C)6.	TRAFFIC, CONTROLLED AND DIRECTED TO DISTINGUISH DISPOSING POINTS.		
(15)(C)7.	SITE DUST CONTROLLED:		
(16) RECORE	S (16)(C)1 A. RECORDS OF MAJOR PROBLEMS AND COMPLAINTS.		
	MONITORING RECORDS)
Contraction of the Contraction o	A. LEACHATE SAMPLING AND ANALYSES		<u> </u>
	B. GAS SAMPLING AND ANALYSES,]	
i.	C. GROUND- AND SURFACE-WATER ANALYSES.		
A 7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	RECORDS OF VECTOR-CONTROL EFFORTS		<u> </u>
	RECORDS OF DUST- AND LITTER-CONTROL EFFORTS.		<u> </u>
		~	1 47 . 123 1 44 . 44
	RECORDS OF QUANTITY OF WASTE HANDLED.	الما ا	
(16)(C)1.F.	RECORDS OF DESCRIPTION, SOURCES, AND VOLUME OF SPECIAL WASTES LISTED IN SUBSECTION (3)(A):		
	N SPECIFICATIONS		yasasila oo s Marakali
	EACHATE COLLECTION SYSTEM PROPERLY INSTALLED AND OPERATED.		
	INER CONSTRUCTED BY APPROVED DESIGN SPECIFICATION.		Agrand Takk
	SHOUNDWATER MONITORING WELLS INSTALLED.	7	- · · · · · · · · · · · · · · · · · · ·
	HORROW AREAS REGLAIMED.		
REMARKS			3.71.7
**	- please review comments & recomm lintering sections of the written		
1197.1 ASS 100 A	<u>and a company of the company of the</u>	Little San Land	
	ER/OPERATOR:		
This inspection	of your facility has been conducted under the authority of Sec. 260.225.1 (b) ASMo: The esentative has marked those items found in violation of the applicable environmental laws		
and requiations	adopted thereuinder perialning to your facility. Your singulary pelloy or that of your agent		•
icknowledges (i	nat you have been notified of the deficiencies and have received recommendations and mes for corrective action(s). If future inspections determine these violations persist, the		
Department may	proceed with more formal enforcement procedures as sufficiend under Sections 200 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	. 4	3
ana 260,240 ASI	40. including but not limited to the assessment of penalties in to \$1000 per doubter pack.	-1	
day, or part ther	sol, the Violation occurred, if any questions accur following your receipt of this inspection. Heturn to Compliance By:	A military	ينجين
SIGNATURE OF	Follow-up Visit Scheduled:	_/	<u> </u>
AGINA (UND UF)	OFFICE ST. Levis Regional COPY RECEIVED BY	A Mary Tiller	
1/15			
FFICE AMORES	TELEPHONE THLE	18 Maria Greek Const.	
10805 3	Survey Office Dr., St. Louis, Mo 63/27 (341) SAR-401	1995	
780-0354 (3-90		er der et er et Malder. Er et er er er er er er er er er	<u> </u>



RECEIVED NOV 0 4 1994

SWMP



October 31, 1994

Mr. Joe Trunko St. Louis Regional Office Missouri Department of Natural Resources 10805 Sunset Office Drive, Suite 100 St. Louis, Mo. 63127-1017

Re: Bridgeton Landfill, Permit Number 118912, Gas Monitoring

Dear Mr. Trunko:

Enclosed are the results of our gas monitoring program for the third quarter monitoring period. The monitoring was conducted in accordance with our previously submitted monitoring plan and our letter of April 8, 1994. A summary of the results follows:

Perimeter monitoring: Bar punch monitoring was conducted at the property line at the locations indicated on the enclosed map. The additional locations written on the map were randomly selected for additional monitoring. All bar punch tests were conducted by driving a 3/8 inch rod 3 feet into the soil, removing the rod and inserting a hose connected to a GEM-500 gas extraction monitor. All bar punch monitoring showed zero methane migration.

Continuous Monitoring: We have installed GHD 2000 gas monitors in five separate onsite buildings. These monitors are set to alert occupants should gas levels reach 5-15% of the LEL, well below the 25% Missouri standard. There has never been an event indicated by our alarm system suggesting concentrations of methane approaching the 25% standard.

Also, I am updating you as to the status of our underground fire and any future fires. The existing fire, which at one time we believed to be extinguished, is now believed to have reignited. Due to settlement from the installation of Sed Pond #1 the fissure has opened up. We plan to regrout the fissure which should result in sealing off the air, thus extinguishing the fire.

Further, I would like to notify you of another possible fire, adjacent to Taussig Road, about half way between St. Charles Rock Road and the Methane Flare. We have seen some smoke and are currently developing a plan to investigate and remediate if necessary.

If you have any questions regarding our monitoring program and procedures, please call.


Singerely,

Larry/Giroux General Manager

CC: Mr. Frank Dolan, MDNR

Mr. Brad Bomanz, St. Louis County DOH

LG:jg



ST. LOUIS COUNTY HEALTH DEPARTMENT MO DEPT OF NATURAL ST. LOUIS RESIDINAL WASTE MANAGEMENT SECTION

SANITARY LANDFILL SURVEILLANCE RECORD

te: 12/01/94 Days/Week Open: 6	Estimated amount of solld waste coming through gate. Compacted Loads 37,500 yds./wk. tons/wk.
te: 12/01/94	Noncompacted Loadsyds./wktons/wk. Noncompacted Loadsyds./wktons/wk. Estimated volume of remaining landfill covered by approved engineering.
wher: Laidlaw Waste Systems Idress: 13570 St. Charles Rock Road Bridgeton, MO 63044	plans acre(s) 10 years

Ordinance 13,320 Chapter 607 Compliance Status

Check all sections: SAT-Satisfactory; UNS-Unsatisfactory; * - Area(s) requiring additional attention. Satisfactory Compliance Section UNS SAT Operating Procedure Satisfactory Compliance Number Section UNS SAT Operating Procedure WATER QUALITY Number Surface water courses diverted. FACILITY PLAN 730.11 Operations comply with facility plan-Grading promotes surface water runoff 720.0 X without excessive erosion. SOLID WASTE HANDLING Grading does not exceed 33 1/3%. Bulky waste crushed and pushed to hottom Surface water courses and runoff control X 730.5 X of cell. 20 year rainfall. Demolition and construction waste, tree X Minimum 15 feet between waste and stumps, etc. pushed to bottom of cell. 730.6 X 730.12 maximum water table. Dead animals under 40 lbs. covered X Water quality protection secure (ie, liner, 730.7 X 730.13 immediately. bedrock). Dead animals over 40 lbs. placed in pit and X Leachate and treatment systems used 730.8 covered with 4 ft. of compacted soil. X 730.14 where necessary. Water treatment plant sludges incorporated X Ground/surface water not contacting waste Into active face and covered immediately. 730.9 730.15 All drinking water sources within 1/4 mile Quantity of sludges does not interfere with X 730.36 sampled annually. normal active face operation. Incinerator and air pollution control residues COVER MATERIAL 730,10 incorporated into working face and χ Minimum of 8 inches approved cover prevented from becoming airborne. 730.3 applied daily. X Minimum 15 day stockpile of daily cover. SOLID WASTE EXCLUDED Intermediate cover (min. 1 ft. after Responsible supervisor present. compaction) applied to all areas idle more 730.32 730.4 Entrance sign posted listing wastes not X 760.0 than 60 days. accepted. Final cover (min. 2 ft. after compaction) 730.33 applied to completed areas. SAFETY Fire extinguishers provided on all equipment X 730.25 COMPACTION X Provisions made for extinguishing fires. Solid waste spread in layers not to exceed 730.26 Communications equipment met standard. X Χ 2 ft. and reduced to smallest volume. 730.1 730.27 X Waste confined to smallest practical area Scavenging prohibited. 730.28 730.2 χ Controlled access limited to operating hours on working face. 730,29 Adequate equipment maintained and Traffic directed to designated disposal 730.24 730.30 X operated. points. Dust control adequate. 730.31

Section Numberly	Satisfactory Compliance	SAT		UNS	Section Number	Satisfactory Compliance Operating Procedure	SAT	* UN	
AIR QUALITY				VECTORS					
730.16 No open burning without permission.				730:19 Vector control programs implemented. X					
GAS CONTROL				RECORDS					
730.17	Decomposition gas control implemented.	X		9 V.	730.35	Records maintained to cover:		**	
730.18	Gases vented to prohibit explosive or toxic accumulations.	Х				Major problems and complaints. Monitoring of leachate, gas, ground, and	X		
AESTHETICS					surface water sampling and analyses.	X	<u>. 3</u>		
730,20	Litter control devices used properly.	Υ		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		c. Vector control efforts.	X		
	Litter collected and secured daily.	x		Parker Call		d. Dust and litter control efforts.	X V	20 30 80 80 80 80 80 80 80 80 80 80 80 80 80	
730.21	Blowable waste covered promptly.	Х		X	e. Quantity of waste handled.				
730.22	Vegetation and natural windbreaks used where necessary.	x	5 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	AT A S	<i>BONDING</i> 690,1	Operating bond adequate:	l x l		
730.23	Salvaged materials stored or removed daily.	X	e reary e i i i i i	8 42 2	CLOSURE				
730,34	Final vegetation planted and graded as required.	X	i 19 S		790.1	Final cover and vegetation provided.	x]		

Weather Conditions: Clear, sunny 60° and windy.	
Observed With: Brad Bomanz, DOH	.:::f
Consulted With: Same	
Additional Remarks/Comments: UNSATISFACTORY ITEMS/RECOMMENDATIONS	*
Leachate levels in LCS 2 and LCS 1 are in violation of Missouri DNR Operations permit which	· ·
requires levels not to exceed 30 feet above the base of the pump. Remediation efforts	
implemented since the last inspection were successful in achieving compliance at the end of	
October. Recent violation for LCS 1 is attributed to an accident which resulted in damage t	ž o
a section of the well that allowed trash to enter the well. Pumping of LCS 1 can not resum	ne
until the trash is removed. Bids are being obtained to remove the trash. Non-compliance in	<u>1</u>
LCS 2 may be due to overloading from LCS 3 and LCS 4 which are pumped to LCS 2 prior to	
discharge to the lagoon. This item was discussed in depth with Mr. Larry Giroux. Laidlaw	ingine <u>Herw</u>
believes sediment accumulation may be part of the problem in maintaining compliance levels i	
LCS 1. A fan will be purchased that will suspend sediment into the leachate allowing the pur	np
to remove both the leachate and the sediment. Please inform DOH when pumping of LCS 1 resum	
and continue to submit monthly monitoring reports. (720.0)	Water .
cc: CONTINUED ON PAGE 2 Signature of Inspector	

Signature of Section Chief

Settlement is occurring along the East wall of Pit I causing several fizzures. Laidlaw is concerned that there may be a fire in this area. Please keep DOH informed of the investigation into this matter. Additional cover is needed over the fissures and the area recontoured. (730.11)

Ponding is occuring in the southwest portion of Pit 3 near LCS 4. Remove this excess surface water and regrade the area to allow diversion of surface water. (730.11)

COMMENTS

Gas tests have confirmed that the fire which recently reignited in Pit 2 is no longer active. Settlement from the retention basin caused fissures along the pit wall. These areas will be regrouted.

The location of the active face in plt prohibited the compactor from being able to move past the base of the lift and effectively push and shred the waste. This resulted in a large active face and less than desirable compaction methods but should be a temporary situation.

The commingled lead contaminated soils from the Federal Couthouse (City Block 205S) site remain tarped and bermed. Currently there are no stockpiles of petroleum contaminated soils to be utilized as alternative daily cover. When stockpiling this material begins, the soils will be placed at the southern end of Pit 3 and identified with appropriate signage. Some petroleum contaminated soils were placed at the active face near the clean fill for use at the end of the day.

All other special wastes from the Couthouse site are being incorporated into the active face.

The new access road to Pit 3 has been completed. Dust control was good and the roadways well maintained.

Signature of Inspector

Signature of Section Chief

cc: Larry Giroux, Laidlaw - Operations Mgr. John Boonstra, Laidlaw - Regional Division Mgr. Bob Eck, MDNR-SLRO Richard Houchin, Bridgeton City Hall



LAIDLAW WASTE SYSTEMS INC.

RECEIVED

MAR 3 1 1995

March 29, 1995

Mr. Jim Bell Chief, Enforcement Section Solid Waste Management Section P.O. Box 176 Jefferson City, Missouri 65102 SWMP

Re: Bridgeton Landfill, Permit Number 118912, Gas Monitoring

Dear Mr. Bell:

Enclosed are the results of our gas monitoring program for the 1st quarter monitoring period. A summary of the results follows:

Perimeter monitoring: Bar punch monitoring was conducted at the property boundary at the locations indicated on the enclosed map. The additional locations written on the map were randomly selected for additional monitoring. All bar punch tests were conducted by driving a 3/8 inch rod 3 feet into the soil, removing the rod and inserting a hose connected to a GEM-500 gas extraction monitor. All bar punch monitoring showed zero methane migration.

Continuous Monitoring: We have installed GHD 2000 gas monitors in five separate onsite buildings. These monitors are set to alert occupants should gas levels reach 5-15% of the LEL, well below the 25% Missouri standard. There has never been an event indicated by our alarm system suggesting concentrations of methane approaching the 25% standard.

I would like to take the opportunity to update you as to the status of our underground fire. The original fire, which we believe had reignited, shows no signs of activity. This fire appears to be related to the TRW gas collection wells. At the present time these wells are not active and the fire does not appear to show any activity. We will continue to monitor the fissure along the quarry wall for any signs of combustion. In a previous letter from Mr. Larry Giroux, LWS to Mr. Joe Trunko MDNR St. Louis Region, dated October 31, 1994, their was mentioned a possibe new fire. At the present time their is no sign of this fire. We will continue to regrout and monitor these areas as necessary.

If you have any questions concerning our monitoring program and procedures, please do not hesitate to contact me at 739-1919.

Sincerely;
Blad Pollock

Brad Pollock

Operations Manager

cc: Mr. Terry Hoevelkamp, MDNR St. Louis Region

Mr. Brad Bomanz, St. Louis County DOH



LAIDLAW WASTE SYSTEMS INC.

June 30, 1995

Mr. Jim Bell Chief, Enforcement Section Solid Waste Management Section P.O. Box 176 Jefferson City, Missouri 65102 RECEIVED Jul 031995

Re: Bridgeton Landfill, Permit Number 118912, Gas Monitoring

Dear Mr. Bell:

Enclosed are the results of our gas monitoring program for the 2nd quarter monitoring period. A summary of the results follows:

Perimeter monitoring: Bar punch monitoring was conducted at the property boundary at the locations indicated on the enclosed map. The additional locations written on the map were randomly selected for additional monitoring. All bar punch tests were conducted by driving a 3/8 inch rod 3 feet into the soil, removing the rod and inserting a hose connected to a GEM-500 gas extraction monitor. All bar punch monitoring showed zero methane migration.

Continuous Monitoring: We have installed GHD 2000 gas monitors in five separate onsite buildings. These monitors are set to alert occupants should gas levels reach 5-15% of the LEL, well below the 25% Missouri standard. There has never been an event indicated by our alarm system suggesting concentrations of methane approaching the 25% standard.

The underground fire which was located along the northern quarry wall, immediately north of Sed-Basin 1, shows no signs of activity.

If you have any questions concerning our monitoring program and procedures, please do not hesitate to contact me at 739-1919.

Sincerely;

Brad Pollock

Operations Manager

Brod Pollick

cc:

Mr. Terry Hoevelkamp, MDNR St. Louis Region

Mr. Brad Bomanz, St. Louis County DOH

Figure 3.5.1

		₹ ₹	<u>5</u>	**			İ
I carefy that these data were obtained is accordance with applicable regulatory and project protocols: Signature: Date: / /	Prot. Csg. in Good Condition? Concrete Pad Intact? Padlock Functional? Inner casing properly capped? Sample litting in Good Condition?	Monitoring Probe Construction: Total Depth (feet): Depth to Top of Screen (feet): Monitoring Probe Condition: Clearly Labeled?	LOCATION IDENTIFICATION:	MONITORING LOCATION TYPE: **** Monitoring Probe: Bashole Probe: Continuous Monitor: Hand Held (Ambient):	Ster Brighton Land 6111 Personnel: Du Dessent Deter	LAIDLAW WASTE SYSTEMS	
ance with applicable regula	DYES DNO	3 feet CH, B C, 28,5%	# 1 3155 pm	(Mas separah Fluid Data Shares to sech type si daraj 6: 9 7: 0 7: 0 7: 0 7: 0	S1, 142 (7 30)	STE ŞYSTEM	
wary and project protocols:	0 Yes 0 No	3 fect CHy B Ch 1992	# 2 4:02pm	FIELD INSTRUMENTATION: LEL Meter: Mod. No.: Pressure Gauge: Mod. No.: Water Level Met; Mod. No.: Other: Mod. No.:	METEOHOLOGIC DATA: Ambient Temperature: 78° D Medsurement Sta.: 0 NOAA;	AS	FIGUI
	DYS DNO	CHU CONO	# 3 4,12pm	Gen So	ASON.		FIGURE 3.5.1
	00000	CHY DO	#4.22pm	Attach calibration data) SN: 277 C SN: 277 C SN: C SN: C	Attach d Barometric Prossure: 23 El-On-site	EXPLOS	•
!		3 feet 010 000	#5 4.40pm	alib. Dale/Time: 6 alib. Dale/Time: alib. Dale/Time: alib. Dale/Time:	Attach data from preceding days (Optional) Pressure: 24,6 ft (inches Hg.) El-On-sile Cl Other:	EXPLOSIVE GAS MONITORING FIELD DATA SHEET	
	Yes Yes Yes Yes	SKeer One	#6 4;45pm	13998 3:15" 	ng days (Optional) .)	TORING ET	
		ENCINEERS OF	SOS	11 2817 72	+ 'CTS.	ET:91	

FIGURE 3.5.1

No. 201441				Oale: / /	dense with opposite regu	Confly find times data were extended in accordance with applicable regulatory and project protocols. Signature: Date: / /
LI Yes LI NO	Li Yes Li No	☐ Yes ☐ No	□ Yes □ No	O Yes CI No	Cl Yes Cl No	Sample hilling in Good Condition?
DYes DNo	Yes D			CI Yes CI No	CI Yes CI No	inner casing properly capped?
CI Yes CI No	CI Yes CI No	CI Yes CI No	□ Yes □ No	D Yes D No	☐ Yes ☐ No	Padlock Functional?
DYes DNo	DY95 DNo	OYes DNo	□ Yes □ No	□ Yes □ No	CI Yes CI No	Concrete Pad Intact?
O Yes O No		D Yes D No	□ Yes □ No	□ Yes □ No	DYes CI No	Prot. Csg. in Good Condition?
OYBS CINO		Q Yes Q No	C Yes C No	CI Yes CI No	CI Yes CI No	Clearly Labeled?
						Monitoring Probe Condition:
					02 20.6%	Depth to Top of Scroen (feet):
					CHUE	Total Depth (feet):
			•		3 Feet	Honitoring Probe Construction:
					4:52	LOCATION IDENTIFICATION:
	Cafb. Dale/filme: /	SN:	Mod. No.:	Other:		Hand Held (Ambient):
	Callb. Date/Time:		Mad. No.:	Water Level Met;		Continuous Munitor:
	Calib. Date/Time:	SA:	Mod. No.:	Pressure Genge:	7	Surhole Probe:
185 5 15	6/39	SM: 279	Wood. Na.: Gen See	LEL Motor:	p	Monitoring Probe:
		(Altech cosbration data)	_	HOLLVANDMINALSM GTELL	esperate Field Orde II for each type of desail	WOULD BE AND WASHINGTON TO THE STREET OF THE
7	sile C Other:	Q-On-sile	: O NOAA:	Measurement Sta.: CI NOAA;	te: 6/29/95	Personnel: Tin JOhnson Date: 6 1291 95
	rossuro: 39.6 R (Inchos Hg.)	Darometric Prossure:	78.	Ambiont Temperature:	•	
	Attach data from preceding days (Optional)	Atter		METEOROLOGIC DATA:	11.7 P	11. JPNHT MOLD BUILD SI HIS
HING	FIELD DATA SHEET	EXPLOS		AS	STE SYSTEM	LAIDLAW WASTE ŞYSTEMS

66 /70 /CE



RECEIVED

OCT 0 4 1995

SWMP

LAIDLAW WASTE SYSTEMS INC.

September 29, 1995

Mr. Jim Bell Chief, Enforcement Section Solid Waste Management Section P.O. Box 176 Jefferson City, Missouri 65102

Re: Bridgeton Landfill, Permit Number 118912, Gas Monitoring

Dear Mr. Bell:

Enclosed are the results of our gas monitoring program for the 3rd quarter monitoring period. A summary of the results follows:

Perimeter monitoring: Bar punch monitoring was conducted at the property boundary at the locations indicated on the enclosed map. The additional locations written on the map were randomly selected for additional monitoring. All bar punch tests were conducted by driving a 3/8 inch rod 3 feet into the soil, removing the rod and inserting a hose connected to a GEM-500 gas extraction monitor. All bar punch monitoring showed zero methane migrations.

Continuous Monitoring: We have installed GHD 2000 gas monitors in five separate onsite buildings. These monitors are set to alert occupants should gas levels reach 5-15% of the LEL, well below the 25% Missouri standard. There has never been an event indicated by our alarm system suggesting concentrations of methane approaching the 25% standard.

The underground fire which was located along the northern quarry wall, immediately north of Sed-Basin I, shows no signs of activity.

If you have any questions concerning our monitoring program and procedures, please do not hesitate to contact me at 739-1919.

Sincerely;

Brad Pollock

Operations Manager and the second sec

cc: Mr. Terry Hoevelkamp, MDNR St. Louis Region

Mr. Brad Bomanz, St. Louis County DOH

is a graph for a linear energy of the control of th

LAIDLAW

LAIDLAW WASTE SYSTEMS INC.

October 3, 1995

Mr. Brad Bomanz, Waste Specialist III St. Louis County Department of Health Waste Management Section 111 South Meramec Avenue Clayton, Missouri 63105

Dear Mr. Bomanz:

File Hobe

OCT 06 1995

SWMP

The purpose of this letter is to update you on recent events at the Bridgeton Sanitary Landfill concerning underground combustion. This site has historically experienced evidence of underground fires in two locations. The first being located adjacent to the quarry wall in the immediate vicinity of sed-basin 1. This area is monitored daily and there has been no evidence of further combustion in this area. The second and most recent location of underground combustion was located in the vicinity of the gas collection well W-4 which is located in the northern inactive area. This area is also monitored on a daily basis and again, no further evidence of combustion has been observed.

As part of the Remedial Investigation and Feasibility Study (RIFS) for Operable Unit 1 (OU1), soil borings were conducted in the area immediately west of W-4; the closest boring being approximately 75 feet from this well. During the course of the excavation of this material, it was reported to Laidlaw by McLaren Hart that some of the material appeared to have elevated temperatures; the highest temperature recorded being 140°F. According to the report prepared for Laidlaw by SCS Engineers in the remediation of the underground fire located near sed-basin 1, this is considered to be in the normal temperature range for deep landfills such as Bridgeton. It should be noted that no physical evidence of combustion was present: that is, no blackened or charred material and no smoke.

Due to the close proximity of this boring to an area with a history of underground combustion we are currently conducting temperature investigations in the well field. With the exception of W-2, all ten wells have been investigated by using a Type K. Thermocouple thermometer attached to a 100 ft. cable. This device allows for quick temperature readings at different depths. As the attached table shows, some of the wells contain temperatures above the 140°F mark. At the present time we do not believe that these temperatures are an indication of present combustion and in fact may still be in what can be considered normal temperature ranges. We are continuing to research and investigate these findings and will keep you informed as to our progress.

Should you have any questions concerning this matter please do not hesitate to contact me at 739-1919.

Sincerely,

Brad Pollock

Operations Manager

c: Mr. Larry Giroux, LWS

Mr. Doug Borro, LWS

Mr. John Workman, P.E., LWS

Brod Pollock

Mr. Dennis Wike, LWS

Mr. Lee Tharp, P.E., MEC

Mr. Ward Herst, CPHG, CEM, Golder Associates

Mr. David Heinze, McLaren Hart

Mr. Frank Dolan, P.E., MDNR-SWMP



LAIDLAW WASTE SYSTEMS INC.

January 31, 1996

Mr. Jim Bell
Chief, Enforcement Section
Solid Waste Management Section
P.O. Box 176
Jefferson City, Missouri 65102

ASCE/VED FEB 13 1998

Re: Bridgeton Landfill, Permit Number 118912, Gas Monitoring

Dear Mr. Bell:

Enclosed are the results of our gas monitoring program for the 4th quarter monitoring period. A summary of the results follows:

Perimeter monitoring: Bar punch monitoring was conducted at the property boundary at the locations indicated on the enclosed map. The additional locations written on the map were randomly selected for additional monitoring. All bar punch tests were conducted by driving a 3/8 inch rod 3 feet into the soil, removing the rod and inserting a hose connected to a GEM-500 gas extraction monitor. All bar punch monitoring showed zero methane migration.

Continuous Monitoring: We have installed GHD 2000 gas monitors in five separate onsite buildings. These monitors are set to alert occupants should gas levels reach 5-15% of the LEL, well below the 25% Missouri standard. There has never been an event indicated by our alarm system suggesting concentrations of methane approaching the 25% standard.

The underground fire which was located along the northern quarry wall, immediately north of Sed-Basin 1, shows no signs of activity.

If you have any questions concerning our monitoring program and procedures, please do not hesitate to contact me at 739-1919.

Sincerely:

Brad Pollock

Operations Manager

cc: Mr. Terry Hoevelkamp, MDNR St. Louis Region

Mr. Brad Bomanz, St. Louis County DOH

gasđeo



11/

LAIDLAW WASTE SYSTEMS INC. July 1, 1996

Mr. Jim Bell Chief, Enforcement Section Solid Waste Management Section

P.O. Box 176 Jefferson City, Missouri 65102 RECEIVED

JUL 0 5 1996

SWMP

Re: Bridgeton Landfill, Permit Number 118912, Gas Monitoring

Dear Mr. Bell:

Enclosed are the results of our gas monitoring program for the 2nd quarter monitoring period. A summary of the results follows:

Perimeter monitoring: Bar punch monitoring was conducted at the property boundary at the locations indicated on the enclosed map. The additional locations written on the map were randomly selected for additional monitoring. All bar punch tests were conducted by driving a 3/8 inch rod 3 feet into the soil, removing the rod and inserting a hose connected to a GEM-500 gas extraction monitor. All bar punch monitoring showed zero methane migration.

Continuous Monitoring: We have installed GHD 2000 gas monitors in five separate onsite buildings. These monitors are set to alert occupants should gas levels reach 5-15% of the LEL, well below the 25% Missouri standard. There has never been an event indicated by our alarm system suggesting concentrations of methane approaching the 25% standard.

The underground fire which was located along the northern quarry wall, immediately north of Sed-Basin 1, shows no signs of activity.

If you have any questions concerning our monitoring program and procedures, please do not hesitate to contact me at 739-1919.


Sincerely:

Larry Giroux

Sr. Division General Manager

ce: Mr. Terry Hoevelkamp, MDNR St. Louis Region

Mr. Brad Bomanz, St. Louis County DOH



au all twick groties, ou

a propresentation of the

FIGURE 3.5.1

LAIDLAW WASTE SYSTEMS	TE SYSTEM	SI		EXPLOS	EXPLOSIVE GAS MONITORING FIELD DATA SHEET	ORING	
Stte: RAID 9eTON Personnel: Tim JOhnson Dat	Stto: BRID 9CTON SLF Personnel: Tim JOhnson Date: 6128196	METEOROLOGIC DATA: Amblent Temperature: 93° Mecsurement Sto.: ロ NOAA:	13° . NOAA:	Attach data from preceding Barometric Pressure: 39,76 (Inches Hg.) E-On-sile Other:	Attach data from preceding days (Optional) and: 39,70 (Inches Hg.) On-site Other:	ig days (Optional)	
MONITORING LOCATION TYPE: (No. separat. Full Out.) Monitoring Probe: Cl. Bathole Probe: Cl. Continuous Monitor: Cl. Hand Held (Amblent): Cl.	operate Fitt Date the seath type of decay []	FIELD INSTRUMENTATION: LEL Meter: Mod. No.: Pressure Garge: Mod. No.: Water Level Met; Mod. No.: Other: Mod. No.:	3 4 50	(Attach calibration data) SN: Gen 100 C SN: Con 100 C SN: Con 100 C SN: Con 100 C	a) Calib. Date/Thns: 6 128/96 Calib. Date/Thns: 1 Calib. Date/Thns:	14. 8 36120	-3
LOCATION IDENTIFICATION:	1 5,17	LFG 2	LFC 3	LAG 4	LPC 5-	7 9,57	
Monitoring Probe Construction: Total Depth (feet): Depth to Top of Screen (feet): Monitoring Probe Condition:	3 BArbole NA NA	3' BAThole	3 BANDOLE	3, BARHO12	3'BARbole 10A NA	3 - RAPADIE NA NA	
Clearly Labeled? Prot. Csg. in Good Condition?	CIYes CINO	CI Yes CI No	O Yes O No	CI Yes CI No	O Yes O No	O Yes O No	
Concrete Pad Intact? Padiock Functional?	CIYes CINO	CIYes CINO	O Yes O No	O Yes C No	O Yes O No	C) Yes CI No	
Irnor casing property capped? Sample fitting in Good Condition?	CIYes CINO	C) Yes () No /	CIYES CINO	DY85 DNa /	O Yes CI No	C) Yes C) No	
La were colored and in excess	Jance with explicable regula	Contify that these data was obtained in accordance with explicable regulatory and project protocole: Signatures: Date: 6/28/96	9,			Acc. 15(10)	
		•					

COMPRESSED GAS FROM LANDEN CONTROL FEC.

CALIBUATION:

So,0% methode Son Son Son

35,0 % CORBON DIOXIDE BALANCE - NITROBEN

STO TO OXYGEN BAIMNOE - CARBON DIOX 1:06

0.11117613243774324939344793

03/02/94	15:13	2513.421 2847	SCS ENGINEERS OH
()	TORING ET	ding days (Optional) 19.5 128.196 13.976 13.976 14.76	C Yes C No C Yes C No
	EXPLOSIVE GAS MONITORING FIELD DATA SHEET	h data from prace 24, to (inches h site □ Other; alib. Date/Time; alib. Date/Time; alib. Date/Time;	☐ Yes ☐ No ☐ Yes ☐ No
	EXPLOS	Attach data from praceding Barometric Pressure: 27,70 (inches Hg.) El-On-site D Other: SN: 6cm /4c Calib. Date/Time: 6 18 SN: 6cm /4c Calib. Date/Time: 7 ☐ Yes ☐ No ☐ Yes ☐ No ☐ Yes ☐ No ☐ Yes ☐ No ☐ Yes ☐ No	
E 3.5.1		o . AAA: sem Ste	1 Yes 10 No 10 Yes 10 No
FIGURE 3.5.1	S	TECHOLOGIC Dibiont Temperatures assure Gatage: alar Level Melt; her:	CI Yes CI No CI Yes CI
•	TE SYSTEM	92	S' BARhofe NA NA CON
	LAIDLAW WASTE SYSTEMS	She: BRIDGCTON SLA Personnel: Tim JOhnSon Date: 6185/96 MONITORING LOCATION TYPE: She is sen by a dead Monitoring Probe: D Barhole Probe: D Continuous Monitoring: D Hand Heid (Ambient): D	Honitoring Probe Construction: Total Depth (feed): Depth to Top of Screen (feet): Monitoring Probe Condition: Clearly Labeled? Concrete Pad Intact? Prof. Csg. in Good Condition? Concrete Pad Intact? Conc

15:14

FIGURE 3.5.1 (CONTINUED)

LAIDLAW WASTE BYSTEMS		•		m #_	EXPLOBIVE GAS MONITURING . FIELD DATA SHEET – page 2 of 2	TCRING page 2 of 2
su. BRIDGETON S	2778					
Parsonnat I'm Johnson	Dets: 6 128176	gi				
LOCATION IDENTFICATION:	1 517	r 5+7	74C3	h. 9#7	L FG 5-	9 947
Fleid Mousureinentst		•				
. 1. Furn on instrument and walt for Main Manu Screen to appear.				,		
			v			
Select 2 - No, unless data is to be stored. Gas Levels Screen will appear.			*4"			•
5. Press Kay 5 - Pump loturin pump on and drawn gas sample						÷
Wall of least 45 seconds and record data:	2/ 0 × 00	07, 0 % 00 00 % 00 720	8, × 0 %	00	9% 0 % 8 8 6 % 8	المرام
	97.8% south as	0,% 20,07 Bahnca 79,78	0,8 40/ Salma 29.81	Outena 79.9	0,% 40,3 Bulina 79,69	0,X 40,/
 Saled Kay i to display LEL Screen and record dita; 	0 0 % EI	Gas % O 10	% O % EI	0.0% C % C 10 10 10 10 10 10 10 10 10 10 10 10 10	01.x O %	Carx O %0
7, Salact a - Edito returnto read · Cae Levris Screen.	9.00 Am	9: 4 AM	9:23 Am	4:30 Am	~05ib	9:38 Am
4. Balect Key—1 Continue.	•					•
9. Select 3-Zero. Presume follow instructions. Be sure to decormed hoses before zeroing pressure (Key-1).	\			1		
10. Select Key-O Exit. Pecord:	Static Pressure Dif Pressure (frapplicable)	Static Pressure Off Pressure (Fappitentie)	Statio Persons Dit Presons (fappleable)	Static Pressure DR Pressure (dapplicable)	Batto Pressure Off Pressure (fapplicable)	Sallo Pressure Oil Pressure (Rapplicable)
11. Select Key-0 Exi will General Lilibe Screen remppears.						
12. To continue montoring stat at Stap 6. To quit, axit using Kay -0.						"]

Dit as Differential Pressure This is a quicknessernor guide and not intended as a substitute for the Operations Namual for the CEM-500.

гистивада, фомпичето)

				-	FIELD DATA SHEET – page 2 of 2	. page 2 of 2
Sw. BRIDgeTow	£18.	1				
Personnet Tim Januson	Des. 6 198796		•			
LOCATION IDENTFICATION:	2 277			-		
Field Moururements:				,		
. 1. Turn on finds unsert and wall for Alin Menu Screen to Appear.						
2. Saisott - Pand Can Lavel	•		١			
5. Select 2 - No, unless this into ten shored			•			
4. Gas Levele Screen will appear.			**			
5. Press Kay 6 - Pump letten pump on and draw a gas samble				•		÷
Wall of least 45 seconds and record data :	A. C. S. C.	x 75	CH, W	04.8 80.8	8, 8 8, 8 8, 8	CH,%
	0,15 27.0 Belance 74.9	O.S.	O,% Baltimos	O. W.	D.% Buknos	Palanca Palanca
6. Soloct Key 1 to deptay LEL Screen and record data:	Gr. 8 0 %	Gas % 1EL %	8 E1	% -B1 % -B1	04.8 Let.8	(b) %
7. Select 0-Eather return to ward · Cas Levels Screen.	4:50 Am					
8. Salvet Kay-1 Continue.						
Select 3 – Zero. Pessums follow instructions. In sure to decounsed hoses before zeroing pressure (Key-1).			•			
10, Select Key-O Exit. Record:	Statio Pressure Dif Pressure (Repaire bie)	Static Pressure Dit Pressure (Napplicable)	Static Pressure Dir Pressure (dapples bis)	Static Presure Dit Presure (depploable)	Gallo Pressure DR Pressure (Rapploable)	Sallo Pressure Dil Pressure (dapplicable)
11. Select Key-0 Exit util Ceneral Ulities Sersen reappears.						
12. To portinue montoring start at Step 5. To quit, and uning fey -0.						

DR = Offenstial Persus This is a girly reference gaids and not intended as a existivite for the Operations Manual for the GEM-500.



RECEIVED

OCT 68 1997

SWMP

October 6, 1997

Mr. Jim Bell
Chief, Enforcement Section
Solid Waste Management Section
P.O. Box 176
Jefferson City, Missourt 65102

Re: Bridgeton Landfill, Site Operating Permit Number 118912 Third Quarter Gas Mountoring

Dear Mr. Bell:

Enclosed please find the Landfill Gas Monitoring report for gas inigration, performed by Bridgeton Landfill associates. Temperatures are continuously being monitored in the twelve gas wells located in the northern inactive portion of the permitted area. There is currently no activity or evidence of fire located adjacent to the quarry wall in the vicinity of the TRW wells.

Should you have any questions, please do not hesitate to call. (314) 739-1919 extension 109.

Sinderely

Jacinta Douma

Technical Administrative Assistant

ce: Brad Bomanz, St. Louis County Department of Health Terry Hoevelkamp, MDNR/St. Louis Region