

STATE OF MISSOURI
DEPARTMENT OF NATURAL RESOURCES
MISSOURI CLEAN WATER COMMISSION



CONSTRUCTION PERMIT

The Missouri Department of Natural Resources hereby issues a permit to:

Gene Gould
Owner
Benton Ridge Winery and RV Park WWTF
24744 Hwy BB
Warsaw, MO 65355

for the construction of (described facilities):

See attached.

Permit Conditions:

See attached.

Construction of such proposed facilities shall be in accordance with the provisions of the Missouri Clean Water Law, Chapter 644, RSMo, and regulation promulgated thereunder, or this permit may be revoked by the Department of Natural Resources (Department).

As the Department does not examine structural features of design or the efficiency of mechanical equipment, the issuance of this permit does not include approval of these features.

A representative of the Department may inspect the work covered by this permit during construction. Issuance of a permit to operate by the Department will be contingent on the work substantially adhering to the approved plans and specifications.

This permit applies only to the construction of water pollution control components; it does not apply to other environmentally regulated areas.

September 8, 2020
Effective Date


Edward B. Galbraith, Director, Division of Environmental Quality

September 7, 2022
Expiration Date


Chris Wieberg, Director, Water Protection Program

CONSTRUCTION PERMIT

I. CONSTRUCTION DESCRIPTION

Construction is for a proposed RV campground with a shower house, ice cream shop, and a restaurant. Flows generated from the RV hook-ups, ice cream shop, and restaurant will receive primary treatment in septic tanks before flowing to proposed subsurface dispersal fields. In total 13 systems will be constructed to receive, treat, and disperse flows to the soils by conventional gravity dispersal or low pressure piping (LPP).

The septic systems will serve the following RV spots, ice cream shop, restaurant, and bath house:

System #	Service Site	Flow (gpd)	Pop. Equiv.
1	RV 1-7	720	21
2	RV 9-14	720	21
3	Restaurant	840	154
4	RV 15-22	720	24
5	Shower/Ice Cream	735	75
6	RV 23-30	720	24
7	RV 31-38	720	24
8	RV 39-46	720	24
9	8 future RV spots	720	24
10	5 future RV spots	450	15
11	8 RV or 2nd shower	720	24
12	8 future RV spots	720	24
13	8 RV or 2nd shower	720	24
		9,225	478

A closure plan will need to be submitted to the Kansas City Regional Office for review and approval prior to any closure activities related to existing wastewater structures.

This project will also include general site work appropriate to the scope and purpose of the project and all necessary appurtenances to make a complete and usable wastewater treatment facility.

II. COST ANALYSIS FOR COMPLIANCE

Pursuant to Section 644.145, RSMo, when issuing permits under this chapter that incorporate a new requirement for discharges from publicly owned combined or separate sanitary or storm sewer systems or publicly owned treatment works, or when enforcing provisions of this chapter or the Federal Water Pollution Control Act, 33 U.S.C. 1251 et seq., pertaining to any portion of a publicly owned combined or separate sanitary or storm sewer system or [publicly owned] treatment works, the Department of Natural Resources shall make a “finding of affordability” on the costs to be incurred and the impact of any rate changes on ratepayers upon which to base such permits and decisions, to the extent allowable under this

chapter and the Federal Water Pollution Control Act. This process is completed through a cost analysis for compliance. Permits that do not include new requirements may be deemed affordable.

The Department is not required to complete a cost analysis for compliance because the facility is not a combined or separate sanitary sewer system for a publically-owned treatment works.

III. CONSTRUCTION PERMIT CONDITIONS

The permittee is authorized to construct subject to the following conditions:

1. This construction permit does not authorize discharge.
2. All construction shall be consistent with plans and specifications signed and sealed by OCD Services, LLC and as described in this permit.
3. The Department must be contacted in writing prior to making any changes to the plans and specifications that would directly or indirectly have an impact on the capacity, flow, system layout, or reliability of the proposed wastewater treatment facilities or any design parameter that is addressed by 10 CSR 20-8, in accordance with 10 CSR 20-8.110(11).
4. State and federal law does not permit bypassing of raw wastewater, therefore steps must be taken to ensure that raw wastewater does not discharge during construction. If a sanitary sewer overflow or bypass occurs, report the appropriate information to the Department's Kansas City Regional Office per 10 CSR 20-7.015(9)(G).
5. The wastewater treatment facility shall be located at least fifty feet (50') from any dwelling or establishment.
6. The wastewater treatment facility shall be located above the twenty-five (25)-year flood level.
7. The wastewater facility structures, electrical equipment, and mechanical equipment shall be protected from physical damage by not less than the one hundred- (100-) year flood elevation per 10 CSR 20-8.140(2)(B). The minimum distance between wastewater treatment facilities and all potable water sources shall be at least three hundred feet (300') per 10 CSR 20-8.140(2)(C)1.
8. In addition to the requirements for a construction permit, 10 CSR 20-6.200 requires land disturbance activities of 1 acre or more to obtain a Missouri state operating permit to discharge stormwater. The permit requires best management practices sufficient to control runoff and sedimentation to protect waters of the state. Land disturbance permits will only be obtained by means of the Department's ePermitting system available online at dnr.mo.gov/env/wpp/epermit/help.htm. See dnr.mo.gov/env/wpp/stormwater/sw-land-disturb-permits.htm for more information.

9. A United States (U.S.) Army Corps of Engineers (COE) permit (404) and a Water Quality Certification (401) issued by the Department or permit waiver may be required for the activities described in this permit. This permit is not valid until these requirements are satisfied. If construction activity will disturb any land below the ordinary high water mark of jurisdictional waters of the U.S. then a 404/401 will be required. Since the COE makes determinations on what is jurisdictional, you must contact the COE to determine permitting requirements. You may call the Department's Water Protection Program at 573-751-1300 for more information. See dnr.mo.gov/env/wpp/401/ for more information.
10. In accordance with 10 CSR 20-6.010(12), a full closure plan shall be submitted to the Department's Kansas City Regional Office for review and approval of any permitted wastewater treatment system being replaced. The closure plan must meet the requirements outlined in Standard Conditions Part III of the Missouri State Operating Permit No. MO-G823166. Closure shall not commence until the submitted closure plan is approved by the Department. Form J – *Request for Termination of a State Operating Permit*, shall be submitted to the Water Protection Program for termination of any existing Missouri state operating permit, once closure is completed in accordance with the approved closure plan.
11. All construction must adhere to applicable 10 CSR 20-8 (Chapter 8) requirements listed below.
 - Flood protection shall apply to new construction and to existing facilities undergoing major modification. The wastewater facility structures, electrical equipment, and mechanical equipment shall be protected from physical damage by not less than the one hundred- (100-) year flood elevation. 10 CSR 20-8.140 (2) (B)
 - Unless another distance is determined by the Missouri Geological Survey or by the department's Public Drinking Water Branch, the minimum distance between wastewater treatment facilities and all potable water sources shall be at least three hundred feet (300'). 10 CSR 20-8.140 (2) (C) 1.
 - Facilities shall be readily accessible by authorized personnel from a public right-of-way at all times. 10 CSR 20-8.140 (2) (D)
 - The alarm shall be activated in cases of high water levels. Follow the provisions in subsection (7)(C) of this rule for alarm systems. 10 CSR 20-8.140 (4) (D)
 - All wastewater treatment facilities shall be provided with an alternate source of electric power or pumping capability to allow continuity of operation during power failures. 10 CSR 20-8.140 (7) (A) 1.
 - Electrical systems and components in raw wastewater or in enclosed or partially enclosed spaces where hazardous concentrations of flammable gases or vapors that are normally present, shall comply with the NFPA 70 National Electric Code (NEC)

- (2017 Edition), as approved and published August 24, 2016, requirements for Class I, Division 1, Group D locations. 10 CSR 20-8.140 (7) (B)
- An audiovisual alarm or a more advanced alert system, with a self-contained power supply, capable of monitoring the condition of equipment whose failure could result in a violation of the operating permit, shall be provided for all wastewater treatment facilities. 10 CSR 20-8.140 (7) (C)
 - No piping or other connections shall exist in any part of the wastewater treatment facility that might cause the contamination of a potable water supply. 10 CSR 20-8.140 (7) (D) 1.
 - A means of flow measurement shall be provided at all wastewater treatment facilities. 10 CSR 20-8.140 (7) (E)
 - All wastewater treatment facilities must have a screening device, comminutor, or septic tank for the purpose of removing debris and nuisance materials from the influent wastewater. 10 CSR 20-8.150 (2)
 - Grease interceptors shall be provided on kitchen drain lines from institutions, hospitals, hotels, restaurants, schools, bars, cafeterias, clubs, and other establishments from which relatively large amounts of grease may be discharged to a wastewater treatment facility owned by the grease producing entity. Grease interceptors are typically constructed from fiberglass reinforced polyester, high density polyethylene (HDPE), or concrete. For corrugated HDPE grease interceptors, follow ASTM F2649 – 14 Standard Specification for Corrugated High Density Polyethylene (HDPE) Grease Interceptor Tanks, as approved and published September 1, 2014. For precast concrete grease interceptor tanks, follow ASTM C1613 – 17 Standard Specification for Precast Concrete Grease Interceptor Tanks, as approved and published September 1, 2017. 10 CSR 20-8.150 (3)
 - A septic tank must have a minimum capacity of at least one thousand (1,000) gallons. 10 CSR 20-8.180 (2) (A)
 - The septic tank shall be baffled. 10 CSR 20-8.180 (2) (B)
 - Subsurface systems shall—
 - Exclude unstabilized fill and soils that have been highly compacted and/or disturbed, such as old road beds, foundations, or similar things; 10 CSR 20-8.200 (7) (A) 1. A.
 - Provide adequate surface drainage where slopes are less than two percent (2%); 10 CSR 20-8.200 (7) (A) 1. B.
 - Provide surface and subsurface water diversion where necessary, such as a curtain or perimeter drain; 10 CSR 20-8.200 (7) (A) 1. C. and
 - Have a ten foot (10') buffer from the property line. 10 CSR 20-8.200 (7) (A) 1. D.

- The vertical separation between the bottom of the drip lines and/or the trench and a limiting layer, including but not limited to, bedrock; restrictive horizon; or seasonal high water table, shall be no less than:
 - Twenty-four inches (24"); 10 CSR 20-8.200 (7) (A) 2. A. or
 - Twelve inches (12") for systems dispersing secondary or higher quality effluent; 10 CSR 20-8.200 (7) (A) 2. B. or
 - Forty-eight inches (48") where karst features are present unless the site can be Subsurface systems shall be, at a minimum, preceded by preliminary treatment. 10 CSR 20-8.200 (7) (B)
- Loading rates shall not exceed the values assigned by the site and soil evaluation. 10 CSR 20-8.200 (7) (C)
- All network piping and low pressure distribution piping and fittings with polyvinyl chloride (PVC) shall meet ASTM Standard D 1785 *Standard Specification for Poly(Vinyl Chloride) (PVC) Plastic Pipe, Schedules 40, 80, or 120* as approved and published August 1, 2015, or equivalent rated to meet or exceed ASTM D2466 *Standard Specification for Poly(Vinyl Chloride) (PVC) Plastic Drain, Waste, and Vent Pipe and Fittings* as approved and published August 1, 2017. 10 CSR 20-8.200 (8) (A) 2.
- Manifold design for LPP systems shall address freeze protection while assuring uniform distribution and to minimize drain down of laterals into other laterals at a lower elevation between dosing events. 10 CSR 20-8.200 (8) (A) 3.
- The orifice number and spacing shall be designed to provide a distribution of no more than six square feet per orifice with an orifice size of not less than one-eighth inch. 10 CSR 20-8.200 (8) (C) 1. reclassified. 10 CSR 20-8.200 (7) (A) 2. C.

12. Upon completion of construction:

- A. Benton Ridge, LLC (LC001700324) will become the continuing authority for operation and maintenance of these facilities;
- B. Submit an electronic copy of the as built if the project was not constructed in accordance with previously submitted plans and specifications;
- C. Submit the eDMR permit Holder and Certifier Registration, Form--MO 780-2204 to comply with your operating permit;
- D. Submit the enclosed form Statement of Work Completed to the Department in accordance with 10 CSR 20-6.010(5)(N); and
- E. Submit a Form B - Application for an Operating Permit for Domestic or Municipal Wastewater ($\leq 100,000$ gallons per day) and fee of \$300 to the Engineering Section of

the Water Protection Program 60 days prior to operation. Identify that the application is for a General permit for land application of domestic wastewater, MO-G823.

IV. REVIEW SUMMARY

1. CONSTRUCTION PURPOSE

Construction of the proposed subsurface dispersal system is intended to provide necessary wastewater treatment for the developing RV Park campsite.

2. FACILITY DESCRIPTION

The proposed facility will be a new subsurface treatment system utilizing both conventional and LPP, for multiple phases of development. The site is 31 acres in size and will include a shower house and a restaurant.

The Benton Ridge Winery and RV Park WWTF is located at 25518 Fitzpatrick Ave. in the City of Warsaw, Benton County, Missouri. The facility has a design average flow of 9,225 gpd and serves a hydraulic population equivalent of approximately 478 people. Currently wastewater is retained in a holding tank and pumped and hauled as needed. The proposed construction will enable the RV Park to properly treat wastewater from phase 1 construction of 46 RV slots, restaurant, and ice cream parlor as well as phase 2 construction of 37 future RV slots. Phase 1 of construction will include systems 1-8 and phase 2 will be systems 9-13.

3. COMPLIANCE PARAMETERS

The proposed project is required to meet the relevant requirements of MO-G823 and specifically the section titled “subsurface Dispersal Operational Requirements”. MO-G823 has an expiration date of [August 24, 2022](#).

4. REVIEW of MAJOR TREATMENT DESIGN CRITERIA

- Components are designed for a Population Equivalent of 478 based on hydraulic loading to the system.
- Grease Interceptor – A grease interceptor is utilized to collect grease from raw wastewater and prevents grease from clogging downstream components. The interceptor will have an actual effective volume of 1,000 gallons, and will be connected to the LPP system #3 prior to the septic tank and subsurface dispersal area.
- Septic Tank – A septic tank provides passive primary treatment as the settleable solids in raw wastewater settle onto the bottom of the tank. Raw wastewater will flow by gravity to the 1,500 gallon, 2 compartment septic tank. Each treatment system will be equipped with a septic tank prior to dispersal to the subsurface.

When the water level reaches a certain height, the wastewater flows into the second compartment by a tee-drop pipe. Each septic tank is 5.08 ft x 11.7 ft x 3.7 ft. The septic tanks provide the following approximate days of detention at design average flow: 50 hrs for Systems #1,2,4,6-9, and 11-13, 43 hrs for system #3, 49 hrs for system #5, and 80 hrs for system #10.

- Subsurface Soil Dispersal System – The soils at this site are rated for 0.35-0.5 gpd/sf for the conventional systems and 0.2 gpd/sf for the LPP system 3. The facility is utilizing different loading rates based on the soils report for the different zones. Soil morphology review was conducted during the facility plan application review and on site soils were determined to be acceptable for this system. The soil investigation was completed by Richard Henderson, Certified Soil Scientist, #10023, on June 5, 2020.
 - Soils Report. In the soils investigation, there were 13 pits dug over the proposed site.
 - The soil report assigned an application rate of 0.5 gpd/sf for conventional systems 1, 2, 4, 5, 6, 7, 8, 9, 11, 12, 13.
 - The soil report assigned an application rate of 0.35 gpd/sf for conventional system 10. And an application rate of 0.2 gpd/sf for the LPP system 3.
 - Conventional Gravity Flow Systems – Flow will be directed to lateral lines by a distribution box. Lateral lines will be buried in trenches ranging from 18 to 30 inches to maintain 24 in. vertical separation from limiting layer. System 10 will have at least 5 in. of imported soils added to achieve 24 in. vertical separation.
 - Trench type will be 22 inch wide gravelless chamber.
 - Chambers will be spaced 10 ft. on centers.
 - Systems 1, 2, and 10 will utilize 6 lateral lines with each lateral being 80 ft. in length. Systems 4, 5, 6, 7, 8, 9, 11, 12, and 13 will utilize 5 lateral lines with each being 100 ft in length.
 - Low-Pressure Piping (LPP) System 3 – The low pressure piping is divided into four zones with three lines per zone. The soils report indicates a loading rate of 0.2 gal/ft²/day. A total of 840 linear feet of 1 in. PVC Schedule 40 pipe will be used with a spacing of 5 ft. on center for each line. Lateral lines will be 70 ft in length and have a ball or gate valve on the inlet and a flush opening at the end of the lateral. All valves and flush points will be housed in yard boxes that provide access from ground surface.
 - The end of each line contains a 2-inch clean out with valve box.
 - The manifold piping will be 3 in. diameter with a total length of 125 ft.
 - The lateral spacing is 5 ft. off center with the orifices spaced 5 ft. apart, for 14 orifices per lateral line for a total of 168 holes.
 - Orifice openings are 1/8 inch.
 - The total area needed for loading is 4,200 square feet and is available.
 - Orifice holes will be on the bottom of the lateral line. The flow rate through each hole is 0.41 gpm.
 - The discharge flow rate for the LPP system is 69 gpm.
 - Laterals will be buried to a depth of at least 6 in.

- Pump Tank – 1,500 gallon precast tank with interior dimensions of 5.08 ft x 11.7 ft x 3.7 ft. The tank is equipped with pump-on at 17.7 inches, pump-off at 12 inches.. The inlet pipe will be 4 in. SCH 40 PVC and have two 20 in. diameter Risers for access. The tank will be fitted with a Liberty FL100, 1 HP, 220 volt, cast iron pump or a Zoeller 188 series, 1 HP, 220 volt, cast iron pump. The pumps will be controlled by timer and operate at 78 gpm at 27 ft. of total dynamic head.
- Drinking water well setback distances – The minimum setback distance from wastewater systems is 300 ft. to potable water wells. The following setback distances were identified for each system:

System #	Distance (ft)
1	560
2	490
3	840
4	355
5	335
6	675
7	510
8	520
9	300
10	565
11	300
12	310
13	300

5. OPERATING PERMIT

After completion of construction project submit: statement of work completed, as-builts if the project was not constructed in accordance with previously submitted plans and specifications, and ensure that Application Form B, and fee has been submitted. Missouri State Operating Permit, General Permit MO-G823166, will be issued after receipt of the above documents.

V. NOTICE OF RIGHT TO APPEAL

If you were adversely affected by this decision, you may be entitled to an appeal before the Administrative Hearing Commission (AHC) pursuant to Section 621.250 RSMo. To appeal, you must file a petition with the AHC within 30 days after the date this decision was mailed or the date it was delivered, whichever date was earlier. If any such petition is sent by registered mail or certified mail, it will be deemed filed on the date it is mailed; if it is sent by any method other than registered mail or certified mail, it will be deemed filed on the date it is received by the AHC. Any appeal should be directed to:

Administrative Hearing Commission
U.S. Post Office Building, Third Floor
131 West High Street, P.O. Box 1557
Jefferson City, MO 65102-1557
Phone: 573-751-2422
Fax: 573-751-5018
Website: <https://ahc.mo.gov>

Aaron Sawyer
Engineering Section
aaron.sawyer@dnr.mo.gov

Cindy LePage, P.E.
Engineering Section
cindy.lepage@dnr.mo.gov



MISSOURI DEPARTMENT OF NATURAL RESOURCES
WATER PROTECTION PROGRAM

**APPLICATION FOR CONSTRUCTION PERMIT –
WASTEWATER TREATMENT FACILITY**

FOR DEPARTMENT USE ONLY	
APP NO.	CP NO.
FEE RECEIVED	CHECK NO.
DATE RECEIVED	

APPLICATION OVERVIEW

The Application for Construction Permit – Wastewater Treatment Facility form has been developed in a modular format and consists of Part A and B. **All applicants must complete Part A.** Part B should be completed for applicants who currently land-apply wastewater or propose land application for wastewater treatment. **Please read the accompanying instructions before completing this form. Submittal of an incomplete application may result in the application being returned.**

PART A – BASIC INFORMATION

1.0 APPLICATION INFORMATION (Note – If any of the questions in this section are answered NO, this application may be considered incomplete and returned.)

- 1.1 Is this a Federal/State funded project? YES N/A Funding Agency: _____ Project #: _____
- 1.2 Has the Missouri Department of Natural Resources approved the proposed project's antidegradation review? YES Date of Approval: _____ N/A
- 1.3 Has the department approved the proposed project's facility plan*? YES Date of Approval: _____ NO (If No, complete No. 1.4.)
- 1.4 [Complete only if answered No on No. 1.3.] Is a copy of the facility plan* for wastewater treatment facilities included with this application? YES NO Exempt because _____
- 1.5 Is a copy of the appropriate plans* and specifications* included with this application? YES Denote which form is submitted: Hard copy Electronic copy (See instructions.) NO
- 1.6 Is a summary of design* included with this application? YES NO
- 1.7 Has the appropriate operating permit application (A, B, or B2) been submitted to the department? YES Date of submittal: _____ Enclosed is the appropriate operating permit application and fee submittal. Denote which form: A B B2 N/A: However, In the event the department believes that my operating permit requires revision to permit limitation such as changing equivalent to secondary limits to secondary limits or adding total residual chlorine limits, please share a draft copy prior to public notice? YES NO
- 1.8 Is the facility currently under enforcement with the department or the Environmental Protection Agency? YES NO
- 1.9 Is the appropriate fee or JetPay confirmation included with this application? YES NO *Please contact 913-669-6168 For Fee if Applicable*

* Must be affixed with a Missouri registered professional engineer's seal, signature and date.

2.0 PROJECT INFORMATION


2.1 NAME OF PROJECT Benton Ridge Winery and Campground	2.2 ESTIMATED PROJECT CONSTRUCTION COST \$ 150,000
---	---

2.3 PROJECT DESCRIPTION
Campground and Winery . Camping and Serving drinks

2.4 SLUDGE HANDLING, USE AND DISPOSAL DESCRIPTION
Gravity systems and LPP system
Tank

2.5 DESIGN INFORMATION
A. Current population: _____; Design population: _____
B. Actual Flow: _____ gpd; Design Average Flow: _____ gpd;
Actual Peak Daily Flow: _____ gpd; Design Maximum Daily Flow: _____ gpd; Design Wet Weather Event: _____

2.6 ADDITIONAL INFORMATION
A. Is a topographic map attached? YES NO
B. Is a process flow diagram attached? YES NO

3.0 WASTEWATER TREATMENT FACILITY				
NAME Benton Ridge Campground and Winery		TELEPHONE NUMBER WITH AREA CODE 913-669-6168		E-MAIL ADDRESS gegould2000@yahoo.com
ADDRESS (PHYSICAL) 25518 Fitzpatrick Avenue		CITY Warsaw	STATE Mo	ZIP CODE 65355
COUNTY Benton				
Wastewater Treatment Facility: Mo- (Outfall Of)				
3.1 Legal Description: _____ 1/4, _____ 1/4, _____ 1/4, Sec. _____, T _____, R _____ <i>N/2 Lot 2 SW Sec 19-41-21</i> (Use additional pages if construction of more than one outfall is proposed.) <i>Benton County Mo</i>				
3.2 UTM Coordinates Easting (X): _____ Northing (Y): _____ For Universal Transverse Mercator (UTM), Zone 15 North referenced to North American Datum 1983 (NAD83)				
3.3 Name of receiving streams: _____				
4.0 PROJECT OWNER				
NAME Gene Gould		TELEPHONE NUMBER WITH AREA CODE 913-669-6168		E-MAIL ADDRESS gegould2000@yahoo.com
ADDRESS 24744 Hwy BB		CITY Warsaw	STATE Mo	ZIP CODE 65355
5.0 CONTINUING AUTHORITY: A continuing authority is a company, business, entity or person(s) that will be operating the facility and/or ensuring compliance with the permit requirements.				
NAME Benton Ridge Campground and Winery		TELEPHONE NUMBER WITH AREA CODE 913-669-6168		E-MAIL ADDRESS gegould2000@yahoo.com
ADDRESS 25518 Fitzpatrick Avenue		CITY Warsaw	STATE Mo	ZIP CODE 65355
5.1 A letter from the continuing authority, if different than the owner, is included with this application. <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> N/A				
5.2 COMPLETE THE FOLLOWING IF THE CONTINUING AUTHORITY IS A MISSOURI PUBLIC SERVICE COMMISSION REGULATED ENTITY.				
A. Is a copy of the certificate of convenience and necessity included with this application? <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO				
5.3 COMPLETE THE FOLLOWING IF THE CONTINUING AUTHORITY IS A PROPERTY OWNERS ASSOCIATION.				
A. Is a copy of the as-filed restrictions and covenants included with this application? <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO				
B. Is a copy of the as-filed warranty deed, quitclaim deed or other legal instrument which transfers ownership of the land for the wastewater treatment facility to the association included with this application? <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO				
C. Is a copy of the as-filed legal instrument (typically the plat) that provides the association with valid easements for all sewers included with this application? <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO				
D. Is a copy of the Missouri Secretary of State's nonprofit corporation certificate included with this application? <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO				
6.0 ENGINEER				
ENGINEER NAME / COMPANY NAME Martin Heins		TELEPHONE NUMBER WITH AREA CODE 913-202-3813		E-MAIL ADDRESS mheins1313@gmail.com
ADDRESS		CITY Warsaw	STATE MO	ZIP CODE 65355
7.0 APPLICATION FEE				
<input type="checkbox"/> CHECK NUMBER <input type="checkbox"/> JETPAY CONFIRMATION NUMBER				
8.0 PROJECT OWNER: I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.				
PROJECT OWNER SIGNATURE 				
PRINTED NAME Gene Gould			DATE 6-29-2020	
TITLE OR CORPORATE POSITION President		TELEPHONE NUMBER WITH AREA CODE 913-669-6168		E-MAIL ADDRESS gegould2000@yahoo.com
Mail completed copy to: MISSOURI DEPARTMENT OF NATURAL RESOURCES WATER PROTECTION PROGRAM P.O. BOX 176 JEFFERSON CITY, MO 65102-0176				
END OF PART A.				
REFER TO THE APPLICATION OVERVIEW TO DETERMINE WHETHER PART B NEEDS TO BE COMPLETE.				