STATE OF MISSOURI DEPARTMENT OF NATURAL RESOURCES

MISSOURI CLEAN WATER COMMISSION



GENERAL PERMIT for SEWER EXTENSION CONSTRUCTION

| The Missouri Department of Natur | al Resources hereby issues a permit to: |
|---|---|
| Construction Permit ID: Title of Project: Owner: Address: | MOGC00818 Perryville SE WWTP City of Perryville 215 North West Street Perryville, MO 63775 |
| | al site work appropriate to the scope and purpose of the project and will include all the necessary and usable collection system. The construction of this project will be in the vicinity of the county Permit ID below: |
| County: Perry | Receiving Permit ID: MO0051144 |
| for the construction of (described o | onstruction project): |
| manholes, 700 lf of 4-inch C900 | -Construction of approximately 1,420 lf of 8-inch PVC SDR-35 gravity sewer with 9 DR 25 PVC force mains, one duplex lift stations with each pump capable of of TDH, and one generator to serve 936 PE and a design average flow of 93,600 |
| County and discharges to an exi | outheast intersection of Edgemont Blvd and S Perryville Blvd in Perryville, Perry sting system to be treated at Perryville Southeast WWTF, MO-0051144. The City e continuing authority for this project. |
| RSMo, and regulation promulgated As the Department does not exami permit does not include approval of | lities shall be in accordance with the provisions of the Missouri Clean Water Law, Chapter 644, I thereunder, or this permit may be revoked by the Department of Natural Resources (Department) ne structural features of design or the efficiency of mechanical equipment, the issuance of this f these features. Struction of water pollution control components; it does not apply to other environmentally |
| December 05, 2024 Issue Date | John Hole, Director Water Protection Program |

December 04, 2026
Expiration Date

APPLICABILITY

- 1. This permit authorizes the construction of gravity sewer extensions, force mains, and lift stations. Non-earthen flow equalization storage basins at lift stations and inline storage, which flows back into the lift station or collection system, are also included.
- 2. The Missouri Department of Natural Resources may require a site-specific sewer extension construction permit due to compliance and enforcement actions in accordance with 10 CSR 20-6.010(13)(C).
- 3. This permit does not apply to:
 - A. Earthen storage basins;
 - B. Exempt projects in accordance with 10 CSR 20-6.010(1)(B), 10 CSR 20-6.010(5)(B), and RSMo 644.051 unless requested by the applicant or required by enforcement.

PREREQUISITES:

- 1. The Sewer Extension Construction Permit application, appropriate fee, and documentation in accordance with 10 CSR 20-6.010(5)(G).
- 2. Submit the Sewer Extension Construction Permit application at least sixty (60) days in advance of the start of construction in accordance with 10 CSR 20-6.010(5)(F).
- 3. Submit an electronic copy of the construction permit application and documents to DNR.WPPEngineerSection@dnr.mo.gov in accordance with 10 CSR 20-6.010(5)(G)3.
- 4. The plans and specifications, each signed, sealed, and dated by a professional engineer registered in the State of Missouri in accordance with 10 CSR 20-8 and 10 CSR 20-6.010.
- 5. The Design Certification form, Engineering Report, or Summary of Design, signed, sealed, and dated by a professional engineer registered in the State of Missouri, certifying the design of the system is in accordance with 10 CSR 20-6 and 10 CSR 20-8.
- 6. A statement from the continuing authority, as defined in 10 CSR 20-6.010, accepting the wastewater for treatment and indicating the permitted treatment facility has the available capacity.
- 7. A statement from the continuing authority, as defined in 10 CSR 20-6.010, accepting responsibility for the operation and maintenance of these facilities.

PERMIT CONDITIONS:

- 1. This permit authorizes the activities and scope of work detailed in the plans and specifications submitted with the request.
- 2. The construction must be in accordance with the final plans and specifications received by the Department. Revisions that affect capacity, flow, or system layout must be approved by the Department prior to construction.

PERMIT CONDITIONS: (continued)

- 3. If construction will incorporate minor changes from previously submitted plans and specifications (i.e., changes that do not affect the capacity, flow, or system layout), submit an electronic copy of the as-built plans and specifications in accordance with 10 CSR 20-8.110(11).
- 4. State and Federal Law does not permit bypassing of raw wastewater; therefore, the applicant must take steps to ensure that raw wastewater does not discharge during construction. If a sanitary sewer overflow or bypass occurs, report the appropriate information to the Department's regional office per 10 CSR 20-7.015(9)(E) or through the Online Bypass/SSO Reporting service on the Missouri Gateway for Environmental Management (MoGEM) portal found at https://dnr.mo.gov/data-e-services/missouri-gateway-environmental-management-mogem.

See https://dnr.mo.gov/document-search/missouri-gateway-environmental-management-mogem-frequently-asked-questions-pub2988/pub2988 for more information.

- 5. Protection of drinking water supplies must meet the requirements of 10 CSR 20-8.120(5).
 - A. There shall be no physical connections between a public or private potable water supply system and a sewer or appurtenance that would permit the passage of any wastewater or polluted water into the potable supply.
 - B. Lay sewers at least 50 feet (50') in a horizontal direction from any existing or proposed public water supply well or other water supply sources or structures.
- 6. Position manholes so that the top access is at or above grade level.
- 7. In addition to the requirements for a construction permit, see 10 CSR 20-6.200 for land disturbance requirements to obtain a Missouri State Operating Permit to discharge stormwater. The permit requires Best Management Practices sufficient to control runoff and sedimentation to protect waters of the state. Applicants shall obtain land disturbance permits through the Department's ePermitting system, available online at <a href="https://dnr.mo.gov/data-e-services/water/electronic-permitting-ep

See https://dnr.mo.gov/water/business-industry-other-entities/permits-certification-engineering-fees/stormwater/construction-land-disturbance for more information.

8. Entities applying for funding under 10 CSR 20-4, "Grants and Loans" will need to comply with those requirements in addition to the requirements of 10 CSR 20-8.

PERMIT CONDITIONS: (continued)

9. The Department may require a United States (U.S.) Army Corps of Engineers (COE) permit (404) and a Water Quality Certification (401) or a permit waiver for the activities described in this permit. If construction activity will disturb any land below the ordinary high water mark of Jurisdictional Waters of the U.S., then a 404/401 is required. Fulfillment of these requirements is necessary before the permit is considered valid. Since the COE makes determinations on what is jurisdictional, you must contact the COE to determine permitting requirements. You may call the Department's Operating Permits Section at 573-522-4502 for more information.

See https://dnr.mo.gov/water/business-industry-other-entities/permits-certification-engineering-fees/section-401-water-quality for more information.

- 10. If this project eliminates a wastewater treatment facility under the jurisdiction of the Department, then the applicant shall submit a full closure plan with a Facility Closure Request Form, Form MO 780-2512, to the Department's appropriate regional office for review and approval. In accordance with 10 CSR 20-6.010(12), the closure plan must meet the requirements outlined in Standard Conditions Part III of the Missouri State Operating Permit. Closure shall not commence until the Department approves the submitted closure plan.
- 11. If this project is part of a project to resolve an enforcement action or is receiving funding from the Department, submit a <u>statement of work complete</u> following the completion of construction.
- 12. Applicants may submit, prior to the expiration date of this permit, a written request that additional time is needed in accordance with 10 CSR 20-6.010(5)(H)3.

| Θ | ≋ ≋ |
|----------|------------|
| 9 | |

MISSOURI DEPARTMENT OF NATURAL RESOURCES WATER PROTECTION PROGRAM APPLICATION FOR CONSTRUCTION PERMIT -

SEWER EXTENSION

| | ARTMENT USE ONLY |
|---------------|------------------|
| APP NO. | CP NO. |
| FEE RECEIVED | CHECK NO. |
| DATE RECEIVED | |

| NOTE ► Please Read the accompanying in 1.0 APPLICATION INFORMATION (Note – I considered incomplete and returned.) | A PRODUCTION AND AND AND AND AND AND AND AND AND AN | PRINCIPLE AND ADDRESS OF THE PRINCIPLE O | ed NO, this applica | tion may be | | |
|---|--|--|--|--|--|--|
| 1.1 Is this a Federal/State funded project? | ☐ YES 🗹 N/A Funding Ager | ncy: | Proj | ect#: | | |
| 1.2 Has the Department of Natural Resource ✓ YES Date of Appro | | engineering ☐ NO | report*? | □ N/A | | |
| 1.3 Is a copy of the appropriate plans* and s | •••• | | ☑YES ☐ NO | | | |
| If the project is using standard specificati | | Perryville | | | | |
| 1.4 Is a summary of design* included with the | The state of the s | | | | | |
| 1.5 Is the appropriate fee or JetPay confirma See Section 7.0 | tion included with this application? | ☑ YES [| □NO | , | | |
| * Must be affixed with a Missouri registered p 2.0 PROJECT INFORMATION | rofessional engineer's seal, signat | ure and date. | | and the second second second second | | |
| 2.1 NAME OF PROJECT | | | | | | |
| Heimos Subdivision Sewer | O.T. | DTATE | Lancope | COLLINA | | |
| South Perryville Boulevard | Perryville | STATE MO | ZIP CODE 63775 | COUNTY Perry | | |
| 2.2 Legal Description: 1/4, 1/4 | 4, 1/4, Sec. N.A. , | T N.A. , | R N.A. | | | |
| 2.3 Project Components (check all that apply ☑ Gravity sewers ☑ Pumping station | | ive sewer sys | stem | escribe below.) | | |
| 2.4 PROJECT DESCRIPTION | | | | | | |
| This project consists of approximately 1,420 L.F approximately 700 L.F. of 4" C900 DR 25 PVC pCity of Perryville, Missouri. | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| 2.5 DESIGN INFORMATION A. Population or number of lots to be served | by this extension: 6 Lots | | | | | |
| B. Estimated flow to be contributed by this ex | ktension: Design Average Flow; g | 3600 gpd | Design Peak Hourly | / Flow: 14000 gph | | |
| C. Industrial Wastes: Type: N.A. | Flow: 0 gpd | | | | | |
| D. Receiving Sewer: Size: 8 inches Capacity: 733 gpm | | | | | | |
| E. Does this project (check all that apply): | | | | | | |
| ☑ Connect to an existing treatment plant ☐ Resolve enforcement issue ☐ Eliminate or consolidate an existing treatment plant | | | | | | |
| F. Estimated number of onsite systems being removed: 0 | | | | | | |
| G: Estimated costs associated with piping: \$ | 170,000 Estimated costs a | ssociated wit | h lift station(s): \$ 58 | 0,000 | | |
| 3.0 PROJECT OWNER | Last sploys who specially as | | EMAIL ADDRESS | 900 22 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | | |
| NAME The City of Perryville | TELEPHONE NUMBER WITH AR 573-547-2594 | | jefflayton@perryvi | llemo.gov | | |
| ADDRESS 215 N. West St. | спү Perryville | STATE MO | ZIP CODE 63775 | | | |
| CHARTER NUMBER (SECRETARY OF STATE) or REGISTERED | AGENT | | , | | | |
| | | | | | | |

MO 780-1632 (10-22)

| 4.0 CONTINUING AUTHORITY: A continuing for ensuring compliance with the permit required Continuing authority should be a relatively permit when needed, of the permitted facility or actively hired by the permittee to sample or operate an analytical laboratory. To access the regulator Water Commission Chapter 6. A continuing a (SoS's) webpage: Missouri Secretary of State required to register with the SoS. | rements a ermanent e vity. A cont and mainta ry requirent authority's | nd provide on the contity responding authoriting authoriting in the systement regardiname must | continuous s sible for the prity is not, h m for a defir ng continuin be listed exa | stable oversic ongoing op- nowever, an ned time peri g authority, actly as it ap | ght of the permitted facility or activity. The eration, maintenance and modernization, entity or individual that is contractually iod, such as a certified operator or 10 CSR 20-6.010(2), please visit Clean pears on the Missouri Secretary of State's | |
|--|--|--|---|---|--|--|
| NAME | | | IUMBER WITH A | REA CODE | EMAIL ADDRESS | |
| The City of Perryville | CITY | 573-547-2 | 594 | STATE | jefflayton@perryvillemo.gov | |
| 215 N. West St. | Perryville |) | | MO | 63775 | |
| CHARTER NUMBER (SECRETARY OF STATE) | | | | J | | |
| 4.1 Has appropriate continuing authority accepting A letter from the continuing authority accepting different than the original owner of the construction Treatment Facility Acceptance" Form 780-25 | ng respons ruction), or | sibility for con a properly of | ntinued mai executed "C | ntenance of | the sewer (if the continuing authority is athority and Receiving Wastewater | |
| ENGINEER NAME / COMPANY NAME | | TELEPHONE N | UMBER WITH A | REA CODE | EMAIL ADDRESS | |
| Clint Brown, P.E. / Zahner & Associates, Inc. | Low | 573-547-17 | 771 | LOTATE | clintb@zahnerinc.com | |
| ADDRESS 200 Zahner Place | Perryvill | е | | MO STATE | 63775 | |
| 6.0 RECEIVING WASTEWATER TREATME | NT FACIL | .ITY | | | | |
| NAME Perryville Southeast Wastewater Treatment I | Plant | 573-547-26 | NUMBER WITH A 690 | REA CODE | EMAIL ADDRESS jeremymeyer@perryvillemo.gov | |
| MISSOURI STATE OPERATING PERMIT # | | COUNTY | | | REMAINING CAPACITY (GPD) | |
| MO-0051144 | ., | Perry | | | 1,250,000 GPD | |
| 6.1 If different from the owner, has a letter be accept the expanded flow or has a properly 6 MO 780-2584 form been provided? | executed 0 | Continuing A | uthority and | Receiving \ | Wastewater Treatment Facility Acceptance | |
| 6.2 A letter from the receiving wastewater tre | ······· | | *************************************** | | | |
| 6.3 If the receiving treatment plant or continu Certificate of Convenience and Necessity ha | | | Yes – Date | | □ No ☑ N/A | |
| OPTIONAL QUESTIONS REGARDING MIL | ITARY SE | RVICE | | | | |
| Have you or an immediate family member ev U.S. Armed Forces? | | Charles and the same of the sa | | 'es | □ No | |
| If yes, would you like information about milita in Missouri? | ry-related | services | ПΑ | 'es | □ No | |
| 7.0 Application Fee | | | | | | |
| ☐ Check Number | | | <u></u> | | n Number 20058995 | |
| 8.0 PROJECT OWNER: I certify under penalty of law this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate and complete. I am aware there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations. | | | | | | |
| PROJECT OWNER SIGNATURE | (16) (16) (16) (16) (16) (16) (16) (16) | underlander (1980) | | 33444400000000000000000000000000000000 | | |
| PRINTED NAME DATE | | | | | | |
| Brent Buerck 10/31/2024 | | | | | | |
| TITLE OR CORPORATE POSITION City Administrator | | 573-547-25 | NUMBER WITH A 594 | REA CODE | brentbuerck@perryvillemo.gov | |
| Mail completed copy to: | | | *************************************** | 0.11 | | |
| MISSOURI DEPARTMENT OF NATURAL RESOURCES WATER PROTECTION PROGRAM PO BOX 176 JEFFERSON CITY, MO 65102-0176 | | | Submit completed electronic copy to: Missouri Department of Natural Resources at DNR.WPPEngineerSection@dnr.mo.gov | | | |

MO 780-1632 (10-22)

| SEWER EXTENSION DESIGN CERTIFICATION: Answer all questions yes on NA. Answer N/A ordy if the question is Seathy not supplicated to the design of the processed sever an elements. REGULATION 8.110(3)(A) 1. 8.110(3)(A) 2. 8.110(3)(B) 3. 8.110(3)(B) 4. Are exerging design flow based on educal flow data for an existing system? 3. 8.110(B)(B) 1. 8.110(B)(B)(B) 1. 8.110(B)(B)(B)(B)(B)(B)(B)(B)(B)(B)(B)(B)(B)(| 9.0 SEWER EXTENSION CHECKLIST | | | | | | | | |
|--|-------------------------------|----------------|--|-----|---|--|--|--|--|
| 1. 8.110(3)(A) | | | | | | | | | |
| 2. 8.110(3)(8) Are exercised testign flows, peak hourly flows and I&L contributions for new systems calculated? 3. 8.110(9)(8) Is the property obtaining and proposed feelibles? 4. 8.120(2) Does the severe exclude water from roofs, streets, groundwater from foundation drains and companied water water control of the property obtaining and proposed feelibles? 5. 8.120(3)(A) Is the pipe installation, embedment and backfill designed to prevent damage to the pipe and its joints? 6. 8.120(3)(A) Is all sever pipe constructed with a slope to obtain mean volocities of not less than 2 feet per second? 7. 8.120(3)(A) Is the pipe installation, embedment and backfill designed to prevent damage to the pipe and its joints? 8. 8.120(3)(A) Is the pipe covered with at least 38° of soil or sufficiently insulated to prevent freezing? 9. 8.120(4)(C) Is the pipe covered with at least 38° of soil or sufficiently insulated to prevent freezing? 9. 8.120(4)(C) Are maintered to ensure no pipe exceeds a deflection of 5% of the inside diameter? 9. 8.120(4)(C) Are maintered to ensure no pipe exceeds a deflection of 5% of the inside diameter? 10. 8.120(4)(C) Are maintered to ensure no pipe exceeds a deflection of 5% of the inside diameter? 11. 8.120(4)(C) Are maintered to ensure no pipe exceeds a deflection of 5% of the inside member? 12. 8.120(4)(E) Are maintered to ensure no pipe exceeds a deflection of 5% of the inside diameter? 13. 8.120(4)(E) Are maintered to ensure no pipe exceeds a deflection of 5% of the inside member? 14. 8.120(4)(E) Are maintered to ensure no pipe exceeds a deflection of 5% of the inside member? 15. 8.120(5)(A) Are sever all ensures a diameter with a clear opening of 22 inches on sewer in learner than the sever member of 1 inches of a mainter with a clear of a mainter of the inside of inches or larger and equal to the diameter for pipes ≤ 8°? 16. 8.120(5)(B) Are severe and maintered of the diameter of pipes ≤ 8°? 17. 8.120(5)(B) Are se | | | | YES | | | | | |
| aclaulated? 1. 8.110(9)(8) Steres a detailed plan showing tributary area, boundaries, pertinent elevetions, topography, existing and proposed facilities? 2. 8.120(2) Does the sewer exclude water from roots, streets, groundwater from foundation drains and combined wastewater? 3. 8.120(3)(A) Step be installation, embedment and backfill designed to prevent damage to the pipe and its joints? 3. 8.120(3)(A) Is all sewer pipe constructed with a slope to obtain mean velocities of not less than 2 feet per second? 3. 8.120(3)(A) Is the pipe covered with at least 36° of soil or sufficiently insulated to prevent freezing? | | | | | V | | | | |
| topography, existing and proposed facilities? 5. 8.120(2) Does the sewer exclude water from roots, streets, groundwater from foundation drains and combined wastewater? 5. 8.120(3)(A) Is the pipe installation, embedment and backfill designed to prevent damage to the pipe and its joints? 7. 8.120(3)(A) Is the pipe covered with at least 36° of soil or sufficiently insulated to prevent freezing? 7. 8.120(3)(A) Is the pipe covered with at least 36° of soil or sufficiently insulated to prevent freezing? 8. 8.120(4)(A) Is the pipe covered with at least 36° of soil or sufficiently insulated to prevent freezing? 9. 8.120(4)(A) Is the pipe covered with at least 36° of soil or sufficiently insulated to prevent freezing? 10. 8.120(4)(A) Are manholes located at the end of each line, at all changes in grade, size or alignment and at all intersactions? 11. 8.120(4)(C) Are manholes located at the end of a lateral instead of a manhole, they are a minimum diameter of 8 inches or targer and equal to the diameter for pipes ≤ 3°. 11. 8.120(4)(C) Where cleanouts are used at the end of a lateral instead of a manhole, they are a minimum diameter of 8 inches or targer and equal to the diameter for pipes ≤ 3°. 12. 8.120(4)(E) Are the manholes watertight, constructed and installed in accordance with the manufacturer's recommendations and procedures? 13. 8.120(5)(A) Is the sever free from physicial connections to a polable water supply system and no water pipes come in contact with a sever membrole? 14. 8.120(5)(A) Are sewers and manholes located at least 50 feet horizontally from any existing or procedures? 15. 8.120(5)(B) Are sewers and manholes located at least 50 feet horizontally from any existing or procedured supply well, sources, structures? 16. 8.125(5)(A)1. Does the cleaning velocity of ≥ 2 ft/s happen more than once per day? 17. 8.125(5)(A)2. Is the diameter of the pressure sever main pipe at least 1.5°? 18. 8.125(5)(B)2. Are appurtenances compatible with the piping system? 29. 8.125(5)(D)3. Is the diameter of | | | calculated? | П | V | | | | |
| combined wastewater? 5. 8.120(3)(A) Is the pipe installation, embedment and backfill designed to prevent damage to the pipe and its joints? 6. 8.120(3)(A) Is all sever pipe constructed with a slope to obtain mean valocities of not less than 2 feet per second? 7. 8.120(3)(A)2 Is the pipe covered with at least 35° of soil or sufficiently insulated to prevent freezing? | 3. | 8.110(9)(B) | topography, existing and proposed facilities? | П | V | | | | |
| and its joints? All Second Secon | 4. | 8.120(2) | combined wastewater? | | Ø | | | | |
| per second? 1. 8.120(3)(A)2 Is the pipe covered with at least 36" of soil or sufficiently insulated to prevent freezing? 2. 8. 8.120(3)(B) Is deflection testing specified to ensure no pipe exceeds a deflection of 5% of the inside diameter? 3. 8.120(4)(A) Are manholes located at the end of each line, at all changes in grade, size or alignment and at all intersections? 4. 120(4)(C) Are manholes located at the end of each line, at all changes in grade, size or alignment and at all intersections? 5. 8.120(4)(C) Are manholes located at the end of a lateral instead of a manhole, they are a minimum diameter of 8 inches or larger and equal to the diameter for pipes < 8"? 11. 8.120(4)(C) Where cleanouts are used at the end of a lateral instead of a manhole, they are a minimum diameter of 8 inches or larger and equal to the diameter for pipes < 8"? 12. 8.120(4)(E) Are the manholes instructed and installed in accordance with the manufacturer's recommendations and procedures? 13. 8.120(4)(F) De the specifications include a requirement for inspection and testing for manholes? 14. 8.120(5)(A) Is the sewer free from physical connections to a potable water supply system and no water pipes come in contact with a sewer manhole? 15. 8.120(5)(B) Are sewers and manholes located at least 50 feet horizontally from any existing or proposed water supply well, sources, structures? 10.0 PRESSURE SEWERS, GRINDER PUMP, STEP AND STEG SEWER CHECKLIST 16. 8.125(5)(A)2. Is the diameter of the pressure sewer main pipe at least 1.5"? 17. 8.125(5)(B)2. Are appurtenances compatible with the piping system? 19. 8.125(5)(B)2. Are sisolation valves located: upstream of major pipe intersections; both sides of stream, bridge and RR crossings; at terminal end of system? 20. 8.125(5)(D)1. Bridge and RR crossings; at terminal end of system? 21. 8.125(5)(D)1. Do grinder pump stations service only a single equivalent dwelling unit (EDU)? I.e. 1 residence − 1 ginder pump. 22. 8.125(5)(D)1. Presidence − 1 ginder pump. 23. 8.125(5)(D)3. Is th | 5. | , C | and its joints? | П | V | | | | |
| 8. 8.120(3)(B) Is deflection testing specified to ensure no pipe exceeds a deflection of 5% of the inside diameter? 9. 8.120(4)(A) Are manholes located at the end of each line, at all changes in grade, size or alignment and at all intersections? 10. 8.120(4)(C) Are manholes located at the end of each line, at all changes in grade, size or alignment and at all intersections? 11. 8.120(4)(C) Where cleanouts are used at the end of a lateral instead of a manhole, they are a minimum diameter of 8 inches or larger and egual to the diameter for pipes < 8° 2. 12. 8.120(4)(E) Are the manholes or larger and egual to the diameter for pipes < 8° 2. 13. 8.120(4)(F) Do the specifications instructed and installed in accordance with the manufacturer's recommendations and procedures? 14. 8.120(5)(A) Is the sewer free from physical connections to a potable water supply system and no water pipes come in contact with a sewer manhole? 15. 8.120(5)(B) Are sewers and manholes located at least 50 feet horizontally from any existing or proposed water supply well, sources, structures? 10.0 PRESSURE SEWERS, GRINDER PUMP, STEP AND STEG SEWER CHECKLIST. REGULATION 16. 8.125(5)(A)2. Is the diameter of the pressure sewer main pipe at least 1.5°? 17. 8.125(5)(B)2. Are appurtenances compatible with the piping system? 19. 8.125(5)(B)2. Are appurtenances compatible with the piping system? 20. 8.125(5)(B)2. Are isolation valves located: upstream of major pipe intersections; both sides of stream, price and Recrossings; at terminal end of system? 22. 8.125(5)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? Le. 1 sidedence – 1 ginder pump. 22. 8.125(5)(D)1.A Signider pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Signider pump stations of storage in the grinder pump unit? 25. 8.125(5)(D)5. Are units serviceable and replaceable under wet conditions with | 6. | 8.120(3) (A)1 | per second? | | Ø | | | | |
| diameter? diameter? diameter diamete | 7. | 8.120(3)(A)2 | | | V | | | | |
| and at all intersections? and at all intersections? | 8. | 8.120(3)(B) | | | Ø | | | | |
| line larger than 8"? 11. 8.120(4)(C) Where cleanouts are used at the end of a lateral instead of a manhole, they are a minimum diameter of 8 inches or larger and equal to the diameter for pipes < 8"? 12. 8.120(4)(E) Are the manholes waterlight, constructed and installed in accordance with the manholes waterlight, constructed and installed in accordance with the manufacturer's recommendations and procedures? 13. 8.120(5)(A) Is the sewer free from physical connections to a potable water supply system and no water pipes come in contact with a sewer manhole? 15. 8.120(5)(B) Are sewers and manholes located at least 50 feet horizontally from any existing or proposed water supply well, sources, structures? 16. 8.125(5)(A)1. Does the cleaning velocity of ≥ 2 ft/s happen more than once per day? 17. 8.125(5)(A)1. Does the cleaning velocity of ≥ 2 ft/s happen more than once per day? 18. 8.125(5)(B) Are appurtenances compatible with the piping system? 19. 8.125(5)(B)2. Are isolation valves located: upstream of major pipe intersections; both sides of stream, bridge and RR crossings; at terminal end of system? 20. 8.125(5)(D)1.A Does implex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence — 1 grinder pump tations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence — 1 grinder pump stations owned, operated and maintained by an approved continuing authority? 24. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 25. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 26. 8.125(5)(D)4. Do grinder pump stations owned, operated and maintained by an approved continuing authority? 27. 8.130(3)(B)2. electrical equipment suitable for hazardous locations (National Electrical Loade, Class I, Group D. Division 1 location)? 28. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume decided to freeboa | 9. | 8.120(4)(A) | and at all intersections? | | Ø | | | | |
| diameter of 8 inches or larger and equal to the diameter for pipes < 8*? 12. 8.120(4)(E) Are the manholes watertight, constructed and installed in accordance with the manufacturer's recommendations and procedures? 13. 8.120(4)(F) Do the specifications include a requirement for inspection and testing for manholes? 14. 8.120(5)(A) Is the sewer free from physical connections to a potable water supply system and no water pipes come in contact with a sewer manhole? 15. 8.120(5)(B) Are sewers and manholes located at least 50 feet horizontally from any existing or proposed water supply well, sources, structures? 10.0 PRESSURE SEWERS, GRINDER PUMP, STEP AND STEG SEWER CHECKLIST REGULATION 16. 8.125(5)(A)1. Does the cleaning velocity of ≥ 2 ft/s happen more than once per day? 17. 8.125(5)(A)2. Is the diameter of the pressure sewer main pipe at least 1.5*? 18. 8.125(5)(B) Are appurtenances compatible with the piping system? 19. 8.125(5)(B)2. Are isolation valves located: upstream of major pipe intersections; both sides of stream, bridge and RR crossings; at terminal end of system? 20. 8.125(5)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence − 1 grinder pumps. 22. 8.125(5)(D)1.B Are multiple unit pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence − 1 grinder pump. 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)3. Revenue and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)3. Revenue and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class | | 7 377 | line larger than 8"? | | Ø | | | | |
| manufacturer's recommendations and procedures? 1. 8.120(4)(F) 1. Do the specifications include a requirement for inspection and testing for manholes? 1. 8.120(5)(A) 1. Is the sewer free from physical connections to a potable water supply system and no water pipes come in contact with a sewer manhole? 1. 8.120(5)(B) 1. Are sewers and manholes located at least 50 feet horizontally from any existing or proposed water supply well, sources, structures? 1. 8.120(5)(B) 1. REGULATION 1. Boes the cleaning velocity of ≥ 2 ft/s happen more than once per day? 1. B. 125(5)(A)1. 1. Does the cleaning velocity of ≥ 2 ft/s happen more than once per day? 1. Is the diameter of the pressure sewer main pipe at least 1.5"? 1. S. 125(5)(B) 1. Are appurtenances compatible with the piping system? 1. Is also and R crossings; at terminal end of system? 2. B. 125(5)(B) 2. Are isolation valves located: upstream of major pipe intersections; both sides of stream, bridge and RR crossings; at terminal end of system? 2. B. 125(5)(D)1. 3. B. 125(5)(D)1. 4. Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence − 1 grinder pumpt. 2. B. 125(5)(D)1. 3. B. 125(5)(D)1. 4. Are unitiple unit pump stations owned, operated and maintained by an approved continuing authority? 2. B. 125(5)(D)4. 3. B. 125(5)(D)5. 4. S. 125(5)(D)7. 5. B. 125(5)(D)7. 6. B. 125(5)(D)7. 6. B. 125(5)(D)7. 7. B. 130(3)(B)2. 2. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 2. B. 125(6)(D) 2. B. 125(6)(D) 3. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 2. B. 125(6)(D) 3. B. 125(6)(D) 4. Resultation in the provided for each electrical equipment suitable for hazardous lo | 11, | 8.120(4)(C) | | | Ø | | | | |
| 14. 8.120(5)(A) Is the sewer free from physical connections to a potable water supply system and no water pipes come in contact with a sewer manhole? 15. 8.120(5)(B) Are sewers and manholes located at least 50 feet horizontally from any existing or proposed water supply well, sources, structures? 10.0 PRESSURE SEWERS, GRINDER PUMP, STEP AND STEG SEWER: CHECKLIST REGULATION 16. 8.125(5)(A)1. Does the cleaning velocity of ≥ 2 ft/s happen more than once per day? 17. 8.125(5)(A)2. Is the diameter of the pressure sewer main pipe at least 1.5"? 18. 8.125(5)(B) Are appurtenances compatible with the piping system? 19. 8.125(5)(B) Are appurtenances compatible with the piping system? 19. 8.125(5)(B) Are appurtenances compatible with the piping system? 20. 8.125(5)(C) Do service line pipes have a minimum diameter of 1.25"? 21. 8.125(5)(D) A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence − 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7., 8.130(3)(B)2. Group D, Division 1 location? 26. 8.125(5)(D)8., Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or greater? 28. 8.125(6)(D) 29. Are duplex pumps provided for the design flow of 1,500 gallons or greater? 20. Are duplex pumps provided for the design flow of 1,500 gallons or greater? | 12. | 8.120(4)(E) | manufacturer's recommendations and procedures? | | Ø | | | | |
| pipes come in contact with a sewer manhole? | 13, | 8.120(4)(F) | Do the specifications include a requirement for inspection and testing for manholes? | | | | | | |
| 15. 8.120(5)(B) Are sewers and manholes located at least 50 feet horizontally from any existing or proposed water supply well, sources, structures? 10.0 PRESSURE SEWERS, GRINDER PUMP, STEP AND STEG SEWER CHECKLIST REGULATION YES N/A 16. 8.125(5)(A)1. Does the cleaning velocity of ≥ 2 ft/s happen more than once per day? ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ | 14. | 8.120(5)(A) | | | V | | | | |
| REGULATION YES N/A 16. 8.125(5)(A)1. Does the cleaning velocity of ≥ 2 ft/s happen more than once per day? 17. 8.125(5)(A)2. Is the diameter of the pressure sewer main pipe at least 1.5"? 18. 8.125(5)(B)2. Are appurtenances compatible with the piping system? 19. 8.125(5)(B)2. Are isolation valves located: upstream of major pipe intersections; both sides of stream, bridge and RR crossings; at terminal end of system? 20. 8.125(5)(C) Do service line pipes have a minimum diameter of 1.25"? 21. 8.125(5)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence − 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? | | | Are sewers and manholes located at least 50 feet horizontally from any existing or proposed water supply well, sources, structures? | | Ø | | | | |
| 16. 8.125(5)(A)1. Does the cleaning velocity of ≥ 2 ft/s happen more than once per day? 17. 8.125(5)(A)2. Is the diameter of the pressure sewer main pipe at least 1.5"? 18. 8.125(5)(B) Are appurtenances compatible with the piping system? 19. 8.125(5)(B)2. Are isolation valves located: upstream of major pipe intersections; both sides of stream, bridge and RR crossings; at terminal end of system? 20. 8.125(5)(C) Do service line pipes have a minimum diameter of 1.25"? 21. 8.125(5)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence − 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7., 8.130(3)(B)2. Group D, Division 1 location)? 26. 8.125(5)(D)8., 8.125(5)(D)8., 8.125(5)(D)8. Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater? | 10.0 F | · | RS, GRINDER PUMP, STEP AND STEG SEWER CHECKLIST | | 1 | | | | |
| 17. 8.125(5)(A)2. Is the diameter of the pressure sewer main pipe at least 1.5"? 18. 8.125(5)(B) Are appurtenances compatible with the piping system? 19. 8.125(5)(B)2. Are isolation valves located: upstream of major pipe intersections; both sides of stream, bridge and RR crossings; at terminal end of system? 20. 8.125(5)(C) Do service line pipes have a minimum diameter of 1.25"? 21. 8.125(5)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence – 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8., Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater? | | | | YES | | | | | |
| 18. 8.125(5)(B) Are appurtenances compatible with the piping system? 19. 8.125(5)(B)2. Are isolation valves located: upstream of major pipe intersections; both sides of stream, bridge and RR crossings; at terminal end of system? 20. 8.125(5)(C) Do service line pipes have a minimum diameter of 1.25"? 21. 8.125(5)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence – 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7., 8.130(3)(B)2. Pare units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8., 8.125(5)(D)8., 8.125(5)(D) Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) Are duplex pumps provided for the design flow of 1,500 gallons or greater? | | | | | | | | | |
| 19. 8.125(5)(B)2. Are isolation valves located: upstream of major pipe intersections; both sides of stream, bridge and RR crossings; at terminal end of system? 20. 8.125(5)(C) Do service line pipes have a minimum diameter of 1.25"? 21. 8.125(5)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence − 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7., 8.130(3)(B)2. dre units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8., 8.125(5)(D)8., 8.125(5)(D)8., 8.125(5)(D)8. Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater? | | 38 7 7 7 | | | | | | | |
| bridge and RR crossings; at terminal end of system? 20. 8.125(5)(C) Do service line pipes have a minimum diameter of 1.25"? 21. 8.125(5)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence – 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7., 8.130(3)(B)2. electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8., 8.125(5)(D)8., 8.125(2)(F)6. Surprise of the ground surface of the provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater? | | 100 1110 11 | | | V | | | | |
| 21. 8.125(5)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence – 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7., 8.130(3)(B)2. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8., 8.125(5)(D)8., 8.125(5)(D)8. Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater? | 19. | | bridge and RR crossings; at terminal end of system? | | | | | | |
| 1 residence – 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7., 8.130(3)(B)2. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8., 8.125(5)(D)8., Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater? | 20. | 8.125(5)(C) | Do service line pipes have a minimum diameter of 1.25"? | П | V | | | | |
| 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7., 8.130(3)(B)2. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8., 8.125(2)(F)6. Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater? | 21. | 8.125(5)(D)1.A | | П | Ø | | | | |
| 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7., 8.130(3)(B)2. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8., 8.125(2)(F)6. Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater? | 22. | 8.125(5)(D)1.B | | | V | | | | |
| siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7., 8.130(3)(B)2. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8., 8.125(2)(F)6. Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater? | 23. | 8.125(5)(D)3. | Is there at least 70 gallons of storage in the grinder pump unit? | П | V | | | | |
| 8.130(3)(B)2. electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8., 8.125(2)(F)6. Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater? | 24. | 8.125(5)(D)4. | Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? | П | V | | | | |
| 8.125(2)(F)6. by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater? | | 8.130(3)(B)2. | electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? | П | V | | | | |
| EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater? | 26. | 8.125(2)(F)6. | by providing standby power, storage capacity, or interconnection with another disposal system? | | Ø | | | | |
| 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater? | 27. | 8.125(6)(D) | EDU with 20% of tank volume dedicatied to freeboard and ventillation? | П | | | | | |
| | | | | ΙП | | | | | |

| 11.0 PUMP STATION CHECKLIST | | | | | | | | |
|--|----------------------------|--|---|--------------------------|---|----------|--|--|
| | REGULATION | | | | | YES | N/A | |
| 29. | 8.125(7)(C) | Is the minimum di | ameter sewer main pip | e and service line of S | TEG sewer at least 4"? | 1 | | |
| 30. | 8.130(2)(A) 8.140(2)(B) | Is the pump statio | n designed to withstand | d the 100-year flood? | | V | | |
| 31. | 8.130(3)(A) | Is the dry well completely separate from the wet well and is a suitable and safe means of access provided to each? | | | V | | | |
| 32. | 8.130(3)(B) | If the design flow is 1,500 gpd or more, are there at least 2 pumps or pneumatic ejectors provided? | | | | 1 | | |
| 33 | 8.130(3)(D) | | l outside wet well unles | s integral to a pump or | r its housing? | 1 | | |
| 34. | 8.130(3)(F) 8.140(8)(J) | Do wet and dry we | ells have separate vent | ilation systems? | | ~ | | |
| 35. | 8.130(3)(G) | Does all potable v | ater brought to pump s | stations comply with 8. | 140(7)(D)? | 1 | П | |
| 36. | 8.130(6) | Is an alarm syster | n provided with uninter | rupted power? | | 1 | | |
| 37. | 8.130(7)(A) | | tention of the peak hou ak hourly flow for a des | | ow > 100,000 gpd or 4 hrs | 4 | | |
| 38. | 8.130(7)(B) | Are there indepen | | provided for emergend | cy power capable of starting | V | | |
| 39. | 8.130(8)(A) | | elocity of ≥ 2 ft/s maint | | | 1 | | |
| 40. | 8.130 | Are there complet emergency proced | e operation instructions | s for the pumpting stati | ons provided that include and spare parts that may be | V | | |
| 12.0 S | UCTION LIFT PU | necessary? MP AND SUBMER | SIBLE PUMP STATIO | N CHECKLIST | | l . | L | |
| | REGULATION | | | | | YES | N/A | |
| 41. | 8.130(4) | Are the suction lift | pumps of the self prim | ing or vacuum priming | type? | 1 | | |
| 42. | 8.130(4)(A) | | otal of dynamic suction ead at design operating | | evation and required net or equal to 22 feet? | V | | |
| 43. | 8.130(4)(B) | Are there dual vac | cuum pumps capable o | f removing air from the | suction lift nump? | 1 | | |
| 44. | 8.130(5)(A) | | | - | nout personnel entering, or | | | |
| | | disconnecting any | pipe in the wet well? | | | | | |
| | | | CERTIFICATION STAT | | al comments regarding desig | | | |
| engine | | ngineer's seal, signa | ature and date: | 图 | OF MISSOCIAL CLINT E. | | | |
| Name: Clint Brown, P.E. #2021000264 | | | | | | | | |
| Address: 200 Zahner Place | | | | | | | | |
| City: F | Perryville | | State: Missouri | | ZIP Code: 63775 | | | |
| Telephone Number with Area Code: 573-547-1771 Email:clintb@zahnerinc.com | | | | | | | | |