STATE OF MISSOURI DEPARTMENT OF NATURAL RESOURCES

MISSOURI CLEAN WATER COMMISSION



GENERAL PERMIT for SEWER EXTENSION CONSTRUCTION

The Missouri I	Department of Natu	ral Resources l	hereby issues a j	permit to:

Construction Permit ID: MOGC00826
Title of Project: Bella Terra

Owner: McBride Berra Land Company, LLC

Address: 17415 North Outer 40 Road

Chesterfield, MO 63005

The project will also include general site work appropriate to the scope and purpose of the project and will include all the necessary appurtenances to make a complete and usable collection system. The construction of this project will be in the vicinity of the county below and discharge to Receiving Permit ID below:

County: St. Louis Receiving Permit ID: MO0127949

for the construction of (described construction project):

Bella Terra-Construction of approximately 4,768 lf of 8-inch PVC SDR-35 and 272 lf of 8-inch PVC SDR-26, and 48 l of 8-inch ductile iron piping gravity sewer lines with approximately 32 manholes to serve 99 lots and a design average flow of 36,630 gpd.

Project is in the vicinity of Vogel Rd. at Old Lemay Ferry Rd. in Jefferson County and discharges to an existing system to be treated at MSD Lower Meramec WWTP, MO-0127949. Jay Hoskins, Assistant Director of Engineering, with Metropolitan Sewer District provided an acceptance letter dated December 30, 2024. The continuing authority of the sewer lines and manholes will be Rock Creek Public Sewer District. Don Daniel, District Administrator provided an acceptance letter dated October 24, 2024.

Construction of such proposed facilities shall be in accordance with the provisions of the Missouri Clean Water Law, Chapter 644, RSMo, and regulation promulgated thereunder, or this permit may be revoked by the Department of Natural Resources (Department) As the Department does not examine structural features of design or the efficiency of mechanical equipment, the issuance of this permit does not include approval of these features.

This permit applies only to the construction of water pollution control components; it does not apply to other environmentally regulated areas.

February 10, 2025 Issue Date	John Hoke, Director Water Protection Program				
February 09, 2027 Expiration Date	_				

APPLICABILITY

- 1. This permit authorizes the construction of gravity sewer extensions, force mains, and lift stations. Non-earthen flow equalization storage basins at lift stations and inline storage, which flows back into the lift station or collection system, are also included.
- 2. The Missouri Department of Natural Resources may require a site-specific sewer extension construction permit due to compliance and enforcement actions in accordance with 10 CSR 20-6.010(13)(C).
- 3. This permit does not apply to:
 - A. Earthen storage basins;
 - B. Exempt projects in accordance with 10 CSR 20-6.010(1)(B), 10 CSR 20-6.010(5)(B), and RSMo 644.051 unless requested by the applicant or required by enforcement.

PREREQUISITES:

- 1. The Sewer Extension Construction Permit application, appropriate fee, and documentation in accordance with 10 CSR 20-6.010(5)(G).
- 2. Submit the Sewer Extension Construction Permit application at least sixty (60) days in advance of the start of construction in accordance with 10 CSR 20-6.010(5)(F).
- 3. Submit an electronic copy of the construction permit application and documents to DNR.WPPEngineerSection@dnr.mo.gov in accordance with 10 CSR 20-6.010(5)(G)3.
- 4. The plans and specifications, each signed, sealed, and dated by a professional engineer registered in the State of Missouri in accordance with 10 CSR 20-8 and 10 CSR 20-6.010.
- 5. The Design Certification form, Engineering Report, or Summary of Design, signed, sealed, and dated by a professional engineer registered in the State of Missouri, certifying the design of the system is in accordance with 10 CSR 20-6 and 10 CSR 20-8.
- 6. A statement from the continuing authority, as defined in 10 CSR 20-6.010, accepting the wastewater for treatment and indicating the permitted treatment facility has the available capacity.
- 7. A statement from the continuing authority, as defined in 10 CSR 20-6.010, accepting responsibility for the operation and maintenance of these facilities.

PERMIT CONDITIONS:

- 1. This permit authorizes the activities and scope of work detailed in the plans and specifications submitted with the request.
- 2. The construction must be in accordance with the final plans and specifications received by the Department. Revisions that affect capacity, flow, or system layout must be approved by the Department prior to construction.

PERMIT CONDITIONS: (continued)

- 3. If construction will incorporate minor changes from previously submitted plans and specifications (i.e., changes that do not affect the capacity, flow, or system layout), submit an electronic copy of the as-built plans and specifications in accordance with 10 CSR 20-8.110(11).
- 4. State and Federal Law does not permit bypassing of raw wastewater; therefore, the applicant must take steps to ensure that raw wastewater does not discharge during construction. If a sanitary sewer overflow or bypass occurs, report the appropriate information to the Department's regional office per 10 CSR 20-7.015(9)(E) or through the Online Bypass/SSO Reporting service on the Missouri Gateway for Environmental Management (MoGEM) portal found at https://dnr.mo.gov/data-e-services/missouri-gateway-environmental-management-mogem.

See https://dnr.mo.gov/document-search/missouri-gateway-environmental-management-mogem-frequently-asked-questions-pub2988/pub2988 for more information.

- 5. Protection of drinking water supplies must meet the requirements of 10 CSR 20-8.120(5).
 - A. There shall be no physical connections between a public or private potable water supply system and a sewer or appurtenance that would permit the passage of any wastewater or polluted water into the potable supply.
 - B. Lay sewers at least 50 feet (50') in a horizontal direction from any existing or proposed public water supply well or other water supply sources or structures.
- 6. Position manholes so that the top access is at or above grade level.
- 7. In addition to the requirements for a construction permit, see 10 CSR 20-6.200 for land disturbance requirements to obtain a Missouri State Operating Permit to discharge stormwater. The permit requires Best Management Practices sufficient to control runoff and sedimentation to protect waters of the state. Applicants shall obtain land disturbance permits through the Department's ePermitting system, available online at <a href="https://dnr.mo.gov/data-e-services/water/electronic-permitting-ep

See https://dnr.mo.gov/water/business-industry-other-entities/permits-certification-engineering-fees/stormwater/construction-land-disturbance for more information.

8. Entities applying for funding under 10 CSR 20-4, "Grants and Loans" will need to comply with those requirements in addition to the requirements of 10 CSR 20-8.

PERMIT CONDITIONS: (continued)

9. The Department may require a United States (U.S.) Army Corps of Engineers (COE) permit (404) and a Water Quality Certification (401) or a permit waiver for the activities described in this permit. If construction activity will disturb any land below the ordinary high water mark of Jurisdictional Waters of the U.S., then a 404/401 is required. Fulfillment of these requirements is necessary before the permit is considered valid. Since the COE makes determinations on what is jurisdictional, you must contact the COE to determine permitting requirements. You may call the Department's Operating Permits Section at 573-522-4502 for more information.

See https://dnr.mo.gov/water/business-industry-other-entities/permits-certification-engineering-fees/section-401-water-quality for more information.

- 10. If this project eliminates a wastewater treatment facility under the jurisdiction of the Department, then the applicant shall submit a full closure plan with a Facility Closure Request Form, Form MO 780-2512, to the Department's appropriate regional office for review and approval. In accordance with 10 CSR 20-6.010(12), the closure plan must meet the requirements outlined in Standard Conditions Part III of the Missouri State Operating Permit. Closure shall not commence until the Department approves the submitted closure plan.
- 11. If this project is part of a project to resolve an enforcement action or is receiving funding from the Department, submit a <u>statement of work complete</u> following the completion of construction.
- 12. Applicants may submit, prior to the expiration date of this permit, a written request that additional time is needed in accordance with 10 CSR 20-6.010(5)(H)3.

MISSOURI DEPARTMENT OF NATURAL RESOURCES WATER PROTECTION PROGRAM APPLICATION FOR CONSTRUCTION PERMIT – SEWER EXTENSION

FOR DEPARTMENT USE ONLY							
APP NO.	CP	NO.					
FEE RECEIVED		CHECK NO.					
DATE RECEIVED							

NOTE ► Please Read the accompanying i	nstruction	s before o	ompleting th	is form				
1.0 APPLICATION INFORMATION (Note – I considered incomplete and returned.)	f any of the	questions	in this section	n are answe r	ed NO, this applic	ation may be		
1.1 Is this a Federal/State funded project?	☐ YES	☑ N/A	Funding Ager	ісу:	Pro	oject #:		
1.2 Has the Department of Natural Resource ☐ YES Date of Appro		the propo	osed project's	engineering NO	report*?	□ N/A		
1.3 Is a copy of the appropriate plans* and s	pecification	s* include	d with this apբ	olication?	☑ YES ☐ NO			
If the project is using standard specificati	ons, name	of commu	nity:					
1.4 Is a summary of design* included with th	is applicatio	on? 🗹 🕻	YES NO					
1.5 Is the appropriate fee or JetPay confirmation See Section 7.0	tion include	ed with this	s application?	✓ YES [□NO			
* Must be affixed with a Missouri registered p	rofessional	engineer'	s seal, signatu	re and date.	and the sale was the sale in the sale.			
2.0 PROJECT INFORMATION 2.1 NAME OF PROJECT								
Bella Terra								
ADDRESS	CITY	_		STATE	ZIP CODE	COUNTY		
Vogel Rd. @ Old Lemay Ferry Rd.	Jefferson (MO	63010	Jefferson		
2.2 Legal Description: 1/4, 1/	4,	1/4, Sec	. 36 ,	Γ43N ,	R 5E			
2.3 Project Components (check all that apply ☑ Gravity sewers ☐ Pumping station		ce mains	☐ Alternati	ve sewer sys	stem 🔲 Other (I	Describe below.)		
2.4 PROJECT DESCRIPTION					,			
Approximately 32 Manholes with 5,088 linear	feet of 8" s	anitary ma	iin.					
						•		
2.5 DESIGN INFORMATION A. Population or number of lots to be served	by this exte	ension: 99	Lots - 36,630) gpd				
B. Estimated flow to be contributed by this ex	xtension: [Design Av	erage Flow:	gpd	Design Peak Hour	ly Flow: 6,105 gph		
C. Industrial Wastes: Type:	Flow	/: g	pd					
D. Receiving Sewer: Size: 8 inches	D. Receiving Sewer: Size: 8 inches Capacity: 7,066 gpm							
E. Does this project (check all that apply):								
✓ Connect to an existing treatment plant	Resolve	enforceme	ent issue	Eliminate or	consolidate an exis	sting treatment plant		
F. Estimated number of onsite systems being	g removed:							
G: Estimated costs associated with piping: \$		Estin	nated costs as	ssociated witl	h lift station(s): \$			
3.0 PROJECT OWNER								
McBride Berra Land Company, LLC	T.	TELEPHONE 314-336-0	NUMBER WITH ARI	EA CODE	EMAIL ADDRESS jroth@elitedevse	rvices.com		
ADDRESS	CITY			STATE	ZIP CODE	111000.00111		
17415 North Outer Forty Road	Chesterfie	ld		MO	63005			
CHARTER NUMBER (SECRETARY OF STATE) or REGISTERED	AGENT		,					
	916.9							

4.0 CONTINUING AUTHORITY: A continuing for ensuring compliance with the permit require Continuing authority should be a relatively perwhen needed, of the permitted facility or active hired by the permittee to sample or operate an analytical laboratory. To access the regulatory Water Commission Chapter 6. A continuing a (SoS's) webpage: Missouri Secretary of State required to register with the SoS.	rements a rmanent e ity. A cont nd mainta r requirem uthority's	nd provide of the contity responding authoring authoring the system and regarding mame must be continuous.	continuous standard sible for the control of the continuing the continuing be listed exact.	able oversigongoing oper owever, an e ed time perion authority, 1 ctly as it app	tht of the permitted facility or activity. The pration, maintenance and modernization, entity or individual that is contractually od, such as a certified operator or 0 CSR 20-6.010(2), please visit Clean pears on the Missouri Secretary of State's
NAME	2014		IUMBER WITH ARE	EA CODE	EMAIL ADDRESS
Rock Creek Public Sewer District, Jefferson Co		636-464-33	305		dondaniel@rockcreekpsd.com
ADDRESS 4133 West Outer Road, P.O. Box 1060	CITY Arnold		,	STATE MO .	ZIP CODE 63010
CHARTER NUMBER (SECRETARY OF STATE)					
4.1 Has appropriate continuing authority acce A letter from the continuing authority acceptin different than the original owner of the constru Treatment Facility Acceptance" Form 780-258	g respons uction), or	sibility for cor a prop <u>er</u> ly e	ntinued main executed "Co		
5.0 ENGINEER ENGINEER NAME / COMPANY NAME		TELEPHONE N	IUMBER WITH ARI	EA CODE	EMAIL ADDRESS
The Sterling Company		(314) 487-0		EA CODE	MBoerding@Sterling-eng-sur.com
ADDRESS 5055 New Baumgartner Road	St. Louis			STATE MO	ZIP CODE 63129
6.0 RECEIVING WASTEWATER TREATMEN	NT FACIL	ITY			
NAME Rock Creek Public Sewer District,Jefferson Co	ounty Mo		IUMBER WITH ARI	EA CODE	email address dondaniel@rockcreekpsd.com
MISSOURI STATE OPERATING PERMIT #	ounty wo	COUNTY Jefferson	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		REMAINING CAPACITY (GPD)
6.1 If different from the owner, has a letter becacept the expanded flow or has a properly e MO 780-2584 form been provided? ✓ YES 6.2 A letter from the receiving wastewater treative of YES NO NA 6.3 If the receiving treatment plant or continuing Certificate of Convenience and Necessity has	xecuted C	Continuing A D N/A cility, if differently is regulat	uthority and l	Receiving W	Vastewater Treatment Facility Acceptance uthority, is included with this application.
OPTIONAL QUESTIONS REGARDING MILI	TARY SE	RVICE			
Have you or an immediate family member even U.S. Armed Forces?	er served	in the	☐ Ye	es	□No
If yes, would you like information about militar in Missouri?	y-related	services	☐ Ye	es	□ No
7.0 Application Fee					
✓ Check Number			☐ JetPay C	Confirmation	Number
8.0 PROJECT OWNER: I certify under penalt supervision in accordance with a system designation submitted. Based on my inquiry of the person gathering the information, the information submitted aware there are significant penalties for submit violations. PROJECT OWNER SIGNATURE	gned to as or persor mitted is,	ssure qualifins who mana to the best of	ed personnel age the syste of my knowle	l properly ga em, or those dge and bel	ather and evaluate the information persons directly responsible for lief, true, accurate and complete. I am
PRINTED NAME	\				DATE
Jeremy Roth					10-25-24
TITLE OR CORPORATE POSITION		314-336-02	iumber with ar 248	EA CODE	iroth@elitedevservices.com
Mail completed copy to: MISSOURI DEPARTMENT OF NATURAL RESOURCES WATER PROTECTION PROGRAM PO BOX 176 JEFFERSON CITY, MO 65102-0176			Submit completed electronic copy to: Missouri Department of Natural Resources at DNR.WPPEngineerSection@dnr.mo.gov		

MO 780-1632 (10-22)

SEWER EXTENSION DESIGN CERTIFICATION: Answer all questions yes or N/A. Answer N/A only if the question is clearly not be proposed sewer extension. REGULATION REGULATION 1. 8 ±10(3)(A) Is the design flow based on actual flow data for an existing system? 2. 8 ±10(3)(B) Is the design flow based on actual flow data for an existing system? 3. 8 ±10(9)(B) Is there actually a detailed plan showing tributary area, boundaries, pertinent elevations, or longing plant and proposed facilities? 4. 8 ±20(2) Does the sewer actually detailed plan showing tributary area, boundaries, pertinent elevations, or longing plant and proposed facilities? 5. 8 ±20(3)(A) Is the sewer actually designed to provent damage to the pipe on the plant and proposed facilities? 6. 8 ±20(3)(A) Is all sever pipe constructed with a slope to obtain mean velocities of not less than 2 feet personal? 7. 8 ±20(3)(A) Is all sever pipe constructed with a slope to obtain mean velocities of not less than 2 feet personal? 8 ±20(3)(A) Is a deflection testing specified to ensure no pipe exceeds a deflection of 5% of the insided diameter? 9 ±120(4)(A) Are mean-fole located at the end of each line, at all changes in grade, size or alignment of the line personal of a markole, they are a minimum diameter of 8 linches or larger and deputal to the diameter for pipes < 8°. 8 ±20(4)(E) Are the manufacturer's recommendations and procedures? 10 ±12 ±12 ±12 ±12 ±12 ±12 ±12 ±12 ±12 ±12	9.0 SI	EWER EXTENSIO	N CHECKLIST		
REGULATION REGULATION REGULATION REGULATION Regulated Regulation Regulat				clearly r	not
2. 8.110(3)(B) Are average design flows, peak hourly flows and I&I contributions for new systems calculations? 8.110(9)(B) Is there a detailed pien showing tributary area, boundaries, pertinent elevations, looporaphy, oxisting and proposed facilities? 8.120(2) Does the sewer exclude water from roofs, streets, groundwater from foundation drains and combined wastewater? 8.120(3)(A) Is the pipe installation, embedment and backfill designed to prevent damage to the pipe and its joints? 8.120(3)(A) Is estimated by the pipe constructed with a slope to obtain mean velocities of not less than 2 feet per second? 8.120(3)(A) Is estimated by the pipe constructed with a slope to obtain mean velocities of not less than 2 feet per second? 8.120(3)(B) Is estimated by the pipe covered with at least 38° of soil or sufficiently insulated to prevent freezing? 9. 8.120(4)(A) Is estimated by the end of each line, at all changes in grade, size or alignment and material intersections? 10. 8.120(4)(C) Are membroes at least 2½ inches in diameter with a clear opening of 2½ inches on sewer line larger than 8°? 11. 8.120(4)(C) Are membroes at least 2½ inches in diameter with a clear opening of 2½ inches on sewer line larger than 8°? 12. 8.120(4)(E) Are the end of a lateral instead of a manhole, they are a minimum diameter of 8° inches or larger and equal to the diameter for pipes × 8°? 12. 8.120(4)(E) Are the manholes were used at the end of a lateral instead of a manhole, they are a minimum diameter of 8° inches or larger and equal to the diameter for pipes × 8°? 13. 8.120(5)(A) Is the sewer free from physical connections to a potable water supply system and no water pipes come in contact with a sewer manhole? 14. 8.120(5)(B) Are severes and manholes blocated at least 50 feet horizontally from any existing or proposed water supply system and once per day? 15. 8.125(5)(B) Are appurtenances compatible with the piping system? 16. 8.125(5)(B) Are appurtenances compatible with the piping system? 17. 8.125(5)(D) Are solved and				YES	N/A
aclautated? 1. 8.110(9)(8) 1. Is there a detailed plan showing tributary area, boundaries, pertinent elevations, topography, existing and proposed facilities? 2. Comparison of the server exclude water from roofs, streets, groundwater from foundation drains and combined wastewater? 3. 8.120(3)(A) 3. Is the pipe installation, embedment and backfill designed to prevent damage to the pipe and its joints? 3. 8.120(3)(A) 4. Is the pipe covered with at least 36° of soil or sufficiently insulated to prevent freezing? 5. 8.120(3)(A) 5. Is deflection testing specified to ensure no pipe exceeds a deflection of 5% of the inside dispersion of the street of the server pipe covered with at least 36° of soil or sufficiently insulated to prevent freezing? 5. 8.120(4)(A) 6. 8.120(4)(A) 6. 8.120(4)(A) 6. 8.120(4)(A) 6. 8.120(4)(C) 6. 8.120(6)(C) 6. 8.1	1.	8.110(3)(A)	Is the design flow based on actual flow data for an existing system?	V	
topography, existing and proposed facilities? 1	2.		calculated?	V	
combined wastewater? Social Combined wastewater? Combined with a slope to obtain mean valocities of not less than 2 feet per second? Combined with a slope to obtain mean valocities of not less than 2 feet per second? Combined with a slope to obtain mean valocities of not less than 2 feet per second? Combined with a slope to obtain mean valocities of not less than 2 feet per second? Combined with a slope to obtain mean valocities of not less than 2 feet per second? Combined with a slope to obtain mean valocities of not less than 2 feet per second? Combined with a slope to obtain mean valocities of not less than 2 feet per second? Combined with a slope to obtain mean valocities of not less than 2 feet per second? Combined with a slope to obtain mean valocities of not less than 2 feet per second? Combined with a slope to obtain mean valocities of not less than 2 feet per second in a slope to obtain mean valocities of not less than 2 feet per second in a slope to obtain mean valocities of not less than 2 feet per second in a slope to obtain mean valocities of not less than 2 feet per second in a slope to obtain mean valocities of the slope to obtain valocities of each line slope to obtain mean valocities of the slope to obtain the slope to obtain valocities of each line slope to obtain the addition of each line slope to obtain the additi	3.		topography, existing and proposed facilities?	V	
and its joints? and its joints? Are sported with a slope to obtain mean velocities of not less than 2 feet per second? 7. 8.120(3)(A)2 Is the pipe covered with at least 36° of soil or sufficiently insulated to prevent freezing? 8. 8.120(3)(B) Is deflection testing specified to ensure no pipe exceeds a deflection of 5% of the inside diameter? 9. 8.120(4)(A) Are manholes located at the end of each line, at all changes in grade, size or alignment and at all intersections? 10. 8.120(4)(C) Are manholes located at the end of each line, at all changes in grade, size or alignment and at all intersections? 11. 8.120(4)(C) Are manholes located at the end of each line, at all changes in grade, size or alignment and at all intersections? 12. 8.120(4)(C) Are cleanouts are used at the end of a lateral instead of a manhole, they are a minimum diameter of B inches or larger and equal to the diameter of pipes < 8°? 12. 8.120(4)(F) Are the manholes watertight, constituted and installed in accordance with the manufacture's recommendations and procedures? 13. 8.120(4)(F) Do the specifications include a requirement for inspection and testing for manholes? 14. 8.120(5)(A) Is the sewer free from physical connections to a potable water supply system and no water pipes come in contact with a sewer manhole? 15. 8.120(5)(B) Are sewers and manholes located at least 50 feet horizontally from any existing or proposed water supply well, sources, sincutres? 10. PRESSURE SEWERS, GRINOBER PUMP. STEP AND STEG SEWER CHECKLIST REGULATION 10. 8.125(6)(A)1. Does the cleaning velocity of 2.2 ft/s happen more than once per day? 11. 8.125(6)(B)2. Are apputenances compatible with the piping system? 12. 9. 8.125(6)(B)2. Are spoutenances compatible with the piping system? 12. 1. 8.125(6)(B)2. Are included a provided in the provided for the pressure sewer main pipe at least 1.5°? 12. 8.125(6)(D)1. A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence -1 grinder pumps. 12. 1. 1. 1. 1. 1			combined wastewater?	V	
per second? 1. 8.120(3)(A)2 1. 8 the pipe covered with at least 36° of soil or sufficiently insulated to prevent freezing? 2. 8. 8.120(3)(B) 1. 8 deflection testing specified to ensure no pipe exceeds a deflection of 5% of the inside diameter? 9. 8.120(4)(A) 1. 8.120(4)(C) 1. 9. 8.120(4)(C) 1. 9. 10 the specifications include a requirement for inspection and testing for manholes? 1. 14. 8.120(5)(A) 1. 15 the sewer free from physical connections to a potable water supply system and no water pipes come in contact with a sewer manhole? 1. 8.120(5)(B) 1. 9. 10 persssure sewers, griniber pump, step And Steg Sewer CHECKLIST 1. 8.125(5)(A)(2) 1. 18 the diameter of the pressure sewer main pipe at least 1.5"? 1. 8.125(5)(B) 1. 8.125(5)(C) 1. 9. 0 service line pipes have a minimum diameter of 1.25"? 2. 8.125(5)(D) 1. 8.125(5)(D) 1. 9. 0 simples grinder pump stations sowned, operated and maintained by an approved continuing authority? 2. 8.125(5)(D) 3. 10 simples grinder pump stations of storage in the grinder pump unit? 2. 8.125(5)(D) 3. 8.125(5)(D) 4. 9. 0 simples grinder pump stations sowned, operated and maintained by an approved continuing authority? 2. 8.125(5)(D) 3. 8.125(5)(D) 4. 9. 0 simples grinder pump stations of storage in the grinder pump unit? 2. 8.125(5)(D) 4. 9. 0 simples grinder pump			and its joints?	V	
8. 8.120(3)(B) Is deflection testing specified to ensure no pipe exceeds a deflection of 5% of the inside diameter? 9. 8.120(4)(A) Are manholes located at the end of each line, at all changes in grade, size or alignment and at all intersections? 10. 8.120(4)(C) Are manholes to least 42 inches in diameter with a clear opening of 22 inches on sewer line larger than 8"? 11. 8.120(4)(C) Where cleanouts are used at the end of a lateral instead of a manhole, they are a minimum diameter of 8 inches or larger and egual to the diameter for pipes < 8"? 12. 8.120(4)(E) Are the manholes not surger and egual to the diameter for pipes < 8"? 13. 8.120(4)(F) Do the specifications include a requirement for inspection and testing for manholes? 14. 8.120(5)(A) Is the sewer free from physical connections to a potable water supply system and no water pipes come in contact with a sewer manhole? 15. 8.120(5)(A) Is the sewer free from physical connections to a potable water supply system and no water pipes come in contact with a sewer manhole? 16. 8.125(5)(A)1. Does the cleaning velocity of ≥ 2 ft/s happen more than once per day? 17. 8.125(5)(A)2. Is the diameter of the pressure sewer main pipe at least 1.5"? 18. 8.125(5)(B) Are appurtenances compatible with the piping system? 19. 8.125(5)(B)2. Are isolation valves located: upstream of major pipe intersections; both sides of stream, bridge and RR crossings; at terminal end of system? 20. 8.125(5)(D)1. Bo simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 2 2 2 2 2 2 2		, , , ,	per second?	V	
diameter? diameter diameter				V	
and at all intersections? 10. 8.120(4)(C) Are manholes at least 42 inches in diameter with a clear opening of 22 inches on sewer line larger than 8°? 11. 8.120(4)(C) Where cleanouts are used at the end of a lateral instead of a manhole, they are a minimum diameter of 8 inches or larger and equal to the diameter for pipes < 8°? 12. 8.120(4)(E) Are the manholes watertight. constructed and installed in accordance with the manholes watertight. Constructed and installed in accordance with the manholes watertight. Constructed and installed in accordance with the manholes watertight. Constructed and installed in accordance with the manholes watertight. Constructed and installed in accordance with the manholes watertight. Constructed and installed in accordance with the manholes watertight. Constructed and installed in accordance with the manholes watertight. Constructed and installed in accordance with the manholes watertight. Constructed and installed in accordance with the manholes watertight. Constructed and installed in accordance with the pipes some in contact with a sewer manhole? 12. 8.120(5)(B) S. 120(5)(B) S. 120(5)(B) Pressures and manholes located at least 50 feet horizontally from any existing or proposed water supply well, sources, structures? 12. 8.125(5)(A) Pressures and manholes located at least 50 feet horizontally from any existing or proposed water supply well, sources, structures? 12. 8.125(5)(A) Pressures and manholes located at least 50 feet horizontally from any existing or proposed water supply well, sources, structures? 13. 8.125(5)(B) Pressures and manholes located at least 50 feet horizontally from any existing or proposed water supply well, sources, structures? 14. 8.125(5)(B) Pressures and manholes? 15. 8.125(5)(B) Pressures and manholes? 16. 8.125(5)(B) Pressures and manholes? 17. 8.125(5)(B) Pressures and manholes? 18. 8.125(5)(B) Pressures and manholes? 18. 8.125(5)(B) Pressures and manholes?			diameter?	V	
line larger than 8"?		, , , ,	and at all intersections?	V	
diameter of 8 Inches or larger and equal to the diameter for pipes < 8"? 12. 8.120(4)(E) Are the manholes watertight, constructed and installed in accordance with the manufacturer's recommendations and procedures? 13. 8.120(4)(F) Do the specifications include a requirement for inspection and testing for manholes? 14. 8.120(5)(A) Is the sewer free from physical connections to a potable water supply system and no water pipes come in contact with a sewer manhole? 15. 8.120(5)(B) Are sewers and manholes located at least 50 feet horizontally from any existing or proposed water supply well, sources, structures? 10.0 PRESSURE SEWERS, GRINDER PUMP, STEP AND STEG SEWER CHECKLIST 16. 8.125(5)(A)1. Does the cleaning velocity of ≥ 2 ft/s happen more than once per day? 17. 8.125(5)(A)2. Is the diameter of the pressure sewer main pipe at least 1.5"? 18. 8.125(5)(B) Are appurtenances compatible with the piping system? 19. 8.125(5)(B) Are appurtenances compatible with the piping system? 20. 8.125(5)(C) Do service line pipes have a minimum diameter of 1.25"? 21. 8.125(6)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. pides and RR crossings; at terminal end of system? 22. 8.125(5)(D)1.B Are multiple unit pump stations service only a single equivalent dwelling unit (EDU)? i.e. pides and RR crossings; at terminal end of system? 23. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 24. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 25. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 26. 8.125(5)(D)3. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 27. Are provisions in place to avoid i			line larger than 8"?	V	
manufacturer's recommendations and procedures?			diameter of 8 inches or larger and equal to the diameter for pipes < 8"?		V
14. 8.120(5)(A) Is the sewer free from physical connections to a potable water supply system and no water pipes come in contact with a sewer manhole? 15. 8.120(5)(B) Are sewers and manholes located at least 50 feet horizontally from any existing or proposed water supply well, sources, structures? 10.0 PRESSURE SEWERS, GRINDER PUMP, STEP AND STEG SEWER CHECKLIST REGULATION 16. 8.125(5)(A)1. Does the cleaning velocity of ≥ 2 ft/s happen more than once per day? 17. 8.125(5)(A)2. Is the diameter of the pressure sewer main pipe at least 1.5"? 18. 8.125(5)(B) Are appurtenances compatible with the piping system? 19. 8.125(5)(B) Are isolation valves located; upstream of major pipe intersections; both sides of stream, bridge and RR crossings; at terminal end of system? 20. 8.125(5)(C) Do service line pipes have a minimum diameter of 1.25"? 21. 8.125(5)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence − 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location? 26. 8.125(5)(D)8. Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septit tank (1.000 gallons or greater? 28. 8.125(6)(D) In a STEP system is at least one septit tank (1.000 gallons or greater? 29. Are duplex pumps provided for the design flow of 1			manufacturer's recommendations and procedures?	V	
pipes come in contact with a sewer manhole? Pipes come in contact with sewer structures? Pipes come in contact with sewer manhole? Pipes come in contact with sex success the contact with a success to five and success fiv			i i i i i i i i i i i i i i i i i i i	V	
proposed water supply well, sources, structures? 10.0 PRESSURE SEWERS, GRINDER PUMP, STEP AND STEG SEWER CHECKLIST REGULATION 16. 8.125(5)(A)1. Does the cleaning velocity of ≥ 2 ft/s happen more than once per day? 17. 8.125(5)(A)2. Is the diameter of the pressure sewer main pipe at least 1.5"? 18. 8.125(5)(B) Are appurtenances compatible with the piping system? 19. 8.125(5)(B)2. Are isolation valves located: upstream of major pipe intersections; both sides of stream, bridge and RR crossings; at terminal end of system? 20. 8.125(5)(C) Do service line pipes have a minimum diameter of 1.25"? 21. 8.125(5)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence − 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8. Are provisions in place to avoid interruption of service due to mechanical or power failure by by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater?			pipes come in contact with a sewer manhole?	V	
REGULATION 16. 8.125(5)(A)1. Does the cleaning velocity of ≥ 2 ft/s happen more than once per day? 17. 8.125(5)(A)2. Is the diameter of the pressure sewer main pipe at least 1.5"? 18. 8.125(5)(B) Are appurtenances compatible with the piping system? 19. 8.125(5)(B)2. Are isolation valves located: upstream of major pipe intersections; both sides of stream, bridge and RR crossings; at terminal end of system? 20. 8.125(5)(C) Do service line pipes have a minimum diameter of 1.25"? 21. 8.125(5)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence − 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8. Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater?			proposed water supply well, sources, structures?		
16. 8.125(5)(A)1. Does the cleaning velocity of ≥ 2 ft/s happen more than once per day? 17. 8.125(5)(A)2. Is the diameter of the pressure sewer main pipe at least 1.5"? 18. 8.125(5)(B) Are appurtenances compatible with the piping system? 19. 8.125(5)(B)2. Are isolation valves located: upstream of major pipe intersections; both sides of stream, bridge and RR crossings; at terminal end of system? 20. 8.125(5)(C) Do service line pipes have a minimum diameter of 1.25"? 21. 8.125(5)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence − 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7., 8.130(3)(B)2. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8., 8.125(5)(D)9. Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater?	10.0 F		ERS, GRINDER PUMP, STEP AND STEG SEWER CHECKLIST	LVEO	T NI/A
17. 8.125(5)(A)2. Is the diameter of the pressure sewer main pipe at least 1.5"? 18. 8.125(5)(B) Are appurtenances compatible with the piping system? 19. 8.125(5)(B)2. Are isolation valves located: upstream of major pipe intersections; both sides of stream, bridge and RR crossings; at terminal end of system? 20. 8.125(5)(C) Do service line pipes have a minimum diameter of 1.25"? 21. 8.125(5)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence − 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7. 8.130(3)(B)2. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(6)(D) Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) Are duplex pumps provided for the design flow of 1,500 gallons or greater? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater?	16		Does the cleaning velocity of ≥ 2 ft/s happen more than once per day?	YES	
18. 8.125(5)(B) Are appurtenances compatible with the piping system? 19. 8.125(5)(B)2. Are isolation valves located: upstream of major pipe intersections; both sides of stream, bridge and RR crossings; at terminal end of system? 20. 8.125(5)(C) Do service line pipes have a minimum diameter of 1.25"? 21. 8.125(5)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence – 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8., Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) Are duplex pumps provided for the design flow of 1,500 gallons or greater?					
19. 8.125(5)(B)2. Are isolation valves located: upstream of major pipe intersections; both sides of stream, bridge and RR crossings; at terminal end of system? 20. 8.125(5)(C) Do service line pipes have a minimum diameter of 1.25"? 21. 8.125(5)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence − 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7., 8.130(3)(B)2. Group D, Division 1 location)? 26. 8.125(5)(D)8., 8.125(5)(D)8., 8.125(5)(D)8., 8.125(5)(D)8. Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) Are duplex pumps provided for the design flow of 1,500 gallons or greater? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater?					V
bridge and RR crossings; at terminal end of system? 20. 8.125(5)(C) Do service line pipes have a minimum diameter of 1.25"? 21. 8.125(5)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence – 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7., 8.130(3)(B)2. electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8., 8.125(5)(D)8., 8.125(2)(F)6. Provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater?	18.	8.125(5)(B)	Are appurtenances compatible with the piping system?		
21. 8.125(5)(D)1.A Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence – 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7., 8.130(3)(B)2. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8. Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater?	19.	8.125(5)(B)2.			V
1 residence – 1 grinder pumpt. 22. 8.125(5)(D)1.B Are multiple unit pump stations owned, operated and maintained by an approved continuing authority? 23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7., 8.130(3)(B)2. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8., 8.125(5)(D)8., 8.125(2)(F)6. Provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater?	20.	8.125(5)(C)	Do service line pipes have a minimum diameter of 1.25"?		V
23. 8.125(5)(D)3. Is there at least 70 gallons of storage in the grinder pump unit? 24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7., 8.130(3)(B)2. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8., 8.125(5)(D)8., 8.125(2)(F)6. Provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater?	21.	8.125(5)(D)1.A			V
24. 8.125(5)(D)4. Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7., 8.130(3)(B)2. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8., 8.125(5)(E)6. Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater?	22.	8.125(5)(D)1.B			V
siphoning could occur) that are accessible from the ground surface? 25. 8.125(5)(D)7., 8.130(3)(B)2. Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8., 8.125(2)(F)6. Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation?	23.	8.125(5)(D)3.	Is there at least 70 gallons of storage in the grinder pump unit?		V
8.130(3)(B)2. electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26. 8.125(5)(D)8., 8.125(2)(F)6. Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater?	24.	8.125(5)(D)4.			V
8.125(2)(F)6. by providing standby power, storage capacity, or interconnection with another disposal system? 27. 8.125(6)(D) In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater?		8.130(3)(B)2.	electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)?		V
EDU with 20% of tank volume dedicatied to freeboard and ventillation? 28. 8.125(6)(F) Are duplex pumps provided for the design flow of 1,500 gallons or greater?		8.125(2)(F)6.	by providing standby power, storage capacity, or interconnection with another disposal system?		V
			EDU with 20% of tank volume dedicatied to freeboard and ventillation?		-l <u>-</u>
ACC 700 ACCO (AD 00)		, , , ,	Are duplex pumps provided for the design flow of 1,500 gallons or greater?		V

11.0 P	UMP STATION C	HECKLIST	E				V 1 1
	REGULATION					YES	N/A
29.	8.125(7)(C)	Is the minimum di	ameter sewer main pip	e and service line of S	TEG sewer at least 4"?	Ī	V
30.	8.130(2)(A) 8.140(2)(B)	Is the pump statio	n designed to withstand	d the 100-year flood?			V
31.	8.130(3)(A)	Is the dry well con access provided to		the wet well and is a su	uitable and safe means of		V
32.	8.130(3)(B)	If the design flow provided?	ls 1,500 gpd or more, a	re there at least 2 pum	ps or pneumatic ejectors		V
33	8.130(3)(D)		d outside wet well unles	s integral to a pump or	its housing?		V
34.	8.130(3)(F) 8.140(8)(J)	Do wet and dry we	ells have separate vent	ilation systems?			V
35.	8.130(3)(G)	Does all potable w	vater brought to pump s	stations comply with 8.	140(7)(D)?		V
36.	8.130(6)	ls an alarm syster	n provided with uninter	rupted power?			V
37.	8.130(7)(A)		etention of the peak houseak hourly flow for a des		ow > 100,000 gpd or 4 hrs		V
38.	8.130(7)(B)	Are there indepen		provided for emergence	cy power capable of starting		V
39.	8.130(8)(A)		velocity of ≥ 2 ft/s maint				V
40.	8.130	Are there complet emergency proced necessary?	e operation instructions dures, maintenance sch	for the pumpting stationedules, special tools a	ons provided that include and spare parts that may be		V
12.0 S	UCTION LIFT PU		SIBLE PUMP STATIO	N CHECKLIST		100 M.	13.16.75
	REGULATION				7	YES	N/A
41.	8.130(4)	Are the suction lift	pumps of the self prim	ing or vacuum priming	type?		V
42.	8.130(4)(A)		otal of dynamic suction ead at design operating		evation and required net or equal to 22 feet?		
43.	8.130(4)(B)	Are there dual vac	cuum pumps capable o	f removing air from the	suction lift pump?	П	
44.	8.130(5)(A)	Are there dual vacuum pumps capable of removing air from the suction lift pump? Are submersible pumps readily removable and replaceable without personnel entering, or					
			plpe in the wet well? CERTIFICATION STATE	The state of the s	910 - 1 - 17 - 17 - 18 - 17		V
Misso	uri Professional Er	ngineer's seal, signa	ature and date:	MARKE OF MOSSOUR			
Name	Mike Boe	rding w Baumgartner Ro	oad	E-28643	124		
City:	St. Louis		State: MO		ZIP Code: 63129		
Telep	hone Number with	Area Code: 314-	487-0440	Email: MBoerdin	g@sterling-eng-sur.com		