#### STATE OF MISSOURI DEPARTMENT OF NATURAL RESOURCES

MISSOURI CLEAN WATER COMMISSION



# GENERAL PERMIT for SEWER EXTENSION CONSTRUCTION

The Missouri Department of Natural Resources hereby issues a permit to:

Construction Permit ID:	MOGC00851
Title of Project:	Liberty Commons
Owner:	Liberty Land Strategy, LLC
Address:	17415 N Outer Forty Rd.
	Chesterfield, MO 63005

The project will also include general site work appropriate to the scope and purpose of the project and will include all the necessary appurtenances to make a complete and usable collection system. The construction of this project will be in the vicinity of the county below and discharge to Receiving Permit ID below:

County: St. Charles Receiving Permit ID: MO0028720

for the construction of (described construction project):

Liberty Commons - Construction of approximately 1,443 lf of 8-inch SDR-26 PVC gravity sewer with 11 manholes to serve 41 residential lots with a design average flow of 15,170 gpd.

Project is in the vicinity of Liberty Village Dr and Highway T in Foristell, St. Charles County and discharges to an existing 8-inch gravity sewer with a capacity of 16,338 gpm to be treated at O Fallon WWTP, MO0028720. Chuck Krakosky, St. Charles County Public Water Supply District No. 2 Senior Project Manager, provided a continuing authority and WWTF acceptance letter dated January 23, 2025.

Construction of such proposed facilities shall be in accordance with the provisions of the Missouri Clean Water Law, Chapter 644, RSMo, and regulation promulgated thereunder, or this permit may be revoked by the Department of Natural Resources (Department) As the Department does not examine structural features of design or the efficiency of mechanical equipment, the issuance of this permit does not include approval of these features.

This permit applies only to the construction of water pollution control components; it does not apply to other environmentally regulated areas.

February 11, 2025 Issue Date

John Hoke, Director Water Protection Program

February 10, 2027 Expiration Date

## APPLICABILITY

- 1. This permit authorizes the construction of gravity sewer extensions, force mains, and lift stations. Non-earthen flow equalization storage basins at lift stations and inline storage, which flows back into the lift station or collection system, are also included.
- 2. The Missouri Department of Natural Resources may require a site-specific sewer extension construction permit due to compliance and enforcement actions in accordance with 10 CSR 20-6.010(13)(C).
- 3. This permit does not apply to:
  - A. Earthen storage basins;
  - B. Exempt projects in accordance with 10 CSR 20-6.010(1)(B), 10 CSR 20-6.010(5)(B), and RSMo 644.051 unless requested by the applicant or required by enforcement.

## **PREREQUISITES:**

- 1. The Sewer Extension Construction Permit application, appropriate fee, and documentation in accordance with 10 CSR 20-6.010(5)(G).
- 2. Submit the Sewer Extension Construction Permit application at least sixty (60) days in advance of the start of construction in accordance with 10 CSR 20-6.010(5)(F).
- 3. Submit an electronic copy of the construction permit application and documents to <u>DNR.WPPEngineerSection@dnr.mo.gov</u> in accordance with 10 CSR 20-6.010(5)(G)3.
- 4. The plans and specifications, each signed, sealed, and dated by a professional engineer registered in the State of Missouri in accordance with 10 CSR 20-8 and 10 CSR 20-6.010.
- 5. The Design Certification form, Engineering Report, or Summary of Design, signed, sealed, and dated by a professional engineer registered in the State of Missouri, certifying the design of the system is in accordance with 10 CSR 20-6 and 10 CSR 20-8.
- 6. A statement from the continuing authority, as defined in 10 CSR 20-6.010, accepting the wastewater for treatment and indicating the permitted treatment facility has the available capacity.
- 7. A statement from the continuing authority, as defined in 10 CSR 20-6.010, accepting responsibility for the operation and maintenance of these facilities.

### **PERMIT CONDITIONS:**

- 1. This permit authorizes the activities and scope of work detailed in the plans and specifications submitted with the request.
- 2. The construction must be in accordance with the final plans and specifications received by the Department. Revisions that affect capacity, flow, or system layout must be approved by the Department prior to construction.

#### **PERMIT CONDITIONS: (continued)**

- 3. If construction will incorporate minor changes from previously submitted plans and specifications (i.e., changes that do not affect the capacity, flow, or system layout), submit an electronic copy of the as-built plans and specifications in accordance with 10 CSR 20-8.110(11).
- 4. State and Federal Law does not permit bypassing of raw wastewater; therefore, the applicant must take steps to ensure that raw wastewater does not discharge during construction. If a sanitary sewer overflow or bypass occurs, report the appropriate information to the Department's regional office per 10 CSR 20-7.015(9)(E) or through the Online Bypass/SSO Reporting service on the Missouri Gateway for Environmental Management (MoGEM) portal found at <a href="https://dnr.mo.gov/data-e-services/missouri-gateway-environmental-management-mogem">https://dnr.mo.gov/data-e-services/missouri-gateway-environmental-management-mogem</a>.

See <u>https://dnr.mo.gov/document-search/missouri-gateway-environmental-management-mogem-frequently-asked-questions-pub2988/pub2988</u> for more information.

- 5. Protection of drinking water supplies must meet the requirements of 10 CSR 20-8.120(5).
  - A. There shall be no physical connections between a public or private potable water supply system and a sewer or appurtenance that would permit the passage of any wastewater or polluted water into the potable supply.
  - B. Lay sewers at least 50 feet (50') in a horizontal direction from any existing or proposed public water supply well or other water supply sources or structures.
- 6. Position manholes so that the top access is at or above grade level.
- 7. In addition to the requirements for a construction permit, see 10 CSR 20-6.200 for land disturbance requirements to obtain a Missouri State Operating Permit to discharge stormwater. The permit requires Best Management Practices sufficient to control runoff and sedimentation to protect waters of the state. Applicants shall obtain land disturbance permits through the Department's ePermitting system, available online at <a href="https://dnr.mo.gov/data-e-services/water/electronic-permitting-epermitting.">https://dnr.mo.gov/data-e-services/water/electronic-permitting-epermitting.</a>

See <u>https://dnr.mo.gov/water/business-industry-other-entities/permits-</u> <u>certification-engineering-fees/stormwater/construction-land-disturbance</u> for more information.

8. Entities applying for funding under 10 CSR 20-4, "Grants and Loans" will need to comply with those requirements in addition to the requirements of 10 CSR 20-8.

### **PERMIT CONDITIONS: (continued)**

9. The Department may require a United States (U.S.) Army Corps of Engineers (COE) permit (404) and a Water Quality Certification (401) or a permit waiver for the activities described in this permit. If construction activity will disturb any land below the ordinary high water mark of Jurisdictional Waters of the U.S., then a 404/401 is required. Fulfillment of these requirements is necessary before the permit is considered valid. Since the COE makes determinations on what is jurisdictional, you must contact the COE to determine permitting requirements. You may call the Department's Operating Permits Section at 573-522-4502 for more information.

See <u>https://dnr.mo.gov/water/business-industry-other-entities/permits-certification-engineering-fees/section-401-water-quality</u> for more information.

- 10. If this project eliminates a wastewater treatment facility under the jurisdiction of the Department, then the applicant shall submit a full closure plan with a Facility Closure Request Form, <u>Form MO 780-2512</u>, to the Department's appropriate <u>regional office</u> for review and approval. In accordance with 10 CSR 20-6.010(12), the closure plan must meet the requirements outlined in Standard Conditions Part III of the Missouri State Operating Permit. Closure shall not commence until the Department approves the submitted closure plan.
- 11. If this project is part of a project to resolve an enforcement action or is receiving funding from the Department, submit a <u>statement of work complete</u> following the completion of construction.
- 12. Applicants may submit, prior to the expiration date of this permit, a written request that additional time is needed in accordance with 10 CSR 20-6.010(5)(H)3.

# Rcvd 1/27/25

			FOR DEPA	RTMENT USE ONLY
	MENT OF NATURAL RESOURCES		APP NO.	CP NO.
	<b>FOR CONSTRUCTION PERMIT</b>	· _	FEE RECEIVED	CHECK NO.
	Sign		DATE RECEIVED	
NOTE  Please Read the accom	panying instructions before complet	ing this form		
1.0 APPLICATION INFORMATION considered incomplete and returned	I (Note - If any of the guestions in this	section are ansi	wered NO, this appli	cation may be
1.1 Is this a Federal/State funded p				roject #:
1.2 Has the Department of Natural YES Dat	Resources approved the proposed protection of Approval:	<u>ject's engineeri</u> ☑ NO	ng report*?	□ N/A
1.3 Is a copy of the appropriate pla	ans* and specifications* included with th		YES 🗍 NO	
	specifications, name of community: PV			
1.4 Is a summary of design* includ	ed with this application?			
	y confirmation included with this applica	ation?	NO NO	
	gistered professional engineer's seal, s	ignature and da	ite.	
2.0 PROJECT INFORMATION				
Liberty Commons				
ADDRESS	CITY	STATE	ZIP CODE	COUNTY
	Foristell	Mo	63348	St. Charles
2.2 Legal Description: ¼, № 2.3 Project Components (check all t Gravity sewers Pumpli 2.4 PROJECT DESCRIPTION Approximately 11 Manholes witrh 1,4	that apply): ng stations            Force mains            Alt	, T47N ernative sewer s	, R 1E system ☐ Other (	(Describe below.)
2.3 Project Components (check all t Gravity sewers Pumping 2.4 PROJECT DESCRIPTION	that apply): ng stations            Force mains            Alt			(Describe below.)
2.3 Project Components (check all t	that apply): ng stations            Force mains            Alt			(Describe below.)
2.3 Project Components (check all t Gravity sewers Pumpin 2.4 PROJECT DESCRIPTION Approximately 11 Manholes witrh 1,4 2.5 DESIGN INFORMATION A. Population or number of lots to b	that apply): ng stations	ernative sewer s	system 🗌 Other (	
2.3 Project Components (check all t	that apply): ng stations	ernative sewer s	system 🗌 Other (	
2.3 Project Components (check all t	that apply): ng stations	ernative sewer s	system 🗌 Other (	
2.3 Project Components (check all t Gravity sewers Pumpin 2.4 PROJECT DESCRIPTION Approximately 11 Manholes witrh 1,4 2.5 DESIGN INFORMATION A. Population or number of lots to b B. Estimated flow to be contributed C. Industrial Wastes: Type:	that apply): ng stations	ernative sewer s	system 🗌 Other (	
2.3 Project Components (check all t	that apply): ng stations ☐ Force mains ☐ Alt 443 linear feet of 8" sanitary main be served by this extension: 41 Lots by this extension: Design Average Fl Flow: gpd inches Capacity: 16338 gpm apply):	ernative sewer s	system 🗌 Other ( Design Peak Hou	rly Flow: 2528 gph
2.3 Project Components (check all t	that apply): ng stations ☐ Force mains ☐ Alt 443 linear feet of 8" sanitary main be served by this extension: 41 Lots by this extension: Design Average Fl Flow: gpd inches Capacity: 16338 gpm apply): plant ☐ Resolve enforcement issue	ernative sewer s	system 🗌 Other ( Design Peak Hou	rly Flow: 2528 gph
2.3 Project Components (check all t	that apply): ng stations ☐ Force mains ☐ Alt 443 linear feet of 8" sanitary main be served by this extension: 41 Lots by this extension: Design Average Flow: Flow: gpd inches Capacity: 16338 gpm apply): plant ☐ Resolve enforcement issue ems being removed:	ernative sewer s ow: 15,170gpd	system Dother ( Design Peak Hou	rly Flow: 2528 gph
2.3 Project Components (check all t	that apply): ng stations ☐ Force mains ☐ Alt 443 linear feet of 8" sanitary main be served by this extension: 41 Lots by this extension: Design Average Flow: Flow: gpd inches Capacity: 16338 gpm apply): plant ☐ Resolve enforcement issue ems being removed:	ernative sewer s ow: 15,170gpd	system 🗌 Other ( Design Peak Hou	rly Flow: 2528 gph
2.3 Project Components (check all t	that apply): ng stations ☐ Force mains ☐ Alt 443 linear feet of 8" sanitary main be served by this extension: 41 Lots by this extension: Design Average Fla Flow: gpd inches Capacity: 16338 gpm apply): plant ☐ Resolve enforcement issue ems being removed: piping: \$ Estimated com	ernative sewer s ow: 15,170gpd	system Dother ( Design Peak Hou or consolidate an exi vith lift station(s): \$	rly Flow: 2528 gph
2.3 Project Components (check all the Gravity sewers Pumpin 2.4 PROJECT DESCRIPTION Approximately 11 Manholes witch 1,4 2.5 DESIGN INFORMATION A. Population or number of lots to b B. Estimated flow to be contributed C. Industrial Wastes: Type: D. Receiving Sewer: Size;8 E. Does this project (check all that a Connect to an existing treatment E. Estimated number of onsite syste G: Estimated number of onsite syste G: Estimated costs associated with 3.0 PROJECT OWNER MME berty Land Strategy, LLC	that apply): ng stations ☐ Force mains ☐ Alt 443 linear feet of 8" sanitary main be served by this extension: 41 Lots by this extension: Design Average Flow: gpd inches Capacity: 16338 gpm apply): plant ☐ Resolve enforcement issue ems being removed: piping: \$ Estimated cost TELEPHONE NUMBER W	ernative sewer s	system Dother ( Design Peak Hou or consolidate an exi with lift station(s): \$	rly Flow: 2528 gph
2.3 Project Components (check all t	that apply): ng stations ☐ Force mains ☐ Alt 443 linear feet of 8" sanitary main be served by this extension: 41 Lots by this extension: Design Average Flance Flow: gpd inches Capacity: 16338 gpm apply): plant ☐ Resolve enforcement issue ems being removed: piping: \$ Estimated com	ernative sewer s ow: 15,170gpd	system Dother ( Design Peak Hou or consolidate an exi vith lift station(s): \$	rly Flow: 2528 gph
2.3 Project Components (check all the Gravity sewers Pumpin 2.4 PROJECT DESCRIPTION Approximately 11 Manholes with 1,4 2.5 DESIGN INFORMATION A. Population or number of lots to b B. Estimated flow to be contributed C. Industrial Wastes: Type: D. Receiving Sewer: Size:8 E. Does this project (check all that a Connect to an existing treatment F. Estimated number of onsite system G: Estimated costs associated with 3.0 PROJECT OWNER MME berty Land Strategy, LLC NDRESS	that apply): ng stations ☐ Force mains ☐ Alt 443 linear feet of 8" sanitary main be served by this extension: 41 Lots by this extension: Design Average Flow: gpd inches Capacity: 16338 gpm apply): plant ☐ Resolve enforcement issue ems being removed: piping: \$ Estimated con TELEPHONE NUMBER W CITY Chesterfield	ernative sewer s	Design Peak Hou Design Peak Hou or consolidate an exi with lift station(s): \$	rly Flow: 2528 gph

4.0 CONTINUING AUTHORITY: A continuing authority is a company, business, entity, or person(s) that will be legally responsible for ensuring compliance with the permit requirements and provide continuous stable oversight of the permitted facility or activity. The Continuing authority should be a relatively permanent entity responsible for the ongoing operation, maintenance and modernization, when needed, of the permitted facility or activity. A continuing authority is not, however, an entity or individual that is contractually hired by the permittee to sample or operate and maintain the system for a defined time period, such as a certified operator or analytical laboratory. To access the regulatory requirement regarding continuing authority, 10 CSR 20-6.010(2), please visit Clean Water Commission Chapter 6. A continuing authority's name must be listed exactly as it appears on the Missouri Secretary of State's (SoS's) webpage: Missouri Secretary of State, unless the continuing authority is an individual(s), government entity, or otherwise not required to register with the SoS. NAME TELEPHONE NUMBER WITH AREA CODE EMAIL ADDRESS PWSD#2 636-561-3737 ckrakosky@colestl.com ADDRESS CITY ZIP CODE STATE 100 Water Dr. O'Fallon MO 63366 CHARTER NUMBER (SECRETARY OF STATE) 4.1 Has appropriate continuing authority acceptance been provided as follows: A letter from the continuing authority accepting responsibility for continued maintenance of the sewer (if the continuing authority is different than the original owner of the construction), or a properly executed "Continuing Authority and Receiving Wastewater Treatment Facility Acceptance" Form 780-2584. YES **5.0 ENGINEER** ENGINEER NAME / COMPANY NAME TELEPHONE NUMBER WITH AREA CODE EMAIL ADDRESS The Sterling Company MBoerding@Sterling-eng-sur.com 314-487-0440 ADDRESS CITY STATE ZIP CODE 5055 New Bumbartner Rd St. Louis MO 63129 6.0 RECEIVING WASTEWATER TREATMENT FACILITY NAME TELEPHONE NUMBER WITH AREA CODE EMAIL ADDRESS PWSD 2 St. Charles County Mo 636-561-3737 ckrakosky@colestl.com MISSOURI STATE OPERATING PERMIT # COUNTY REMAINING CAPACITY (GPD) MO-0028720 St. Charles 11.25 MGD 6.1 If different from the owner, has a letter been provided from the receiving treatment facility demonstrating that they agree to accept the expanded flow or has a properly executed Continuing Authority and Receiving Wastewater Treatment Facility Acceptance MO 780-2584 form been provided? YES NO NA 6.2 A letter from the receiving wastewater treatment facility, if different than the continuing authority, is included with this application. YES N/A 6.3 If the receiving treatment plant or continuing authority is regulated by the Public Service Commission (PSC) for sewer activities, a Certificate of Convenience and Necessity has been received? Yes - Date: □ No ΠN/A **OPTIONAL QUESTIONS REGARDING MILITARY SERVICE** Have you or an immediate family member ever served in the Yes No No **U.S. Armed Forces?** If yes, would you like information about military-related services Yes in Missouri? 7.0 Application Fee Check Number JetPay Confirmation Number 8.0 PROJECT OWNER: I certify under penalty of law this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate and complete. I am aware there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations. PROJECT OWNER PRINTED NAME DATE Miller 24/2025 hristian TITLE OR CORPORATE POSITION TELEPHONE NUMBER WITH AREA CODE EMAIL ADDRES Project Manager 314-682-9604 cmiller@elitedevservices.com>. Mail completed copy to: Submit completed electronic copy to: MISSOURI DEPARTMENT OF NATURAL RESOURCES Missouri Department of Natural Resources WATER PROTECTION PROGRAM at DNR.WPPEngineerSection@dnr.mo.gov **PO BOX 176** JEFFERSON CITY, MO 65102-0176

MO 780-1632 (10-22)

SEV	VER EXTENSION I	DESIGN CERTIFICATION: Answer all questions yes or N/A. Answer N/A only if the question is of the proposed sewer extension.	clearly	not
appi	REGULATION		YES	N/A
1.	8.110(3)(A)	Is the design flow based on actual flow data for an existing system?		
2.	8.110(3)(B)	Are average design flows, peak hourly flows and I&I contributions for new systems calculated?		
3.	8.110(9)(B)	Is there a detailed plan showing tributary area, boundaries, pertinent elevations, topography, existing and proposed facilities?		
4.	8.120(2)	Does the sewer exclude water from roofs, streets, groundwater from foundation drains and combined wastewater?		E
5.	8.120(3)(A)	Is the pipe installation, embedment and backfill designed to prevent damage to the pipe and its joints?		C
6.	8.120(3) (A)1	Is all sewer pipe constructed with a slope to obtain mean velocities of not less than 2 feet per second?		
7.	8.120(3)(A)2	Is the pipe covered with at least 36" of soil or sufficiently insulated to prevent freezing?		╎┍
8.	8.120(3)(B)	Is deflection testing specified to ensure no pipe exceeds a deflection of 5% of the inside diameter?		
9.	8.120(4)(A)	Are manholes located at the end of each line, at all changes in grade, size or alignment and at all intersections?		С
10.	8.120(4)(C)	Are manholes at least 42 inches in diameter with a clear opening of 22 inches on sewer line larger than 8"?		E
11.	8.120(4)(C)	Where cleanouts are used at the end of a lateral instead of a manhole, they are a minimum diameter of 8 inches or larger and equal to the diameter for pipes < 8"?		
12.	8.120(4)(E)	Are the manholes watertight, constructed and installed in accordance with the manufacturer's recommendations and procedures?		Ē
13.	8.120(4)(F)	Do the specifications include a requirement for inspection and testing for manholes?		Г
14.	8.120(5)(A)	Is the sewer free from physical connections to a potable water supply system and no water pipes come in contact with a sewer manhole?		
15.	8.120(5)(B)	Are sewers and manholes located at least 50 feet horizontally from any existing or proposed water supply well, sources, structures?		
10.0	PRESSURE SEWE	RS, GRINDER PUMP, STEP AND STEG SEWER CHECKLIST		
16.	REGULATION		YES	N/A
	8.125(5)(A)1.	Does the cleaning velocity of $\geq 2$ ft/s happen more than once per day?		
17.	8.125(5)(A)2.	Is the diameter of the pressure sewer main pipe at least 1.5"?		Ŀ
18.	8.125(5)(B)	Are appurtenances compatible with the piping system?		L.
19.	8.125(5)(B)2.	Are isolation valves located: upstream of major pipe intersections; both sides of stream, bridge and RR crossings; at terminal end of system?		V
20.	8.125(5)(C)	Do service line pipes have a minimum diameter of 1.25"?		2
21.	8.125(5)(D)1.A	Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence – 1 grinder pumpt.		V
2.	8.125(5)(D)1.B	Are multiple unit pump stations owned, operated and maintained by an approved continuing authority?		•
23.	8.125(5)(D)3.	Is there at least 70 gallons of storage in the grinder pump unit?		•
.4.	8.125(5)(D)4.	Do grinder pump stations have shutoff valves, check valves and anti-siphon valves (where siphoning could occur) that are accessible from the ground surface?		<u>د</u>
5.	8.125(5)(D)7., 8.130(3)(B)2.	Are units serviceable and replaceable under wet conditions without electrical hazard and is electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)?		
6.	8.125(5)(D)8., 8.125(2)(F)6.	Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity, or interconnection with another disposal system?		V
7.	8.125(6)(D)	In a STEP system is at least one septic tank (1,000 gallons or more) provided for each EDU with 20% of tank volume dedicatied to freeboard and ventillation? Are duplex pumps provided for the design flow of 1,500 gallons or greater?		2

.....

÷

1.1

11.0	PUMP STATION C	HECKLIST					
	REGULATION					YES	N/A
29.	8.125(7)(C)	Is the minimum o	diameter sewer main pi	pe and service line of §	STEG sewer at least 4"?		
30.	8.130(2)(A) 8.140(2)(B)	Is the pump station designed to withstand the 100-year flood?					
31.	8.130(3)(A)	Is the dry well completely separate from the wet well and is a suitable and safe means of access provided to each?					
32.	8.130(3)(B)	If the design flow is 1,500 gpd or more, are there at least 2 pumps or pneumatic ejectors provided?					
33	8.130(3)(D)	Are valves located outside wet well unless integral to a pump or its housing?					
34.	8.130(3)(F) 8.140(8)(J)	Do wet and dry wells have separate ventilation systems?					
35.	8.130(3)(G)	Does all potable	water brought to pump	stations comply with 8	3.140(7)(D)?		
36.	8.130(6)		m provided with uninte			台	
37.	8.130(7)(A)	Is there 2 hours retention of the p	etention of the peak ho eak hourly flow for a de	ourly flow for a design f	flow > 100,000 gpd or 4 hrs		
38.	8.130(7)(B)	Are there indepe	retention of the peak hourly flow for a design flow < 100,000 gpd? Are there independent utility substations provided for emergency power capable of starting and operating the pump station at its rated capacity?				
39.	8.130(8)(A)	Is the force main	velocity of ≥ 2 ft/s main	italned?			
40.	8.130	Are there comple	te operation instruction	is for the pumpting stat	tions provided that include	╞╘┙	
10 -		necessary?			and spare parts that may be		
12.0.5		MP AND SUBMER	RSIBLE PUMP STATIC	ON CHECKLIST			1. Pr. 1
41.	REGULATION	Are the second second	P 13 5.4 5			YES	N/A
	8.130(4)		ft pumps of the self prin				
42.	8.130(4)(A)	positive suction h	otal of dynamic suction lead at design operatin	) lift at the "pump off" e g conditions less than	levation and required net or equal to 22 feet?		V
43.	8.130(4)(B)	Are there dual va	cuum pumps capable d	of removing air from the	e suction lift oump?	+	
44.	8.130(5)(A)	Are submersible	pumps readily removat		hout personnel entering, or		
12.0 5	EMED EVTENIEK	disconnecting an	y pipe in the wet well? CERTIFICATION STA				
engine		gineer's seal, signa	ature and date:		MICHAEL BOEDDING E-28643	25	
Name: Addres					116.4		
City: State:			State:		ZIP Code:		
Teleph	one Number with	Area Code:		Email:			

.....

1.1.1

11464 - NUD